

VENTILATOR SYSTEM WITH MULTIPLE AIRFLOW CONTROL LUMENS

DOCUMENT ID **DATE**
US 20220072250 A1 **PUBLISHED**
2022-03-10

INVENTOR INFORMATION

NAME	CITY	STATE	ZIP CODE	COUNTRY
Kiljanek; Lukasz R.	Chesapeake Beach	MD	N/A	US

APPLICANT INFORMATION

NAME	CITY	STATE	ZIP CODE	COUNTRY
Kiljanek; Lukasz R.	Chesapeake Beach	MD	N/A	US

AUTHORITY	TYPE
N/A	N/A

APPLICATION NO	DATE FILED
17/345994	2021-06-11

DOMESTIC PRIORITY (CONTINUITY DATA)

us-provisional-application US 63075327 20200908

us-provisional-application US 63075555 20200908

us-provisional-application US 63077037 20200911

US CLASS CURRENT:

[1/1](#)

CPC CURRENT

TYPE	CPC	DATE
CPCI	A 61 M 16/0463	2013-01-01
CPCI	A 61 M 16/106	2014-02-04
CPCI	A 61 M 16/042	2014-02-04
CPCI	A 61 M 16/0404	2014-02-04
CPCI	A 61 M 16/208	2013-01-01
CPCI	A 61 M 16/12	2013-01-01
CPCI	A 61 M 16/0486	2014-02-04
CPA	A 61 M 2202/0225	2013-01-01

APPLICANT GROUP

Kiljanek; Lukasz R. Chesapeake Beach MD US

Abstract

Ventilator system with multiple inspiratory lumens is provided. The inspiratory lumens are configured so that separate inspiratory lumens provide inspiratory gas mixtures to separate portions of a patient's airways, for instance to separate lungs and/or bronchi. The ventilator system can include one or more expiratory lumens to evacuate expiratory gases from airways. The use of separate inspiratory lumen(s), with expiratory lumen(s), allows for functional separation of structural portions of the lungs, and maintenance of continuous or almost continuous flow through at least part of respiratory cycle via inspiratory and expiratory lumens. This can further reduce dead space and clear suspended therein diseases causative agents with improvement in outcomes, reduce risk of cross-contamination or cross-infection between different parts of airways, for example such as cross-infection from one lung lobe to another lobe or. The ventilator system allows for independent titration of PEEP, pCO₂ and pO₂ with no need for permissive hypercapnia.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims the priority benefit of U.S. provisional application No. 63/075,327 filed Sep. 8, 2020 and entitled "Methods and Devices to Decrease Functional and Anatomical Dead Space and Improve Outcomes in Severe, Infectious Process Involving Lungs;" U.S. provisional application No. 63/075,555 filed Sep. 8, 2020 and entitled "Methods and Devices to Decrease Functional and Anatomical Dead Space and Improve Outcomes in Severe, Infectious Process Involving Lungs;" and U.S. provisional application No. 63/077,037 filed Sep. 11, 2020 and entitled "Methods and Devices to Decrease Functional and Anatomical Dead Space and Improve Outcomes in Severe, Infectious Process Involving Lungs;" the disclosures of which are all hereby incorporated by reference in their entireties.

BACKGROUND

1. Field

[0002] The present teachings are generally related to ventilator systems. More specifically, the present teachings relate to ventilator systems with multiple inspiratory lumens configured so that separate inspiratory lumens provide gas to different portions of a patient's airways, reducing dead space in the patient's airways and reducing risk of cross-infection between the different portions of the patient's airways.

2. Description of the Related Art

[0003] A ventilator is life support machine that can be used to assist a patient with breathing. A ventilator generally includes a tube that is inserted into the patient's mouth. A ventilator mechanically provides air into the patient's airways. A ventilator may be used, for example, when a patient is having trouble breathing on their own due to an infection, an injury, a disability, and/or another medical condition.

[0004] Dead space represents a volume of ventilated air in a patient's airways that does not participate in gas exchange. For instance, dead space can represent a volume of air that remains in the patient's airways even after an exhalation, and that is thus not replaced by fresh air from the patient's next

inhalation. The average dead space in a healthy individual's airways represent 26% of tidal volume. Respiratory conditions, such as diseases, injuries, or disabilities, can all increase dead space in the airways of patients, for example by impairing a patient's ability to inhale and/or exhale. Disease-causative agents (DCAs) can move throughout dead space in a patient's airways, which can cause infections or other diseases to spread throughout the patient's airways. DCAs suspended in dead space are generally not accessible to inhaled medications or to the human body's defense systems (e.g., immune cells and antibodies).

SUMMARY

[0005] Techniques and systems are described herein for reducing dead space and increasing clearance of dead space in a patient's airways using a ventilator apparatus with multiple inspiratory lumens. The inspiratory lumens are configured so that separate inspiratory lumens provide air to separate lungs and/or bronchi. The ventilator apparatus can also include one or more expiratory lumens to receive and/or evacuate expiratory gases from the patient's airways. The use of separate inspiratory lumens, together with one or more expiratory lumens, can reduce dead space in the patient's airways and increase the clearance of dead space. The use of separate inspiratory lumens, together with one or more expiratory lumens, can thus reduce risk of cross-infection and/or cross-contamination between different parts of the patient's airways, such as cross-infection from one lung to the other and/or cross-infection between bronchi and reinfection of already recovered portions of patient's lungs, with the DCAs suspended in dead space.

[0006] In one example, an apparatus for airflow control is provided. The apparatus includes a first inspiratory lumen that is configured to receive a first inspiratory gaseous volume and to provide the first inspiratory gaseous volume to a first portion of an airway of a patient while the first inspiratory lumen is at least partially inserted into the airway. The apparatus includes a second inspiratory lumen that is configured to receive a second inspiratory gaseous volume and to provide the second inspiratory gaseous volume to a second portion of the airway while the second inspiratory lumen is at least partially inserted into the airway. The apparatus includes one or more expiratory lumens that are configured to evacuate an expiratory gaseous volume from at least one of the first portion of the airway and from the second portion of the airway while the one or more expiratory lumens are at least partially inserted into the airway.

[0007] In another example, a method for airflow control is provided. The method includes receiving a first inspiratory gaseous volume into a first inspiratory lumen. The method includes providing the first inspiratory gaseous volume to a first portion of an airway of a patient using the first inspiratory lumen while the first inspiratory lumen is at least partially inserted into the airway. The method includes receiving a second inspiratory gaseous volume into a second inspiratory lumen. The method includes providing the second inspiratory gaseous volume to a second portion of the airway using the second inspiratory lumen while the second inspiratory lumen is at least partially inserted into the airway. The method includes evacuating an expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens while the one or more expiratory lumens are at least partially inserted into the airway.

[0008] In another example, an apparatus for airflow control is provided. The apparatus includes means for receiving a first inspiratory gaseous volume into a first inspiratory lumen. The apparatus includes means for providing the first inspiratory gaseous volume to a first portion of an airway of a patient using the first inspiratory lumen while the first inspiratory lumen is at least partially inserted into the airway. The apparatus includes means for receiving a second inspiratory gaseous volume into a second inspiratory lumen. The apparatus includes means for providing the second inspiratory gaseous volume to a second portion of the airway using the second inspiratory lumen while the second inspiratory lumen is at least partially inserted into the airway. The apparatus includes means for evacuating an expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens while the one or more expiratory lumens are at least partially inserted into the airway.

[0009] In another example, a non-transitory computer-readable medium is provided having stored thereon instructions that, when executed by one or more processors, cause the one or more processors to: receive a first inspiratory gaseous volume into a first inspiratory lumen; provide the first inspiratory gaseous volume to a first portion of an airway of a patient using the first inspiratory lumen while the first inspiratory lumen is at least partially inserted into the airway; receive a second inspiratory gaseous volume into a second inspiratory lumen; provide the second inspiratory gaseous volume to a second portion of the airway use the second inspiratory lumen while the second inspiratory lumen is at least partially inserted into the airway; and evacuate an expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens while the one or more expiratory lumens are at least partially inserted into the airway.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0010] FIG. 1 is a conceptual diagram illustrating a front view of a ventilator system connected to a patient;

[0011] FIG. 2 is a conceptual diagram illustrating a side view of a ventilator system connected to a patient;

[0012] FIG. 3 is a conceptual diagram illustrating a trachea connected to a left lung and a right lung;

[0013] FIG. 4A is a conceptual diagram illustrating part of a ventilator system with an endotracheal tube (ETT) in a trachea providing inspiratory gas into a diseased right lung and a healthy left lung.

[0014] FIG. 4B is a conceptual diagram illustrating part of the ventilator system of FIG. 4A with the endotracheal tube (ETT) evacuating expiratory gas that includes disease-causative agents (DCAs) from the diseased right lung and the healthy left lung.

[0015] FIG. 4C is a conceptual diagram illustrating part of the ventilator system of FIGS. 4A-4B with the endotracheal tube (ETT) providing inspiratory gas that spreads disease-causative agents (DCAs) to more of the diseased right lung and newly introduces the DCAs into the newly-diseased left lung;

[0016] FIG. 4D is a conceptual diagram illustrating an example of the ventilator systems of FIGS. 4A-4C with an adapter added on one side of the balloon and another adapter added on the other side of the balloon;

[0017] FIG. 4E is a conceptual diagram **400E** illustrating a cross-section of a micro-filter adapter;

[0018] FIG. 4F is a conceptual diagram **400F** illustrating a cross-section of an airflow rerouting adapter;

[0019] FIG. 5A is a conceptual diagram illustrating part of a ventilator system with an endotracheal tube (ETT) that includes an expiratory lumen that evacuates expiratory gas, a left inspiratory lumen that provides inspiratory gas to the left primary bronchus and left lung, and a right inspiratory lumen that provides inspiratory gas to the right primary bronchus and right lung;

[0020] FIG. 5B is a conceptual diagram illustrating part of the ventilator system of FIG. 5A where the right lung is diseased and the left lung is healthy;

[0021] FIG. 5C is a conceptual diagram illustrating part of a ventilator system with an endotracheal tube (ETT) that includes a left expiratory lumen that evacuates expiratory gas from a left primary bronchus and left lung, a right expiratory lumen that evacuates expiratory gas from a right primary bronchus and right lung, a left inspiratory lumen that provides inspiratory gas to the left primary bronchus and left lung, and a right inspiratory lumen that provides inspiratory gas to the right primary bronchus and right lung;

[0022] FIG. 5D is a conceptual diagram illustrating part of a ventilator system with an endotracheal tube (ETT) that includes an inspiratory lumen that provides inspiratory gas, a left expiratory lumen that

evacuates expiratory gas from the left primary bronchus and left lung, and a right expiratory lumen that evacuates expiratory gas from the right primary bronchus and right lung;

[0023] FIG. 6 is a conceptual diagram illustrating part of a ventilator system with an endotracheal tube (ETT) that includes an expiratory lumen that evacuates expiratory gas, a left inspiratory lumen that provides inspiratory gas, and a right inspiratory lumen that provides inspiratory gas;

[0024] FIG. 7A is a conceptual diagram illustrating a cross-section of an endotracheal tube (ETT) that includes an expiratory lumen that evacuates expiratory gas, a left inspiratory lumen that provides inspiratory gas, and a right inspiratory lumen that provides inspiratory gas;

[0025] FIG. 7B is a conceptual diagram illustrating a cross-section of a tube that includes a first lumen and a second lumen separated by a membrane;

[0026] FIG. 8A is a graph diagram illustrating inspiratory flow, expiratory flow, and pressure changes over time in a ventilator system according to a first illustrative example;

[0027] FIG. 8B is a graph diagram illustrating inspiratory flow, expiratory flow, and pressure changes over time in a ventilator system according to a second illustrative example;

[0028] FIG. 8C is a graph diagram illustrating inspiratory flow, expiratory flow, and pressure changes over time in a ventilator system according to a third illustrative example;

[0029] FIG. 8D is a graph diagram illustrating inspiratory flow, expiratory flow, and pressure changes over time in a ventilator system according to a fourth illustrative example;

[0030] FIG. 8E is a graph diagram illustrating inspiratory flow, expiratory flow, and pressure changes over time in a ventilator system according to a fifth illustrative example;

[0031] FIG. 9A is a block diagram illustrating an architecture of an exemplary ventilator system that includes an inspiratory control system that provides inspiratory gas to a left lung and a right lung through a left inspiratory lumen and a right inspiratory lumen, and an expiratory control system that evacuates expiratory gas from the left lung and the right lung through one or more expiratory lumens;

[0032] FIG. 9B is a block diagram illustrating an architecture of an exemplary ventilator system that includes a left inspiratory control system that provides inspiratory gas to a left lung through a left inspiratory lumen, a right inspiratory control system that provides inspiratory gas to a right lung through a right inspiratory lumen, a left expiratory control system that evacuates expiratory gas from a left lung through a left expiratory lumen, and a right expiratory control system that evacuates expiratory gas from a right lung through a right expiratory lumen;

[0033] FIG. 10 is a flow diagram illustrating exemplary operations for airflow control; and

[0034] FIG. 11 is a block diagram of an exemplary computing device that may be used to implement some aspects of the technology.

DETAILED DESCRIPTION

[0035] A ventilator is a life support machine that can be used to assist a patient with breathing. A ventilator generally includes an endotracheal tube that is inserted via mouth into the patient's trachea. A ventilator can mechanically provide an inspiratory gas into the patient's airways. A ventilator can mechanically evacuate an expiratory gas from the patient's airways. A ventilator may be used, for example, when a patient is having trouble breathing on their own due to an infection, an injury, a disease, a physical handicap, a physical disability, weakness, sedation, use of paralyzing anesthetics, another medical condition, another physical condition, another anatomical condition, or a combination thereof.

[0036] A patient's lungs and airways can become infected with and/or otherwise affected by a disease-causative agent (DCA). DCAs can include, for example, bacteria, fungi, viruses (e.g., virions, viral agents), parasites, protozoa, helminths, prions, toxins, synthetic toxicants, physical contaminants, chemical contaminants, biological contaminants, radiological contaminants, portions of a patient's immune system in patients that have an autoimmune disease, other antigens or hazards, or combinations thereof. Diseases can include infections, injuries, poisonings, disabilities, disorders, syndromes, infections, isolated symptoms, deviant behaviors, atypical, aberrant and pathologic variations of structure and function, or combinations thereof. Certain types of DCAs can be referred to as infection agents, toxins, antigens, antibodies, cells, prions, infection vectors, disease agents, disease vectors, microorganisms, microbes, pathogens, germs, contaminants, chemicals, or combinations thereof.

[0037] Dead space represents a volume of ventilated air in a patient's airways that does not participate in alveolar gas exchange. For instance, dead space can represent a volume of air that remains in the patient's airways even after an exhalation. The average dead space in a healthy individual's airways represent 26% of tidal volume. Tidal volume represents the volume of gas inspired with breath. Average tidal volume is 450 milliliters (ml), so average dead space is 117 milliliters (mL). Diseases, such as respiratory diseases, and pathologic conditions, such as being ventilated on mechanical ventilator with high respiratory rate, as commonly required per treatment protocols, can cause a significant increase in dead space in the airways of patients, for example because a patient's ability to inhale and/or exhale may be impaired. DCAs can freely move, or float, or move throughout dead space in a patient's airways. This movement of DCAs within the dead space can facilitate spreading of the diseases from contaminated to uncontaminated yet portions of respiratory system, also to uncontaminated portions of lungs. DCAs suspended in the dead space are generally not accessible to other than inhaled medications, circulating antibodies, immune cells, or other immune response mechanisms of the patient.

[0038] The SARS-CoV-2 virus is an example of a disease-causative agent (DCA). COVID-19 is an example of a disease that can be caused by the SARS-CoV-2 virus. During the COVID-19 pandemic, ventilators have been used to treat most severely sick patients with COVID-19 infections. According to some news reports during the COVID-19 pandemic, some patients' conditions appeared to worsen after the patient was connected to a ventilator. In some examples, the disease spread throughout a patient's airways after the patient was connected to a ventilator. In some cases, patients can get reinfected with COVID-19, sometimes weeks after their first COVID-19 infection. In some patients, portions of the lungs can get reinfected with COVID-19 while the patient is on a ventilator, even during a first-in-lifetime COVID-19 infections. Furthermore, in at least some patients, intravenous provision of antibodies can be beneficial only before patient present significant lungs disease and before patients end up on ventilator. Once such a patient is on a ventilator, antibodies provide limited effect, for instance because the dead space in the patient's lungs is already filled with DCAs, the antibodies cannot reliably reach the DCAs suspended in the dead space, and the effectiveness of such therapies is lost.

[0039] Systems and techniques are described herein that minimize or reduce the risk of infection and/or reinfection of patients' lungs (and/or other portions of the patients' airways) while patients are on a ventilator by clearing and reducing the dead space in the patients' lungs. Once a patient ends up on a ventilator, the only remaining treatments may have very limited effectiveness, so any improvements to the functioning of the ventilator, such as improved ability to clear DCAs from the patient's airways mechanically and/or to reduce dead space, may significantly improve patient outcomes and save lives. By preventing patients' conditions from getting significantly worse, improvements to ventilators can also expand the treatments that will be available and effective for patients, for example allowing antibody treatments to be effective for a longer period of time for COVID-19 patients. Such improvements can also help patients with any lung disease or airway issue caused by any DCA, even empirically caused by unknown DCAs.

[0040] FIG. 1 is a conceptual diagram **100** illustrating a front view of a ventilator system connected to a patient **105**. The airway of the patient **105** includes at least the patient **105**'s mouth **110**, larynx **112**, trachea **115**, bronchi (not pictured), left lung **130**, and right lung **135**. The ventilator system includes an

endotracheal tube (ETT) **120** that is inserted into the mouth **110** of the patient **105** and into the patient **105**'s trachea **115**, alongside the patient **105**'s larynx **112**. The ETT **120** ends in a tip **125** of the ETT **120** within the trachea **115**. Additional dashed tubes are illustrated extending beyond the tip **125** of the ETT **120** partway into the left lung **130** and right lung **135**, and may represent inspiratory lumens (e.g., left inspiratory lumen **220**, right inspiratory lumen **225**) and/or expiratory lumens (e.g., left expiratory lumen **520**, right expiratory lumen **525**) as discussed further herein. The ETT **120** is kept in position through a patient interface **149**, which can be mechanically coupled to the patient **105** using one or more coupling mechanisms of the patient interface **149**, such as one or more rubber bands, one or more clamps, one or more clips, one or more fasteners, or a combination thereof. The ETT **120** provides inspiratory gas (e.g., clean air) to the left lung **130** and right lung **135** of the patient. The ETT **120** receives and evacuates expiratory gas (e.g., exhaled air) from the left lung **130** and right lung **135** of the patient **105**.

[0041] The ventilator system includes a pneumatic system **140** with a pressurizer **145** (e.g., compressor and/or decompressor), an inspiratory flow control system **150**, and an expiratory flow control system **155**. The inspiratory flow control system **150** provides flow of inspiratory gas(es) from one or more inspiratory gas sources **160**, through an inspiratory tube **152**, through a first fitting **147** (e.g., a wye-fitting), through a second fitting **148**, through a patient interface **149**, through the ETT **120**, and/or into the airway of the patient **105**. In some examples, the inspiratory flow control system **150** can mix inspiratory gases from the one or more inspiratory gas sources **160**. For example, the one or more inspiratory gas sources **160** can include an oxygen (O.sub.2) gas source, a nitrogen (N) gas source, a carbon dioxide (CO.sub.2) gas source, an argon (Ar) gas source, one or more gas sources for one or more drugs (in gaseous and/or aerosolized form), one or more gas sources for one or more other elemental gases, one or more gas sources for one or more other molecular gases, an pre-mixed atmospheric gas source, or a combination thereof. For example, the inspiratory flow control system **150** can mix oxygen (O.sub.2), nitrogen (N), carbon dioxide (CO.sub.2), argon (Ar), one or more drugs (in gaseous and/or aerosolized form), one or more one or more other elemental gases, one or more other molecular gases, a pre-mixed atmospheric gas source, or a combination thereof.

[0042] Even though it may seem counter-intuitive to include carbon dioxide (CO.sub.2) in the inspiratory gas mixture, it may be useful to include carbon dioxide (CO.sub.2) in the inspiratory gas mixture when carbon dioxide (CO.sub.2) is being evacuated in excess from the patient **105**'s airways, as lack of carbon dioxide (CO.sub.2) can increase alkalinity, pushing pH too high, and can cause negative effects such as alkalosis. Some types of ventilator systems, such as those illustrated in FIGS. 4A-4C, might not evacuate enough carbon dioxide (CO.sub.2) to necessitate or benefit significantly from inclusion of carbon dioxide (CO.sub.2) in the inspiratory gas mixture. Other types of ventilator systems that regularly and actively evacuate expiratory airflow, such as those illustrated in or discussed with respect to FIGS. 2, 5A-5C, 6, 7A-7B, 8A-8E, 9A-9B, and 10, can evacuate enough carbon dioxide (CO.sub.2) that inclusion of carbon dioxide (CO.sub.2) in the inspiratory gas mixture may be necessary and/or significantly beneficial to reduce alkalinity and prevent alkalosis or other negative effects.

[0043] In some examples, the inspiratory flow control system **150** can mix one or more liquids and/or one or more particulate solids into the one or more gases, for example in aerosolized form. The one or more liquids can include water (H.sub.2O), one or more drugs in liquid form, one or more other liquids, or a combination thereof. The one or more particulate solids can include one or more drugs in particulate solid form, one or more other particulate solids, or a combination thereof. The inspiratory flow control system **150** can include an aerosolizer and/or particulatizer to aerosolize and/or particulate the one or more liquids and/or the one or more solids. The inspiratory flow control system **150** can mix the one or more aerosolized and/or particulate liquids and/or solids into the one or more inspiratory gases.

[0044] The inspiratory flow control system **150** can mix gases and/or liquids and/or particulate solids from the one or more inspiratory gas sources **160** at one or more predetermined ratios and/or proportions. The inspiratory flow control system **150** can mix inspiratory gases and/or liquids and/or particulate solids from the one or more inspiratory gas sources **160** at one or more predetermined ratios and/or proportions to

simulate the natural ratios and/or proportions of these gases in Earth's atmosphere or other ratios and/or proportions that may be selected or recommended by an operator, by an artificial intelligence algorithm (e.g., one or more trained machine learning models, one or more trained neural networks, or a combination thereof), or a combination thereof. The inspiratory flow control system **150** can mix inspiratory gases from the one or more inspiratory gas sources **160** at one or more predetermined ratios and/or proportions that increase or decrease a relative quantity of one or more specific gases (e.g., increased oxygen and/or decreased carbon monoxide) relative to the natural ratios and/or proportions of these gases in Earth's atmosphere or other ratios and/or proportions that may be selected or recommended by an operator, by an artificial intelligence algorithm (e.g., one or more trained machine learning models, one or more trained neural networks, or a combination thereof), or a combination thereof. The mixture mixed by the inspiratory flow control system **150** can be referred to as the inspiratory mixture, the inspiratory gas, the inspiratory substance, the inspiratory air, or some combination thereof.

[0045] In some examples, some of the mixing and/or modifications to gas properties described above with respect to the inspiratory flow control system **150** can occur between the inspiratory tube **152** and the ETT **120**. In some examples, some of the mixing and/or modifications to gas properties described above with respect to the inspiratory flow control system **150** can occur at the first fitting **147**, at the second fitting **148**, and/or at the patient interface **149**. For example, a drug tube **118** is illustrated in FIG. 1 going into the second fitting **148**. The drug tube **118** can provide one or more drugs from one or more drug sources (e.g., one or more of the one or more inspiratory gas sources **160**) to the inspiratory gas provided through the ETT **120** to the patient **105**'s airways. The one or more drugs can include, for example, anesthetics, drugs for treating an injury, drugs for treating a disability, a drugs for treating a disease (e.g., a respiratory disease and/or any other disease discussed herein), and/or drugs for treating symptoms of a disease (e.g., a respiratory disease and/or any other disease discussed herein), bronchodilators, or a combination thereof.

[0046] The inspiratory flow control system **150** can control various properties of the inspiratory gas, such as temperature and/or humidity. The inspiratory flow control system **150** can include a warmer and/or a heat exchanger to control (e.g., increase or decrease) the temperature of the inspiratory gas before the inspiratory flow control system **150** provides the inspiratory gas to the patient **105**'s airways through the inspiratory tube **152**, through the first fitting **147**, through the second fitting **148**, through the patient interface **149**, and/or through the ETT **120**. The inspiratory flow control system **150** can include a humidifier and/or a moisture exchanger and/or a moisture trap to control (e.g., increase or decrease) the humidity of the inspiratory gas before the inspiratory flow control system **150** provides the inspiratory gas to the patient **105**'s airways through the inspiratory tube **152**, through the first fitting **147**, through the second fitting **148**, through the patient interface **149**, and/or through the ETT **120**. The inspiratory flow control system **150** can control properties such as temperature and/or humidity before mixing inspiratory gases/liquids/solids, after mixing inspiratory gases/liquids/solids, or both.

[0047] The inspiratory flow control system **150** can include one or more filters that filter out the contaminants from the inspiratory gas before the inspiratory flow control system **150** provides the inspiratory gas to the patient **105**'s airways through the inspiratory tube **152**, through the first fitting **147**, through the second fitting **148**, through the patient interface **149**, and/or through the ET **120**. The inspiratory flow control system **150** can filter the inspiratory air before mixing inspiratory gases/liquids/solids, after mixing inspiratory gases/liquids/solids, or both.

[0048] In some examples, the inspiratory flow control system **150** can include one or multiple inspiratory lumens that provide inspiratory gas to both lungs or separately provide inspiratory gas to different portions of the patient **105**'s airways. For instance, the inspiratory flow control system **150** can include a first inspiratory lumen and a second inspiratory lumen. The multiple inspiratory lumens can include a left inspiratory lumen **220** and a right inspiratory lumen **225** as illustrated in, and/or described with respect to, FIGS. 2, 5A, 5B, 6, 9A, and/or **9B**. In some examples with at least 2 inspiratory lumens, as illustrated on FIG. 9B, the inspiratory flow control system **150** can include a pressure relief valve **906**, a gas property

control **908**, inspiratory mixture sensors **910**, a buffer **912**, an inspiratory mixture pressurizer **914**, a pressure relief valve **916**, a gas property control **918**, inspiratory mixture sensors **920**, a buffer **922**, an inspiratory mixture pressurizer **924**, a capnometer **926**, a gas property control **928**, a gas mixer **930**, or a combination thereof.

[0049] The expiratory flow control system **155** receives flow of expiratory gas(es) from the patient **105**'s airways, through the ETT **120**, through the patient interface **149**, through the second fitting **148**, through the first fitting **147**, through an expiratory tube **157**, and/or transfers expiratory gas(es) into one or more expiratory gas outputs **165**. The one or more expiratory gas outputs **165** can include a sink (e.g., a reservoir), an exhaust, or both. For example, if the expiratory gas is from a patient whose airways include disease-causative agents that might cause disease in others in the area (e.g., doctors, nurses other patients), the one or more expiratory gas outputs **165** can include a sink (e.g., a reservoir) to trap the expiratory gas(es) within. If the disease-causative agents can be reliably filtered out using one or more filters, the one or more expiratory gas outputs **165** can include the one or more filters and/or an exhaust.

[0050] In some examples, the expiratory flow control system **155** includes a suction device that provides suction from the patient **105**'s airway through the ETT **120** and expiratory tube **157**. The compressor(s) and/or pressurizer(s) **145** can provide gas compression and/or pressure that can provide the suction for the suction device of the expiratory flow control system **155**. In some examples, the expiratory flow control system **155** does not include or does not activate its suction device, and instead receives expiratory flow from the airways of the patient **105** based on the airflow provided by patient **105**'s own exhalations. In some examples, the expiratory flow control system **155** receives the expiratory partially using suction from the suction device and partially using airflow provided by patient **105**'s own exhalations, for example if patient **105** is passively exhaling during the expiration, but with not enough flow rate to provide sufficient exhalation, or if the patient **105** is breathing on their own but too weakly to provide sufficient exhalation.

[0051] In some examples, the expiratory flow control system **155** filters out and/or traps one or more liquids (e.g., aerosolized liquids), one or more solids (e.g., particulate solids), or a combination thereof. The expiratory flow control system **155** can filters out and/or traps the liquids and/or solids using one or more filters, one or more moisture traps, or a combination thereof. For example, a moisture tube **128** is illustrated coming from the second fitting **148**, which may output liquid collected by a moisture trap within the second fitting **148**. In some examples, the moisture tube **128** can output to an expiratory gas output **165** (e.g., sink or exhaust).

[0052] The expiratory flow control system **155** can control various properties of the expiratory gas, such as temperature and/or humidity. The expiratory flow control system **155** can include a warmer and/or a heat exchanger to control (e.g., increase or decrease) the temperature of the expiratory gas. The expiratory flow control system **150** can include a humidifier and/or a moisture exchanger and/or a moisture trap to control (e.g., increase or decrease) the humidity of the expiratory gas. The expiratory flow control system **155** can include one or more filters that filter out the contaminants (such as disease-causative agents) from the expiratory gas.

[0053] In some examples, the expiratory flow control system **155** can include multiple expiratory lumens that separately receive expiratory gas from different portions of the patient **105**'s airways. For instance, the inspiratory flow control system **150** can include a first expiratory lumen and a second expiratory lumen. The multiple expiratory lumens can include a left expiratory lumen **520** and a right inspiratory lumen **525** as illustrated in, and/or described with respect to, FIGS. 5C and 9B. In some examples, the expiratory flow control system **155** can include a water trap **936**, a capnometer **938**, expiratory mixture sensors **940**, a buffer **942**, an expiratory mixture pressurizer **944**, a water trap **946**, a capnometer **948**, expiratory mixture sensors **950**, a buffer **952**, an expiratory mixture pressurizer **954**, a filtration system **956**, or a combination thereof.

[0054] The pressurizer(s) **145** can be used to compress and/or pressurize the inspiratory gas (e.g., the mixture of inspiratory gases from the inspiratory gas sources **160**) before providing the inspiratory gas compressed and/or pressurized to the patient **105**'s airways through the ETT **120**. The pressurizer(s) **145** can compress and/or pressurize the inspiratory gas within a buffer chamber. The pressurizer(s) **145** can be used to compress, decompress, pressurize, and/or depressurize expiratory gas, for example to provide suction as part of a suction device.

[0055] The ventilation system can include one or more controllers **170**. The one or more controllers **170** can each include one or more computing systems **1100**. For examples, the one or more controllers **170** can each include one or more processors **1110**, one or more memory units (e.g., ROM **1120**, RAM **1125**), one or more storage devices **1130**, one or more input devices **1145**, one or more output devices **1135**, one or more communication interfaces **1140**, or a combination thereof. In some examples, the one or more controllers **170** can receive sensor data from one or more sensors of the ventilator system, such as one or more capnometers **926/938/948**, one or more inspiratory mixture sensors **910/920**, one or more expiratory mixture sensors **940/950**, or a combination thereof and/or other sensors (not shown on pictures) used in clinical practice like oxygen saturation of patient's blood, patient's blood pressure, ECG curve, temperature, central line catheter transducer, video camera, microphone, or a combination thereof. In some examples, the one or more controllers **170** can analyze the sensor data from the one or more sensors and one or more capnometers of the ventilator system, for example to compare the sensor data to one or more predetermined thresholds or ranges that the one or more controllers **170** can trigger actions based on. In some examples, the one or more controllers **170** can analyze the sensor data from the one or more sensors of the ventilator system to identify one or more patterns that the one or more controllers **170** can trigger actions based on. Actions that can be triggered can include, for example, modifying inspiratory airflow pressure, modifying inspiratory airflow patterns (e.g., between inspiratory flows **830A-830E**), modifying expiratory airflow pressure (e.g., expiratory suction), modifying expiratory airflow patterns (e.g., between expiratory flows **835A-835E**), or a combination thereof.

[0056] The ventilation system can include one or more interfaces **175** for the one or more controllers **170**. The one or more interfaces **175** can include one or more output devices **180**, which can include one or more display screens, one or more indicator lights (e.g., light emitting diodes (LEDs)), one or more speakers, one or more headphones, one or more output devices **1135**, or a combination thereof. The one or more output devices **180** also include connectors that can be used to connect the one or more controllers **170** to one or the previously-listed types of output devices **180**, such as plugs, ports, jacks, wires, and/or wireless transceivers. The one or more output devices **180** can output data to one or more users **190**, such as sensor data from the one or more sensors of the ventilator system, indicators that the sensor data has exceeded a threshold, indicators that the sensor data has fallen below a threshold, indicators that the sensor data has crossed into a predetermined range, indicators that the sensor data has crossed out of a predetermined range, indications of one or more patterns recognized in the sensor data by the one or more controllers **170**, or a combination thereof.

[0057] The one or more interfaces **175** can include one or more input devices **185**, which can include one or more touchscreens, keyboards, keypads, mouse pointers, trackpads, trackballs, microphones, cameras, one or more input devices **1145**, or a combination thereof. The one or more input devices **185** also include connectors that can be used to connect the one or more controllers **170** to one or the previously-listed types of input devices **185**, such as plugs, ports, jacks, wires, and/or wireless transceivers. The one or more input devices **185** can receive input data from one or more users **190**, such as input data identifying a threshold, a range, an inspiratory airflow pattern to use (e.g., one of inspiratory flows **830A-830E**), an inspiratory airflow pattern to use (e.g., one of expiratory flows **835A-835E**), or a combination thereof.

[0058] In some examples, a ventilator system may include multiple inspiratory flow control systems **150**, multiple expiratory flow control systems **152**, multiple pressurizers **145**, multiple controllers **170**, multiple

inspiratory tubes **152**, multiple expiratory tubes **157**, or a combination thereof. In an illustrative example, the inspiratory flow control systems **150** of the ventilator system may include a left inspiratory flow control system and a right inspiratory flow control system. The left inspiratory flow control system can mix an inspiratory mixture for, and/or provides the inspiratory mixture to, the left lung **130** of the patient, in some examples through a left inspiratory tube of the inspiratory tubes **152** and/or through a left inspiratory lumen (e.g., left inspiratory lumen **220**). In some examples, a left pressurizer of the multiple pressurizers **145** can provide pressure to provide the inspiratory mixture from the left inspiratory flow control system to the left lung **130** of the patient. In some examples, a left controller of the multiple controllers **170** can control inspiratory pressure, inspiratory mixture components, inspiratory mixture component ratios, and/or other aspects of provision of the inspiratory mixture from the left inspiratory flow control system to the left lung **130**. The right inspiratory flow control system can mix an inspiratory mixture for, and/or provides the inspiratory mixture to, the right lung **135** of the patient, in some examples through a right inspiratory tube of the inspiratory tubes **152** and/or through a right inspiratory lumen (e.g., right inspiratory lumen **225**). In some examples, a right pressurizer of the multiple pressurizers **145** can provide pressure to provide the inspiratory mixture from the right inspiratory flow control system to the right lung **135** of the patient. In some examples, a right controller of the multiple controllers **170** can control inspiratory pressure, inspiratory mixture components, inspiratory mixture component ratios, and/or other aspects of provision of the inspiratory mixture from the right inspiratory flow control system to the right lung **135**. The inspiratory tube(s) **152** are illustrated as a single tube with a dashed line dividing the single tube into two tubes. The single tube represents that the inspiratory tube(s) **152** can be a single tube, while the dashed line division represents that the inspiratory tube(s) **152** can include a left inspiratory tube and a right inspiratory tube as discussed above.

[0059] In an illustrative example, the expiratory flow control systems **155** of the ventilator system may include a left expiratory flow control system and a right expiratory flow control system. The left expiratory flow control system can receive an expiratory mixture from, and/or suction the expiratory mixture from, the left lung **130** of the patient, in some examples through a left expiratory tube of the expiratory tubes **157** and/or through a left expiratory lumen (e.g., left expiratory lumen **520**). In some examples, a left pressurizer of the multiple pressurizers **145** can provide negative pressure to pull, extract, and/or suction the expiratory mixture from the left expiratory flow control system from the left lung **130** of the patient **105** to the expiratory gas output(s) **165**. In some examples, a left controller of the multiple controllers **170** can control expiratory negative pressure and/or other aspects of receipt of the expiratory mixture from the left lung **130** to the expiratory gas output(s) **165**. The right expiratory flow control system can receive an expiratory mixture from, and/or suction the expiratory mixture from, the right lung **130** of the patient, in some examples through a right expiratory tube of the expiratory tubes **157** and/or through a right expiratory lumen (e.g., right expiratory lumen **525**). In some examples, a right pressurizer of the multiple pressurizers **145** can provide negative pressure to pull, extract, and/or suction the expiratory mixture from the right expiratory flow control system from the right lung **135** of the patient **105** to the expiratory gas output(s) **165**. In some examples, a right controller of the multiple controllers **170** can control expiratory negative pressure and/or other aspects of receipt of the expiratory mixture from the right lung **135** to the expiratory gas output(s) **165**. The expiratory tube(s) **157** are illustrated as a single tube with a dashed line dividing the single tube into two tubes. The single tube represents that the expiratory tube(s) **157** can be a single tube, while the dashed line division represents that the expiratory tube(s) **157** can include a left expiratory tube and a right expiratory tube as discussed above.

[0060] FIG. 2 is a conceptual diagram **200** illustrating a side view of a ventilator system connected to a patient **105**. The side view illustrates the ETT **120** entering the patient **105**'s mouth **110**, passing along the patient **105**'s larynx **112**, and passing into and/or through at least a portion of the patient **105**'s trachea **115**. The ventilator system includes a connector **230** to which a drug tube **118** can be connected.

[0061] The ventilator system includes a balloon **205** for the ETT **120**. The balloon **205** inflates once the ETT **120** is in the trachea **115**. The balloon **205**, once inflated, secures the ETT **120** in position in the

trachea **115**. The balloon **205**, once inflated, can protect the ETT **120** from scraping the walls of, colliding with the walls of, or otherwise injuring the trachea **115**. The balloon **205**, once inflated, can prevent airflow from passing through the trachea **115** other than through the ETT **120**.

[0062] The ventilator system includes multiple inspiratory lumens that provide inspiratory gas(es) to different portions of the patient **105**'s airways. In particular, the ventilator system of FIG. 2 includes a left inspiratory lumen **220** and a right inspiratory lumen **225**. The left inspiratory lumen **220** and the right inspiratory lumen **225** pass through the ETT **120** and extends beyond the tip **125** of the ETT **120**, further into the patient **105**'s airways. The left inspiratory lumen **220** extends toward and/or into the left primary bronchus **210** and/or the left lung **130** of the patient **105**. The right inspiratory lumen **225** extends toward and/or into the right primary bronchus **215** and/or the right lung **135** of the patient **105**.

[0063] FIG. 3 is a conceptual diagram **300** illustrating a trachea **115** connected to a left lung **130** and a right lung **135**. The trachea **115**, as illustrated in FIG. 3, starts from a point below the larynx **112** (not pictured). The trachea **115**, as it extends toward the left lung **130** and the right lung **135**, branches into the left primary bronchus **210** and the right primary bronchus **215**. The left primary bronchus **210** conducts airflow between the trachea **115** and the left lung **130**. The right primary bronchus **215** conducts airflow between the trachea **115** and the right lung **135**. The primary bronchi can branch into further, smaller bronchi. For example, the left primary bronchus **210** branches into three left secondary bronchi **310**. The right primary bronchus **215** branches into three right secondary bronchi **315**. The secondary bronchi may be referred to as lobar bronchi. Each secondary bronchus of the left secondary bronchi **310** and/or right secondary bronchi **315** can branch off further into narrower tertiary bronchi or segmental bronchi. Further divisions of the segmental bronchi are known as 4th order segmental bronchi, 5th order segmental bronchi, 6th order segmental bronchi, and so forth, or may be referred to as subsegmental bronchi.

[0064] Bronchi may branch into smaller bronchioles **320**, which themselves may branch into further bronchioles **320**. Some bronchioles **320**, referred to as respiratory bronchioles **320**, end in alveoli **325** that include alveolar ducts and alveolar sacs. The alveoli may include surface epithelial cells referred to as pneumocytes. If a patient **105** has a disease, alveoli **325** in the left lung **130** and/or alveoli **325** in right lung **135** can become infected with disease-causative agents (DCAs) such as viruses or bacteria. In some examples, if a patient **105** has a disease, pneumocytes of the alveoli **325** can become infected by certain DCAs such as viruses or bacteria.

[0065] FIG. 4A is a conceptual diagram **400A** illustrating part of a ventilator system with an endotracheal tube (ETT) **120** in a trachea **115** providing inspiratory gas into a diseased right lung **135** and a healthy left lung **130**. The ventilator system includes a balloon **205** for the ETT **120**. The balloon **205** is illustrated in its inflated state, in which the balloon **205** secures the ETT **120** in position in the trachea **115**, protects the trachea **115** from being damaged by the ETT **120**, and/or prevent airflows from passing through the trachea **115** other than through the ETT **120**.

[0066] A shaded area within part of the trachea **115** and some of the bronchi represents the dead space **410** with limited gas exchange or no gas exchange. The dead space **410** covers a significant portion of the left primary bronchus **210** and the right primary bronchus **215**, for instance. The dead space **410** covers at least some of the left secondary bronchi **310** and/or right secondary bronchi **315**. In some examples, the dead space **410** can also include certain segmental bronchi, subsegmental bronchi, bronchioles **320**, and/or alveoli **325**.

[0067] The right lung **135** of FIG. 4A includes two infected alveoli **420** and a recovered alveolus **430**. The two infected alveoli **420** are each illustrated as white-colored 16-point starburst shape that are shaded with a black crosshatch pattern and outlined in black. The recovered alveolus **430** is illustrated as a white-colored 16-point starburst shape that is outlined in black. The two infected alveoli **420** may be infected with a disease caused by DCAs **425**. As noted above, DCAs **425** can include, for example, bacteria,

fungi, viruses (e.g., virions), parasites, protozoa, helminths, prions, toxins, synthetic toxicants, physical contaminants, chemical contaminants, biological contaminants, radiological contaminants, portions of a patient's immune system that have an autoimmune disease, or combinations thereof. Diseases can include infections, injuries, disabilities, disorders, syndromes, infections, isolated symptoms, deviant behaviors, atypical, aberrant, or pathologic variations of structure and function, or combinations thereof. The recovered alveolus **430** may have previously been an infected alveolus that has since recovered from the disease and/or no longer harbors DCAs **425**. Two example DCAs **425** are also illustrated in secondary and tertiary bronchi of the right lung **135** near the infected alveoli **420**. The DCAs **425** are illustrated as white-colored 5-point star shapes that are shaded with a black crosshatch pattern and outlined in black.

[0068] The ETT **120**, as illustrated in FIG. 4A, is providing an inspiratory gas to the patient **105**'s airways. An exemplary flow of the inspiratory gas down the ETT **120** and into and through the bronchi of the left lung **130** and the right lung **135** is illustrated using white arrows outlined in black. Because the DCAs **425** in the bronchi are largely clustered close to the infected alveoli **420** in FIG. 4A, the flow of inspiratory gas in FIG. 4A might spread the DCAs **425** to certain segmental bronchi, subsegmental bronchi, bronchioles **320**, and/or alveoli **325** that are close to the infected alveoli **420**. Because the DCAs **425** in the bronchi are largely clustered close to the infected alveoli **420** in FIG. 4A, the flow of inspiratory gas in FIG. 4A is unlikely to spread the DCAs **425** from the right lung **135** to the left lung **130**, or otherwise to portions of the patient **105**'s airway (e.g., bronchi, bronchioles **320**, and/or alveoli **325**) that are far away from the infected alveoli **420** in FIG. 4A.

[0069] FIG. 4B is a conceptual diagram **400B** illustrating part of the ventilator system of FIG. 4A with the endotracheal tube (ETT) **120** evacuating expiratory gas that includes disease-causative agents (DCAs) **425** from the diseased right lung **135** and the healthy left lung **130** during the expiration. The right lung **135** of FIG. 4B includes the two infected alveoli **420** of FIG. 4A and the recovered alveolus **430** of FIG. 4A.

[0070] The ETT **120**, as illustrated in FIG. 4B, is receiving and/or evacuating an expiratory gas from the patient **105**'s airways. An exemplary flow of the expiratory gas up the ETT **120** and from the bronchi of the left lung **130** and the right lung **135** is illustrated using white arrows shaded with black dots and outlined in black. The flow of the expiratory gas from the patient **105**'s airways toward and up the ETT **120** has pulled more DCAs **425** from the infected alveoli **420** and spread the DCAs **425** through more of the patient's airways. The expiratory gas from the infected alveoli **420**'s exit path can all become contaminated with DCAs **425**, including for instance the secondary right bronchus, the main right bronchus, and the distal part of trachea **115** and ETT **120**. Additionally, because the dead space **410** is not briskly evacuated, DCAs **425** released from pneumocytes of infected alveoli **420**, or otherwise present in the infected alveoli **420**, can float into dead space **410**, and then from there spread to other proximal portions of lungs **130-135**. For example, the flow of the expiratory gas from the patient **105**'s airways toward and up the ETT **120** has pulled some DCAs **425** into other bronchi of the right lung **135** (e.g., the right primary bronchus **215**), adjacent to (or even into) bronchi of the left lung **130** (e.g., the left primary bronchus **210**), into the trachea **115**, and into the ETT **120**. While some of these DCAs **425** will be successfully evacuated from the patient's airways by the ETT **120**, in some cases DCAs **425** may remain in the dead space **410** due to lack of timely evacuation of the dead space **410**. The DCAs **425** that remain in the dead space **410** can then be spread further by a inspiratory gas provided from the ETT **120** as illustrated in FIG. 4C with an subsequent inspiration after the expiration of FIG. 4B.

[0071] FIG. 4C is a conceptual diagram **400C** illustrating part of the ventilator system of FIGS. 4A-4B with the endotracheal tube (ETT) **120** providing inspiratory gas that spreads disease-causative agents (DCAs) **425** to more of the diseased right lung **135** and newly introduces DCAs **425** into the newly-diseased left lung **130**, for instance as inspiratory gas passes through previously-contaminated airways and ETT **120** (e.g., areas with DCAs **425** in FIG. 4B). This spread causes the right lung **135** of FIG. 4C to include two newly infected alveoli **440**, and causes the recovered alveolus **430** of FIG. 4B to become reinfected,

becoming a reinfected alveolus **435**. The right lung **135** of FIG. 4C also still includes the two infected alveoli **420** of FIGS. 4A-4B.

[0072] The ETT **120**, as illustrated in FIG. 4C, is providing an inspiratory gas to the patient **105**'s airways. An exemplary flow of the inspiratory gas down the ETT **120** and into and through the bronchi of the left lung **130** and the right lung **135** is illustrated using white arrows outlined in black. Because some DCAs **425** remain in the dead space **410** after being pulled into the dead space **410** by the flow of the expiratory gas of FIG. 4B, and because the ETT **120** and some airways became contaminated by the expiratory gas as illustrated in FIG. 4B, the inspiratory gas provided from the ETT **120** into the patient **105**'s airways spreads the DCAs **425** from the dead space **410** and other portions of the patient **105**'s airways that were contaminated during the expiration of FIG. 4B (e.g., the ETT **120**) throughout the patient **105**'s airways, even to parts of the patient **105**'s airways that were previously healthy, non-diseased, and/or free of DCAs **425**. For example, the flow of the inspiratory gas spreads the DCAs **425** to the recovered alveolus **430** of FIGS. 4A-4B, which newly becomes reinfected to become a reinfected alveolus **435** in FIG. 4C. The reinfected alveolus **435** is illustrated as a black-colored 16-point starburst shape that is shaded with a white crosshatch pattern and outlined in black. The flow of the inspiratory gas spreads the DCAs **425** to other previously-healthy alveoli **325**, newly infecting them, including two newly infected alveoli **440**. The newly infected alveoli **440** are illustrated as black-colored 16-point starburst shapes. The first of the newly infected alveoli **440** is located in a part of the right lung **135** far from the infected alveoli **420**, branching from a different one of the right secondary bronchi **315** than the infected alveoli **420**. The second of the newly infected alveoli **440** is located in the left lung **130**. Thus, FIGS. 4A-4C illustrate how a ventilator system that both provides inspiratory gas to the patient **105**'s airways from the tip **125** of the ETT **120** and evacuates an expiratory gas from the patient **105**'s airways through the same tip **125** of the ETT **120** can spread DCAs **425** throughout the patient **105**'s airways, for example from a diseased lung (as in the right lung **135** of FIGS. 4A-4B) to a formerly-healthy lung (as in the left lung **130**). This cycle of reinfected the patient **105**'s airways, and spreading the DCAs **425** throughout the patient **105**'s airways, perpetuates and/or spreads diseases and makes it harder for medications, therapeutics, patients' native immune system cells, antibodies, or other treatments to neutralize or eliminate the DCAs **425**. This maintains and/or spreads the diseased state in the patient **105**'s airways.

[0073] FIG. 4D is a conceptual diagram **400D** illustrating an example of the ventilator systems of FIGS. 4A-4C with an adapter **450** added on one side of the balloon **205** and another adapter **455** added on the other side of the balloon **205**. The conceptual diagram **400D** of FIG. 4D includes an exploded view of the ventilator system of FIG. 4D, illustrating the ETT **120**, the adapter **450**, the adapter **455**, and a ventilator circuit tube **457**. The adapter **450** is coupled to the ETT **120** on one end of the adapter **450**, and to a ventilator circuit tube **457** on the other end of the adapter **450**. The adapter **455** is coupled to one portion of the ETT **120** (that includes the balloon **205** and goes toward the patient **105**'s mouth) one end of the adapter **455**, and to another portion of the ETT **120** (that includes the tip **125** of the ETT **120** and goes toward the patient **105**'s lungs **130-135**) on the other end of the adapter **455**.

[0074] The ventilator circuit tube **457** may be, for example, a tube between the ETT **120** and the patient interface **149**, at least a part of the patient interface **149**, a tube between the patient interface **149** and the second fitting **148**, a tube between the second fitting **148** and the first fitting **147**, an inspiratory tube **152**, an expiratory tube **157**, or a combination thereof.

[0075] Examples of the adapter **450** include the micro-filter adapter **460** of FIG. 4E, the airflow rerouting adapter **470** of FIG. 4F, and the connector **610** of FIG. 6. Examples of the adapter **455** include the micro-filter adapter **460** of FIG. 4E, the airflow rerouting adapter **470** of FIG. 4F, and the connector **610** of FIG. 6. In some examples, the ventilator system of FIG. 4D may include the adapter **450** but may omit the adapter **455**. In some examples, the ventilator system of FIG. 4D may include the adapter **455** but may omit the adapter **450**. In some examples, the ventilator system of FIG. 4D may include both the adapter **450** and the adapter **455**, which may both be the same type of adapter or may be different types of adapters.

[0076] FIG. 4E is a conceptual diagram **400E** illustrating a cross-section of a micro-filter adapter **460**. The micro-filter adapter **460** includes an inner area **462** and an outer area **464**. The inner area **462** and the outer area **464** may be separated by a barrier **463**. In some examples, the barrier **463** may be rigid. In some examples, the barrier **463** may be pliable, as in a sleeve and/or a membrane or the barrier may be the microfiltration medium, on of a kinds later listed. The inner area **462** includes a microfilter medium **465**. The microfilter medium **465** may include, for example, N95 filter medium, N99 filter medium, HVAC filter medium, HEPA filter medium, ULPA filter medium, MERV 16 filter medium, MERV 15 filter medium, MERV 14 filter medium, MERV 13 filter medium, MERV 12 filter medium, MERV 11 filter medium, MERV 10 filter medium, MERV 9 filter medium, MERV 8 filter medium, MERV 7 filter medium, MERV 6 filter medium, MERV 5 filter medium, MERV 4 filter medium, paper filter medium, pleated filter medium, non-pleated filter medium, or a combination thereof.

[0077] The micro-filter adapter **460** can be an example of the adapter **250** and/or of the adapter **255** of FIG. 4D. Either way, the micro-filter adapter **460** couples to the ETT **120** along a bottom side of the micro-filter adapter **460** in a direction toward the patient **105**'s left lung **130**, right lung **135**, left primary bronchus **210**, right primary bronchus **215**, left secondary bronchi **310**, right secondary bronchi **315**, other bronchi, bronchioles **320**, alveoli **325**, or combinations thereof. The micro-filter adapter **460** can couple to the ETT **120** and/or to the ventilator circuit tube **457** along a top side of the micro-filter adapter **460** in a direction away from the patient **105**'s left lung **130**, right lung **135**, left primary bronchus **210**, right primary bronchus **215**, left secondary bronchi **310**, right secondary bronchi **315**, other bronchi, bronchioles **320**, alveoli **325**, or combinations thereof.

[0078] Examples of inspiratory airflow are illustrated in FIG. 4E using white arrows outlined in black, which enter from the top side of the micro-filter adapter **460** and move toward the bottom side of the micro-filter adapter **460**. Examples of expiratory airflow are illustrated in FIG. 4E using white arrows shaded with black dots and outlined in black, which enter from the bottom side of the micro-filter adapter **460** and move toward the top side of the micro-filter adapter **460**. While both the inspiratory airflow and expiratory airflow are illustrated flowing at the same time, in some cases inspiratory and expiratory airflow happen sequentially (i.e. inspiratory flow via microfilter medium **465** during inspiration and expiratory flow via outer area bypassing the microfilter medium **465** during expiration). In some cases, inspiratory and expiratory airflow happen simultaneously (i.e. continuous inspiratory flow via microfilter medium **465** and continues expiratory flow via outer area bypassing the microfilter medium). In some cases, inspiratory and expiratory airflow happen independently and intermittently (i.e. intermittent independent inspiratory flow via microfilter medium **465** and intermittent independent intermittent expiratory flow via outer area bypassing the microfilter medium **465** during at any other times). In some cases either inspiratory airflow or expiratory airflow may be flowing through the micro-filter adapter **460** without the other. For instance, at some times, only the inspiratory airflow may be flowing through the micro-filter adapter **460**, while at other times, only the expiratory airflow may be flowing through the micro-filter adapter **460**. In some examples, the microfilter medium can be placed in outer area **464** as well, as addition to microfilter medium **465** placed in inner area **464**, or without the microfilter medium **465** in the inner area.

[0079] The micro-filter adapter **460** includes a first one-way airflow valve **465A** that permits inspiratory airflow to pass through the first one-way airflow valve **465A** into the inner area **462** (based on movement direction moving toward the lungs **130-135**) and prevents expiratory airflow from passing through the first one-way airflow valve **465A** (based on movement direction moving away from the lungs **130-135**). Once in the inner area **462**, the inspiratory airflow passes through the microfilter medium **465** and is filtered by the microfilter medium **465**. The micro-filter adapter **460** includes a second one-way airflow valve **465B** that permits inspiratory airflow to pass through the second one-way airflow valve **465B** out from inside the inner area **462** (based on movement direction moving toward the lungs **130-135**) and prevents expiratory airflow from passing through the second one-way airflow valve **465B** to enter the inner area **462** (based on movement direction moving away from the lungs **130-135**). Thus, inspiratory airflow is filtered by the microfilter medium **465** before reaching the lungs **130-135** and bronchi.

[0080] The micro-filter adapter **460** can include a one or more one-way airflow valves **467A-467B** that permit expiratory airflow to pass through the one or more one-way airflow valves **467A-467B** into the outer area **464** (based on movement direction moving away from the lungs **130-135**) and prevents inspiratory airflow from passing through the one or more one-way airflow valves **467A-467B** (based on movement direction moving toward the lungs **130-135**). Once in the outer area **464**, the inspiratory airflow moves up without passing through the microfilter medium **465**, ensuring the microfilter medium **465** is kept free of DCAs **425** from the patient **105**'s airways. The micro-filter adapter **460** includes one or more one-way airflow valves **467C-467D** that permit expiratory airflow to pass through the one or more one-way airflow valves **467C-467D** out from inside the outer area **464** (based on movement direction moving away from the lungs **130-135**) and prevents inspiratory airflow from passing through the one or more one-way airflow valves **467C-467D** to enter the outer area **464** (based on movement direction moving away from the lungs **130-135**). Thus, the inspiratory airflow and the expiratory airflow are kept separate within the micro-filter adapter **460** by the barrier **463** and the various one-way airflow valves.

[0081] In some examples, the micro-filter adapter **460** can include, and/or be coupled to, one or more mucus extraction tubes **469A-469B**, which may extract mucus from expiratory airflow and/or inspiratory airflow to help prevent mucus from clogging any of the one-way airflow valves **465A-465B**, from clogging any of the one-way airflow valves **467A-467F**, from clogging the microfilter medium **465**, from clogging the inner area **462**, from clogging the outer area **464**, from weakening the barrier **463**, or a combination thereof. The one or more mucus extraction tubes **469A-469B** may use suction (e.g., negative pressure) to extract the mucus from the airflow. In some examples, the micro-filter adapter **460** can include one or more one-way airflow valves **467E-467F** that permit expiratory airflow to pass through the one or more one-way airflow valves **467E-467F** into the one or more mucus extraction tubes **469A-469B** (based on movement direction moving away from the lungs **130-135**) and prevents inspiratory airflow from passing through the one or more one-way airflow valves **467E-467F** to enter the one or more mucus extraction tubes **469A-469B** (based on movement direction moving toward the lungs **130-135**). In some examples, the one or more one-way airflow valves **467E-467F** instead permit inspiratory airflow to pass through the one or more one-way airflow valves **467E-467F** into the one or more mucus extraction tubes **469A-469B** (based on movement direction moving toward the lungs **130-135**) and prevents expiratory airflow from passing through the one or more one-way airflow valves **467E-467F** to enter the one or more mucus extraction tubes **469A-469B** (based on movement direction moving away from the lungs **130-135**). In some examples, the one or more one-way airflow valves **467E-467F** permit both inspiratory airflow and expiratory airflow to pass through the one or more one-way airflow valves **467E-467F** into the one or more mucus extraction tubes **469A-469B**. A first mucus extraction tube **469A** is illustrated above (away from the lungs **130-135**) the microfilter medium **465** and above one-way airflow valves **465A**, **467C**, and **467D**. A second mucus extraction tube **469B** is illustrated below (toward from the lungs **130-135**) the microfilter medium **465** and below one-way airflow valves **465B**, **467A**, and **467B**. The mucus extraction tube(s) **469A-469B** can connect to the outer area **464**, the inner area **462**, or both. In some examples, the barrier **463** may be cylindrical in shape as illustrated in FIG. 4E, In some examples, the barrier **463** may be conical in shape, which may increase filtration surface area, reducing the pressure gradient across the microfilter medium **465** and maximizing the lifetime of microfilter medium **465**. In some examples, a microfilter adapter **460** (and/or a microfilter medium **465** on its own) can be placed distally from trachea **115**, within inspiratory lumens **220-225** and/or expiratory lumens **520/525**. In some examples, a microfilter adapter **460** may be used upside-down, or backwards, relative to the airflow and directionality illustrated in FIG. 4E, so that the expiratory airflow is filtered through the microfilter medium **465** rather than the inspiratory airflow. In some examples, the outer area **464** may also include a separate microfilter medium (of any of the types discussed with respect to the microfilter medium **465**) that may filter the airflow passing through the outer area **464** of the microfilter adapter **460**.

[0082] A micro-filter adapter **460** may provide technical improvements over the ventilator systems of FIGS. 4A-4C by filtering inspiratory airflow before the inspiratory airflow reaches the patient **105**'s lungs

130-135. A micro-filter adapter **460** may provide technical improvements over the ventilator systems of FIGS. 4A-4C by separating the inspiratory airflows and expiratory airflows to prevent DCAs **425** from the expiratory airflows from mixing into the inspiratory airflows and spreading throughout the patient **105**'s lungs **130-135** and airways in general.

[0083] FIG. 4F is a conceptual diagram **400F** illustrating a cross-section of an airflow rerouting adapter **470**. The airflow rerouting adapter **470** can be an example of the adapter **450** and/or of the adapter **455** of FIG. 4D. Either way, the airflow rerouting adapter **470** couples to the ETT **120** along a bottom side of the airflow rerouting adapter **470** in a direction toward the patient **105**'s left lung **130**, right lung **135**, left primary bronchus **210**, right primary bronchus **215**, left secondary bronchi **310**, right secondary bronchi **315**, other bronchi, bronchioles **320**, alveoli **325**, or combinations thereof. The airflow rerouting adapter **470** can couple to the ETT **120** and/or to the ventilator circuit tube **457** along a top side of the airflow rerouting adapter **470** in a direction away from the patient **105**'s left lung **130**, right lung **135**, left primary bronchus **210**, right primary bronchus **215**, left secondary bronchi **310**, right secondary bronchi **315**, other bronchi, bronchioles **320**, alveoli **325**, or combinations thereof.

[0084] Examples of inspiratory airflow are illustrated in FIG. 4F using white arrows outlined in black. A primary inspiratory airflow enters the airflow rerouting adapter **470** from the top side of the airflow rerouting adapter **470** and moves toward the filter **485** and the output **487**. A secondary inspiratory airflow enters the airflow rerouting adapter **470** from the inspiratory gas provision system **490** of the airflow rerouting adapter **470** moves toward the bottom of the airflow rerouting adapter **470**, toward the patient **105**'s lungs **130-135**.

[0085] Examples of expiratory airflow are illustrated in FIG. 4E using white arrows shaded with black dots and outlined in black. A primary expiratory airflow enters the airflow rerouting adapter **470** from the bottom side of the airflow rerouting adapter **470** (from the patient **105**'s lungs **130-135**) and moves toward the filter **485** and the output **487**. A secondary expiratory airflow enters the airflow rerouting adapter **470** from the inspiratory gas provision system **490** of the airflow rerouting adapter **470** moves toward the top of the airflow rerouting adapter **470**, away from the patient **105**'s lungs **130-135**. While both the inspiratory airflow and expiratory airflow are illustrated flowing at the same time, in some cases either inspiratory airflow or expiratory airflow may be flowing through the airflow rerouting adapter **470** without the other, and/or sequentially, or continuously, For instance, at some times, only the inspiratory airflow may be flowing through the airflow rerouting adapter **470**, while at other times, only the expiratory airflow may be flowing through the airflow rerouting adapter **470**.

[0086] A set of one-way airflow valves **465C-465D** can route the inspiratory airflow along the previously-described and illustrated paths. A set of one-way airflow valves **467G-467H** can route the expiratory airflow along the previously-described and illustrated paths.

[0087] The airflow rerouting adapter **470** includes a one-way airflow valve **465C** that permits the primary inspiratory airflow to pass through the one-way airflow valve **465C** toward the inspiratory sensors **472A**, the filter **485**, and the output **487** (based on movement direction moving toward the lungs **130-135**) and prevents expiratory airflow from passing through the one-way airflow valve **465C** (based on movement direction moving away from the lungs **130-135**). The airflow rerouting adapter **470** includes a one-way airflow valve **465D** that permits the secondary inspiratory airflow to pass through the one-way airflow valve **465D** toward the inspiratory sensors **472B**, and into the ETT **120** toward the tip **125** of the ETT **120** and toward the patient **105**'s lungs **130-135** (based on movement direction moving toward the lungs **130-135**) and prevents expiratory airflow from passing through the one-way airflow valve **465D** (based on movement direction moving away from the lungs **130-135**).

[0088] The airflow rerouting adapter **470** includes a one-way airflow valve **467G** that permits the primary expiratory airflow to pass through the one-way airflow valve **467G** toward the expiratory sensors **475A**, the

filter **485**, and the output **487** (based on movement direction moving away from the lungs **130-135**) and prevents inspiratory airflow from passing through the one-way airflow valve **467G** (based on movement direction moving toward the lungs **130-135**). The airflow rerouting adapter **470** includes a one-way airflow valve **467H** that permits the secondary expiratory airflow to pass through the one-way airflow valve **467H** toward the expiratory sensors **475B**, toward the top of the airflow rerouting adapter **470** and into the ventilator circuit tube **457** and/or ETT **120** (based on movement direction moving away from the lungs **130-135**) and prevents inspiratory airflow from passing through the one-way airflow valve **467H** (based on movement direction moving toward the lungs **130-135**).

[0089] The output **487** can be, for example, a sink or an exhaust. Examples of the output **487** include the expiratory gas output(s) **165** and the output **958**. Examples of the filter **485** include the filtration **956**. In some examples, the primary inspiratory airflow may be output to the filter **485** and/or to the output **487**. The airflow rerouting adapter **470** can effectively replace the primary inspiratory airflow with the secondary inspiratory airflow provided by the inspiratory gas provision system **490**, which can provide the patient **105**'s lungs **130-135** and airways generally with more fine-tuned inspiratory airflow than the ventilator system into which the airflow rerouting adapter **470** is being added. This fine-tuned inspiratory airflow can be clean of DCAs **425**, as it is not coming from an already-contaminated ETT **120**, ventilator circuit tubing **457**, other tubing, or other portion(s) of the ventilator system. In some examples, the primary expiratory airflow may be output to the filter **485** and/or to the output **487**. The airflow rerouting adapter **470** can effectively replace the primary expiratory airflow with the secondary expiratory airflow provided by the expiratory gas provision system **490**, which can provide the ETT **120** and/or ventilator circuit tube **457** with expiratory airflow that prevents warnings or alarms (e.g., regarding lack of expiratory airflow or irregular expiratory airflow) from being raised by the ventilator system into which the airflow rerouting adapter **470** is being added.

[0090] In some examples, the airflow rerouting adapter **470** includes one or more airflow sensors **466C** beside the one-way airflow valve **465C** that detect attributes of the primary inspiratory airflow. In some examples, the one or more airflow sensors **466C** are above the one-way airflow valve **465C**, and therefore the primary inspiratory airflow encounters the one or more airflow sensors **466C** before passing through the one-way airflow valve **465C**. In some examples, the airflow rerouting adapter **470** includes one or more airflow sensors **466D** beside the one-way airflow valve **465D** that detect attributes of the secondary inspiratory airflow. In some examples, the one or more airflow sensors **466D** are below the one-way airflow valve **465D**, and therefore the secondary inspiratory airflow encounters the one or more airflow sensors **466D** after passing through the one-way airflow valve **465D**. In some examples, the airflow rerouting adapter **470** includes one or more airflow sensors **468G** beside the one-way airflow valve **467G** that detect attributes of the primary expiratory airflow. In some examples, the one or more airflow sensors **468G** are below the one-way airflow valve **467G**, and therefore the primary expiratory airflow encounters the one or more airflow sensors **468G** before passing through the one-way airflow valve **467G**. In some examples, the airflow rerouting adapter **470** includes one or more airflow sensors **468H** beside the one-way airflow valve **467H** that detect attributes of the secondary expiratory airflow. In some examples, the one or more airflow sensors **468H** are above the one-way airflow valve **467H**, and therefore the secondary expiratory airflow encounters the one or more airflow sensors **468H** after passing through the one-way airflow valve **467H**.

[0091] The various sensors of the airflow rerouting adapter **470**—including the one or more airflow sensors **466C**, the one or more airflow sensors **466D**, the one or more airflow sensors **468G**, the one or more airflow sensors **468H**, the—can each measure one or more airflow attributes of airflow. Each of these sensors can include, for example, pressure sensors, pressure transducers, flow sensors, capnometers, humidity sensors, oximeters (oxygen sensors), thermometers (temperature sensors), other types of sensors discussed herein, or a combination thereof. The one or more airflow attributes can include, for example, airflow, pressure, speed, velocity, volume, temperature, moisture, humidity, O.sub.2 concentration, CO.sub.2 concentration, N concentration, Ar concentration, H.sub.2O concentration, other

sensor measurement data discussed herein, or a combination thereof. For instance, examples of any of the sensors of the airflow rerouting adapter **470** can include the capnometer **926**, the inspiratory mixture sensors **910**, the inspiratory mixture sensors **920**, the intratracheal sensors **934**, the capnometer **938**, the capnometer **948**, the expiratory mixture sensors **940**, the expiratory mixture sensors **950**, or a combination thereof. Sensor data from the sensors of the airflow rerouting adapter **470** can be passed to a controller **480**. The controller **480** can control airflow provision (e.g., of the secondary inspiratory airflow and/or of the secondary expiratory airflow) by the inspiratory gas provision system **490**. The controller **480** can be an example of a controller **170**.

[0092] In some examples, the inspiratory gas provision system **490** can include gas sources, gas mixer, gas property control, humidifier, warmer, heat and moisture exchanger, capnometer, inspiratory mixture pressurizer, buffer, inspiratory mixture sensors (e.g., pressure and flow), gas property control (humidifier, warmer, heat and moisture exchangers), pressure relieve valve. In some examples, the inspiratory gas provision system **490** can include, for example, the inspiratory flow control system(s) **150**, the inspiratory gas source(s) **160**, the gas sources **932**, the gas mixer(s) **930**, the gas property control(s) **928**, the capnometer(s) **926**, the inspiratory mixture pressurizer **914**, the buffer **912**, the inspiratory mixture sensors **910**, the gas property control **908**, the pressure release valve **906**, the inspiratory mixture pressurizer **924**, the buffer **922**, the inspiratory mixture sensors **920**, the gas property control **918**, the pressure release valve **916**, or a combination thereof.

[0093] In some examples, the controller **480** may mix, pressurize, heat, cool, humidify, dehumidify, or otherwise set one or more attributes of the secondary inspiratory airflow based on one or more one or more attributes of the primary inspiratory airflow as measured by the airflow sensor(s) **466C** and/or the inspiratory sensors **472A**. The controller **480** may verify that the attributes match using the inspiratory sensors **472B** and/or the airflow sensors **466D**. In some examples, the controller **480** may mix, pressurize, heat, cool, humidify, dehumidify, or otherwise set one or more attributes of the secondary expiratory airflow based on one or more one or more attributes of the primary expiratory airflow as measured by the airflow sensor(s) **468G** and/or the expiratory sensors **475A**. The controller **480** may verify that the attributes match using the expiratory sensors **475B** and/or the airflow sensors **468H**.

[0094] An airflow rerouting adapter **470** may provide technical improvements over the ventilator systems of FIGS. 4A-4C by allowing to provide uncontaminated with DCAs inspiratory gas via uncontaminated with DCAs inspiratory lumens, and customized control of inspiratory airflow and/or expiratory airflow using the inspiratory gas provision system **490**, while still using the framework of a ventilator system such as those of FIGS. 4A-4C, and simulating expected inspiratory airflow and/or expiratory airflow to the ventilator system using the inspiratory gas provision system **490**. In some examples, use of an airflow rerouting adapter **470** can provide some technical improvements similar to a ventilator system illustrated in FIGS. 5A-5D.

[0095] FIG. 5A is a conceptual diagram **500A** illustrating part of a ventilator system with an endotracheal tube (ETT) **120** that includes an expiratory lumen **510** that evacuates expiratory gas, a left inspiratory lumen **220** that provides inspiratory gas to the left primary bronchus **210** and left lung **130**, and a right inspiratory lumen **225** that provides inspiratory gas to the right primary bronchus **215** and right lung **135**. The left inspiratory lumen **220** and right inspiratory lumen **225** both extend beyond the tip **125** of the ETT **120** toward and/or into the patient **105**'s airways. The left inspiratory lumen **220** and right inspiratory lumen **225** both extend further into the patient **105**'s airways than the tip **125** of the ETT **120** does. In particular, the left inspiratory lumen **220** extends beyond the tip **125** of the ETT **120** toward the patient **105**'s left primary bronchus **210**, left lung **130**, and/or other left bronchi within the left lung **130**. The right inspiratory lumen **225** extends beyond the tip **125** of the ETT **120** toward the patient **105**'s right primary bronchus **215**, right lung **135**, and/or other right bronchi within the right lung **135**.

[0096] The left inspiratory lumen **220** and right inspiratory lumen **225** each provide a gaseous volume of inspiratory gas(es) to different portions of the patient **105**'s airways. The left inspiratory lumen **220** provides a first (left) gaseous volume of inspiratory gas(es) to patient **105**'s left primary bronchus **210**, left lung **130**, other left bronchi within the left lung **130**, bronchioles **320** within the left lung **130**, alveoli **325** within the left lung **130**, or a combination thereof. An exemplary flow of the first (left) gaseous volume of inspiratory gas(es) down the left inspiratory lumen **220** and into the patient **105**'s airways is illustrated using white arrows outlined in black. The right inspiratory lumen **225** provides a second (right) gaseous volume of inspiratory gas(es) to patient **105**'s right primary bronchus **215**, right lung **135**, other right bronchi within the right lung **135**, bronchioles **325** within the right lung **135**, alveoli **325** within the right lung **135**, or a combination thereof. An exemplary flow of the second (right) gaseous volume of inspiratory gas(es) down the right inspiratory lumen **225** and into the patient **105**'s airways is illustrated using white arrows outlined in black.

[0097] The ETT **120** of FIG. 5A houses an expiratory lumen **510**. For instance, as illustrated in FIG. 6 and FIG. 7A, any space in the ETT **120** not taken up by the left inspiratory lumen **220** or the right inspiratory lumen **225** can be used as an expiratory lumen **510**. Thus, the tip **125** of the ETT **120** is also the tip of the expiratory lumen **510**. Thus, in FIG. 5A, the left inspiratory lumen **220** and right inspiratory lumen **225** both extend beyond the tip of the expiratory lumen **510** toward the patient **105**'s airways. The left inspiratory lumen **220** and right inspiratory lumen **225** both extend further into the patient **105**'s airways than the tip of the expiratory lumen **510** does. The expiratory lumen **510**, as illustrated in FIG. 4B, is receiving and/or evacuating expiratory gas(es) from the patient **105**'s airways. An exemplary flow of the expiratory gas(es) up the expiratory lumen **510** and from the trachea **115** and bronchi of the left lung **130** and the right lung **135** is illustrated using white arrows shaded with black dots and outlined in black.

[0098] The ventilator systems of FIGS. 5A-5C reduce dead space **410** compared to the ventilator systems of FIGS. 4A-4C by having inspiratory gas delivered more directly and proximally to the alveoli, and in most embodiment and most of ventilatory modes (as illustrated on FIGS. 8A-8E) by continuous or all almost continuous clearing of the dead space with continuous gas flow between the inspiratory lumen or lumens and expiratory lumen or lumens. The dead space **410** in FIGS. 5A-5C is identified by shaded regions similar to those that indicate dead space **410** in FIGS. 4A-4C. The reduction in dead space **410** and continuous or close to continuous clearance of dead space **410** can reduce the ventilator's ability to spread DCAs **425** from diseased portions of a patient **105**'s airways to healthy portions of the patient **105**'s airways, as illustrated in FIG. 5B. Additionally, inspiratory gas can be consistently and/or continuously delivered to the lungs **130-135** by clean (non-contaminated) inspiratory lumens **250/255**, as all contaminated expiratory gas leaves the lungs via separate expiratory lumen(s) **510/520/525**.

[0099] FIG. 5B is a conceptual diagram **500B** illustrating part of the ventilator system of FIG. 5A where the right lung **135** is diseased and the left lung **130** is healthy. Like FIG. 4A, the right lung **135** of FIG. 5B includes two infected alveoli **420** and a recovered alveolus **430**. Several DCAs **425** are illustrated near the two infected alveoli **420** in the diseased right lung **135**. However, the ventilator system(s) of FIGS. 5A-5C does not spread the DCAs **425** to different parts of the patient **105**'s airways as readily as the ventilator system(s) of FIGS. 4A-4C. For instance, the ventilator system(s) FIGS. 5A-5C include physical separation between the tip of the expiratory lumen **510** (the tip **125** of the ETT **120**) and tips of the inspiratory lumens (the left inspiratory lumen **220** and the right inspiratory lumen **225**), preventing dead space cross between the left lung **130** (and/or the left primary bronchus **210**) and the right lung **135** (and/or the right primary bronchus **215**) through which DCAs **425** could otherwise cross between left lungs/bronchi and right lungs/bronchi. The ventilator system(s) FIGS. 5A-5C include physical separation between the tip of the left inspiratory lumen **220** and the tip of the right inspiratory lumen **225**, also preventing dead space between the left lung **130** (and/or the left primary bronchus **210**) and the right lung **135** (and/or the right primary bronchus **215**) through which DCAs **425** could otherwise cross between lungs/bronchi.

[0100] FIG. 5C is a conceptual diagram **500C** illustrating part of a ventilator system with an endotracheal tube (ETT) **120** that includes a left expiratory lumen **520** that evacuates expiratory gas from a left primary bronchus **210** and left lung **130**, a right expiratory lumen **525** that evacuates expiratory gas from a right primary bronchus **215** and right lung **135**, a left inspiratory lumen **220** that provides inspiratory gas to the left primary bronchus **210** and left lung **130**, and a right inspiratory lumen **225** that provides inspiratory gas to the right primary bronchus **215** and right lung **135**. The ventilator system of FIG. 5C is similar to the ventilator system of FIGS. 5A and 5B, for instance because the ventilator system of FIG. 5C also includes the left inspiratory lumen **220** and the right inspiratory lumen **225**. The left inspiratory lumen **220** and the right inspiratory lumen **225** of the ventilator system of FIG. 5C function similarly to the left inspiratory lumen **220** and the right inspiratory lumen **225** of the ventilator system of FIGS. 5A and 5B.

[0101] However, the ventilator system of FIG. 5C includes the left expiratory lumen **520** and the right expiratory lumen **525** in place of a single expiratory lumen **510** of the ventilator system of FIGS. 5A and 5B. The left expiratory lumen **520** and right expiratory lumen **525** both extend beyond the tip **125** of the ETT **120** toward and/or into the patient **105**'s airways. The left expiratory lumen **520** and right expiratory lumen **525** both extend further into the patient **105**'s airways than the tip **125** of the ETT **120** does. In particular, the left expiratory lumen **520** extends beyond the tip **125** of the ETT **120** toward the patient **105**'s left primary bronchus **210**, left lung **130**, and/or other left bronchi within the left lung **130**. The right expiratory lumen **525** extends beyond the tip **125** of the ETT **120** toward the patient **105**'s right primary bronchus **215**, right lung **135**, and/or other right bronchi within the right lung **135**.

[0102] In some examples (as illustrated in FIG. 4C), the left inspiratory lumen **220** extends beyond the tip of the left expiratory lumen **520** toward and/or into the patient **105**'s airways. In some examples (as illustrated in FIG. 4C), the left inspiratory lumen **220** extends further into the patient **105**'s airways than the tip of the left expiratory lumen **520**. In some examples (as illustrated in FIG. 4C), the right inspiratory lumen **225** extends beyond the tip of the right expiratory lumen **525** toward and/or into the patient **105**'s airways. In some examples (as illustrated in FIG. 4C), the right inspiratory lumen **225** extends further into the patient **105**'s airways than the tip of the right expiratory lumen **525**.

[0103] In some examples (not illustrated), the left expiratory lumen **520** extends beyond the tip of the left inspiratory lumen **220** toward and/or into the patient **105**'s airways. In some examples (not illustrated), the left expiratory lumen **520** extends further into the patient **105**'s airways than the tip of the left inspiratory lumen **220**. In some examples (not illustrated), the right expiratory lumen **525** extends beyond the tip of the right inspiratory lumen **225** toward and/or into the patient **105**'s airways. In some examples (not illustrated), the right expiratory lumen **525** extends further into the patient **105**'s airways than the tip of the right inspiratory lumen **225**.

[0104] The left expiratory lumen **520** and the right expiratory lumen **525**, as illustrated in FIG. 5C, are both receiving and/or evacuating expiratory gas(es) from different parts of the patient **105**'s airways. An exemplary flow of the expiratory gas(es) up the left expiratory lumen **520** from the bronchi of the left lung **130** is illustrated using white arrows shaded with black dots and outlined in black. An exemplary flow of the expiratory gas(es) up the right expiratory lumen **525** from the bronchi of the right lung **135** is illustrated using white arrows shaded with black dots and outlined in black.

[0105] In some examples, the left inspiratory lumen **220** and the left expiratory lumen **520** are coupled together. In some examples, the right inspiratory lumen **225** and the right expiratory lumen **525** are coupled together. In some examples, the left inspiratory lumen **220** and the left expiratory lumen **520** are two distinct parts of a single lumen, for example with a membrane in between (as in FIG. 7B). In some examples, the right inspiratory lumen **225** and the right expiratory lumen **525** are two distinct parts of a single lumen, for example with a membrane in between (as in FIG. 7B).

[0106] In some examples, a balloon **530** for the left lumens (the left inspiratory lumen **220** and the left expiratory lumen **520**) may, in its inflated state (as illustrated in FIG. 5C), secure the left lumens in position in the trachea **115** and/or left primary bronchus **210**, protect the trachea **115** and/or left primary bronchus **210** from being damaged by the left lumens, and/or prevent airflows from passing through the trachea **115** and/or left primary bronchus **210** other than through the left lumens. In some examples, a balloon **535** for the right lumens (the right inspiratory lumen **225** and the right expiratory lumen **525**) may, in its inflated state (as illustrated in FIG. 5C), secure the right lumens in position in the trachea **115** and/or right primary bronchus **215**, protect the trachea **115** and/or right primary bronchus **215** from being damaged by the right lumens, and/or prevent airflows from passing through the trachea **115** and/or right primary bronchus **215** other than through the right lumens. In some examples, the balloon **530** and/or the balloon **535** may be missing and/or may be intentionally left uninflated, for example to prevent unintentionally producing one or more ulcers, because the balloon **205** may be safer, and/or because the balloon **205** may provide sufficient isolation of airflow on its own in some circumstances. In some examples, a controller **170** of a pneumatic system **140** can adjust pressures to help prevent airflow from crossing between the left lung **130** and the right lung even without presence or inflation of the balloon **530** and/or the balloon **535**. In some examples, the balloon **205** may be missing and/or may be intentionally left uninflated, because the balloon **530** and/or the balloon **535** may provide sufficient isolation of airflow without the balloon **205**.

[0107] In some examples, the left expiratory lumen **520**, the right expiratory lumen **525**, the left inspiratory lumen **220**, and/or the right inspiratory lumen **225** can include one or more valves for uni-directional gas flow. Valves for uni-directional gas flow can prevent expiratory gas from getting into the left inspiratory lumen **220** and/or the right inspiratory lumen **225**. Valves for uni-directional gas flow can prevent inspiratory gas from getting into the left expiratory lumen **520** and/or the right expiratory lumen **525**. This can be particularly useful when an adapter such as the connector **610** of FIG. 6 is used. Such valves can improve isolation of inspiratory and expiratory lumens.

[0108] In some examples, the left expiratory lumen **520** and the right expiratory lumen **525** can reach positions at or adjacent to the carina of the left primary bronchus **310** and the carina of the right primary bronchus **315**, respectively. In some examples, the left inspiratory lumen **220** and the right inspiratory lumen **225** can reach positions past (and/or further deeper into the bronchial tree than) the carina of the left primary bronchus **310** and the carina of the right primary bronchus **315**, respectively.

[0109] In some examples, the left expiratory lumen **520**, the right expiratory lumen **525**, the left inspiratory lumen **220**, and/or the right inspiratory lumen **225** can extend deeper into a patient **105**'s bronchial tree, which may further reduce dead space. For instance, the left expiratory lumen **520**, the right expiratory lumen **525**, the left inspiratory lumen **220**, and/or the right inspiratory lumen **225** can extend into secondary bronchi, tertiary bronchi, 4.sup.th order bronchi, 5.sup.th order bronchi, 6.sup.th order bronchi, and so forth, or some combination thereof. The tips of the left inspiratory lumen **220** and/or left expiratory lumen **520** can extend into the superior lobe and/or the inferior lobe of the left lung **130**. The tips of the right inspiratory lumen **225** and/or the right expiratory lumen **525** can extend into the superior lobe, the middle lobe, or the inferior lobe of the right lung **135**. In an illustrative example, the tips of the left expiratory lumen **520** and the right expiratory lumen **525** extend into the superior lobes of the left lung **130** and the right lung **135**, while the tips of the left inspiratory lumen **220** and the right inspiratory lumen **225** extend into inferior lobes of the left lung **130** and the right lung **135**. The arrangement in this illustrative example can reduce dead space **410** by a particularly significant amount. In some examples, the left expiratory lumen **520**, the right expiratory lumen **525**, the left inspiratory lumen **220**, and/or the right inspiratory lumen **225** can themselves branch off into further sub-lumens, for example with different sub-lumens going into different bronchi (e.g., different secondary bronchi, tertiary bronchi, 4.sup.th order bronchi, 5.sup.th order bronchi, 6.sup.th order bronchi, and so forth).

[0110] In some examples, different lumens (e.g., the left expiratory lumen **520**, the right expiratory lumen **525**, the left inspiratory lumen **220**, and/or the right inspiratory lumen **225**) can include markers (e.g., at the

tips of the lumens and/or along the lengths of the lumens) that allow the lumens to be located using a scan of the patient **105** and/or using triangulation. The markers can include materials that are visible in scans of the patient **105**, such as radiopaque markers, radiolucent markers, radioactive tracers. Scans may include X-ray scans, magnetic resonance imagery (MRI) scans, computerized tomography (CT) scans, computed axial tomography (CAT) scans, C-arm scans, positron emission tomography (PET) scans, fluoroscopy scans, angiography scans, or combinations thereof. In some examples, the markers may include solenoids, magnetic field emitters, electromagnetic field emitters, wireless signal transmitters, or a combination thereof. Such markers may be located within the patient **105** by detecting the fields or signals transmitted by the markers and detecting distance between the receiver(s) and the marker transmitting the signals based on signal travel time, signal frequency shift, and/or another change in a signal property between transmission of the signal and receipt of the signal. Such markers may be located within the patient **105** using triangulation, by detecting the fields or signals transmitted by the markers using multiple receivers or using a single receiver at multiple points in time.

[0111] FIG. 5D is a conceptual diagram **500D** illustrating part of a ventilator system with an endotracheal tube (ETT) **120** that includes an inspiratory lumen **540** that provides inspiratory gas, a left expiratory lumen **520** that evacuates expiratory gas from the left primary bronchus and left lung **130**, and a right expiratory lumen **525** that evacuates expiratory gas from the right primary bronchus and right lung **135**.

[0112] As noted previously, it may be useful in the ventilator systems of FIGS. 5A-5D to include carbon dioxide (CO.sub.2) in the inspiratory gas mixture. For instance, depending on how inspiratory flows are set (see e.g., inspiratory flows **830A-830E**) and/or how expiratory flows are set (see e.g., inspiratory flows **835A-835E**), carbon dioxide (CO.sub.2) may be being evacuated excessively and/or from the patient **105**'s airways. Lack or decreased concentration of carbon dioxide (CO.sub.2) can increase alkalinity, pushing pH too high, and can cause negative effects such as alkalosis. Including carbon dioxide (CO.sub.2) in the inspiratory gas mixture can offset the evacuation of carbon dioxide (CO.sub.2), reducing alkalinity, lowering pH, and preventing negative effects such as alkalosis.

[0113] In some examples, the ventilator systems of FIGS. 5A-5D may be modified to include only inspiratory lumen into only one lung and/or only one expiratory lumen into only one lung. For instance, the ventilator systems of FIGS. 5A-5D may be modified to include only the left inspiratory lumen **220** without the right inspiratory lumen **225**, or to include only the right inspiratory lumen **225** without the left inspiratory lumen **220**. Similarly, the ventilator systems of FIGS. 5A-5D may be modified to include only the left expiratory lumen **520** without the right expiratory lumen **525**, or to include only the right expiratory lumen **525** without the left expiratory lumen **520**. Even in situations with only one inspiratory lumen **220/225** into only one lung **130/135** and/or only one expiratory lumen **520/525** into only one lung **130/135**, dead space **410** is still decreased relative to dead space **410** in ventilator systems of FIGS. 4A-4C, due to deeper division of inspiratory and expiratory airflow. In some examples, this type of modification may be desirable, for example to assist a patient that only has one functional lung and/or to make a low-cost ventilator system (e.g., to assist patients in developing countries).

[0114] FIG. 6 is a conceptual diagram **600** illustrating part of a ventilator system with an endotracheal tube (ETT) **120** that includes an expiratory lumen **510** that evacuates expiratory gas, a left inspiratory lumen **220** that provides inspiratory gas, and a right inspiratory lumen **225** that provides inspiratory gas. The ventilator system of FIG. 6 is similar to the ventilator system of FIGS. 5A and 5B in that the ventilator system of FIG. 6 includes an ETT **120** with a left inspiratory lumen **220**, a right inspiratory lumen **225**, an expiratory lumen **510**, a tip **125**, and a balloon **205**. The left inspiratory lumen **220** and the right inspiratory lumen **225** pass through at least part of the ETT **120**. The expiratory lumen **510** can include at least a part of the ETT **120**. A connector **610** can mechanically and/or pneumatically connect the left inspiratory lumen **220** and the right inspiratory lumen **225** to the ETT **120**. In some examples, the connector **610** can mechanically and/or pneumatically introduce the left inspiratory lumen **220** and the right inspiratory lumen **225** into the ETT **120**. The connector **610** can also mechanically and/or pneumatically couple the ETT **120** to the ventilator tubing **605**.

[0115] The ETT **120**, the expiratory lumen **510**, the left inspiratory lumen **220**, and/or the right inspiratory lumen **225**, can each extend downward in FIG. 6 toward the left lung **130**, right lung **135**, left primary bronchus **210**, right primary bronchus **215**, left secondary bronchi **310**, right secondary bronchi **315**, other bronchi, bronchioles **320**, alveoli **325**, or combinations thereof. The left inspiratory lumen **220**, and/or the right inspiratory lumen **225** can come from the left side of FIG. 6, from inspiratory tube(s) **152**, the inspiratory flow control system(s) **150**, inspiratory gas source(s) **160**, or a combination thereof. In some examples, the left inspiratory lumen **220** couples to its own inspiratory tube **152**, inspiratory flow control system **150**, and/or inspiratory gas source(s) **160**. In some examples, the right inspiratory lumen **225** couples to its own inspiratory tube **152**, inspiratory flow control system **150**, and/or inspiratory gas source(s) **160**. The ventilator tubing **605** can couple to the expiratory tube(s) **157**, the expiratory flow control system(s) **155**, the expiratory gas output(s) **165**, or a combination thereof. In another illustrative example the ventilator tubing **605** can couple to the patient interface **149**, 1.sup.st fitting **147** or 2.sup.nd fitting **148**, inspiratory tube(s) **152** and expiratory tube(s) **157**, the expiratory flow control system(s) **155**, the expiratory gas output(s) **165**, or a combination thereof. In the latter example, it would be the appropriate combination of pressures (high-pressure flow in inspiratory lumens left **220** and right **225**) that would direct the inspiratory gas from inspiratory lumens **220** and **225** into the expiratory tube(s) **157**, the expiratory flow control system(s) **155**, the expiratory gas output(s) **165**. Same high-pressure flow in the inspiratory lumens **220** and **225** would limit or stop the inflow of inspiratory gas via inspiratory tube(s) **152**.

[0116] Exemplary flows of the inspiratory gas(s) into, along, and out of each of the left inspiratory lumen **220** and the right inspiratory lumen **225** are illustrated using white arrows that are outlined in black. Exemplary flows of the expiratory gas(s) up the expiratory lumen **510** of the ETT **120**, up the ventilator tubing **605**, and out of the ventilator tubing are illustrated using white arrows shaded with black dots and outlined in black. In some examples, the connector **510** may also provide a left expiratory lumen **520** and a right expiratory lumen **525** as in FIGS. 5C and 5D. In some examples, the connector **610** may be used as an adapter **450** and/or as an adapter **455**. In some examples, use of the connector **610** as an adapter **450** and/or as an adapter **455** can provide a left inspiratory lumen **220**, a right inspiratory lumen **225**, a left expiratory lumen **520**, and/or a right expiratory lumen **525** to a ventilator system that might not otherwise include such lumens, such as the ventilator system(s) of FIGS. 4A-4D. In some examples, use of the connector **610** as an adapter **450** and/or as an adapter **455** can provide inspiratory airflow through the left inspiratory lumen **220** and/or right inspiratory lumen **225** from a separate inspiratory airflow source than the ventilator system to which the connector **610** is connected. The separate inspiratory airflow source can include, for example, the inspiratory flow control system(s) **150**, the inspiratory gas source(s) **160**, the inspiratory gas provision system **490**, the gas sources **932**, the gas mixer(s) **930**, the gas property control(s) **928**, the capnometer(s) **926**, the inspiratory mixture pressurizer **914**, the buffer **912**, the inspiratory mixture sensors **910**, the gas property control **908**, the pressure release valve **906**, the inspiratory mixture pressurizer **924**, the buffer **922**, the inspiratory mixture sensors **920**, the gas property control **918**, the pressure release valve **916**, or a combination thereof. In some examples, use of the connector **610** as an adapter **450** and/or as an adapter **455** can provide expiratory pressure and/or suction through the left expiratory lumen **520**, and/or a right expiratory lumen **525** from a separate expiratory pressure control, which can include, for example, expiratory tube(s) **157**, the expiratory flow control system(s) **155**, the expiratory gas output(s) **165**, the water trap **936**, the capnometer **938**, the expiratory mixture sensors **940**, the buffer **942**, the expiratory mixture pressurizer **944**, the water trap **946**, the capnometer **948**, the expiratory mixture sensors **950**, the buffer **952**, the expiratory mixture pressurizer **954**, or a combination thereof.

[0117] FIG. 7A is a conceptual diagram **700A** illustrating a cross-section of an endotracheal tube (ETT) **120** that includes an expiratory lumen **705** that evacuates expiratory gas, a left inspiratory lumen **220** that provides inspiratory gas, and a right inspiratory lumen **225** that provides inspiratory gas. In some examples, the left inspiratory lumen **220** and the right inspiratory lumen **225** can pass freely through the ETT **120**. In some examples, the left inspiratory lumen **220** and the right inspiratory lumen **225** can be

coupled to one another within at least a portion of the ETT **120**. In some examples, the left inspiratory lumen **220** and the right inspiratory lumen **225** can be two parts of a single lumen separated by a membrane, similarly to the separation of the first lumen **710** and the second lumen **715** by the membrane **720** in the tube **750** of FIG. 7B.

[0118] In some ventilator devices, the left inspiratory lumen **220** of FIG. 7A can instead be a left expiratory lumen **520**, the right inspiratory lumen **225** of FIG. 7A can instead be a right expiratory lumen **525**, and the expiratory lumen **705** can instead be an inspiratory lumen **540**. An example of such a ventilator device is illustrated in FIG. 5D.

[0119] In some ventilator devices, the ETT **120** of FIG. 7A can also include a left expiratory lumen **520** and/or a right expiratory lumen **525** in addition to the left inspiratory lumen **220** and the right inspiratory lumen **225**. In such ventilator devices, the ETT **120** itself can function as an expiratory lumen **705** as discussed above, as an inspiratory lumen **540**, as both, or as neither. An example of such a ventilator device is illustrated in FIG. 5C.

[0120] FIG. 7B is a conceptual diagram **700B** illustrating a cross-section of a tube **750** that includes a first lumen **710** and a second lumen **715** separated by a membrane **720**. In some examples, the membrane **720** can be stretch-compliant, allowing for the lumens cross section area to accommodate current needs. If more flow is required via first lumen **710**, the pressure within the first lumen **710** can be higher than in second lumen **715**, and the compliant membrane **720** can allow for first lumen **710** to consume some of space previously taken up by second lumen **715**. If more flow is required via second lumen **715**, the pressure within the second lumen **715** can be higher than in the first lumen **710**, and the compliant membrane **720** can allow for second lumen **715** to consume some of space previously taken up by first lumen **710**.

[0121] In some examples, the tube **750** is an ETT **120**. For instance, the first lumen **710** may be an inspiratory lumen, which may in some cases split into a left inspiratory lumen **220** and a right inspiratory lumen **225**. The second lumen **715** may be an expiratory lumen **510**, which may in some cases split into a left expiratory lumen **520** and a right expiratory lumen **525**. The balloon **740** for the tube **750** may be an example of the balloon **205** for the ETT **120**.

[0122] In some examples, the tube **750** includes the left inspiratory lumen **220** and the right inspiratory lumen **225** within the ETT **120**. For instance, the first lumen **710** may be the left inspiratory lumen **220**, and the second lumen **715** may be the right inspiratory lumen **225**. The balloon **740** for the tube **750** need not be present, or may be an example of the balloon **205** for the ETT **120**.

[0123] In some examples, the tube **750** includes the left lumens (the left inspiratory lumen **220** and the left expiratory lumen **520**) of FIG. 5C. For instance, the first lumen **710** may be the left inspiratory lumen **220**, and the second lumen **715** may be the left expiratory lumen **520**. The balloon **740** for the tube **750** may be an example of the balloon **530** for the left lumens of FIG. 5C.

[0124] In some examples, the tube **750** includes the right lumens (the right inspiratory lumen **225** and the right expiratory lumen **525**) of FIG. 5C. For instance, the first lumen **710** may be the right inspiratory lumen **225**, and the second lumen **715** may be the right expiratory lumen **525**. The balloon **740** for the tube **750** may be an example of the balloon **535** for the right lumens of FIG. 5C.

[0125] In some examples, the tube **750** includes an inspiratory tube **152** and an expiratory tube **157**. For instance, the first lumen **710** may be the inspiratory tube **152**, and the second lumen **715** may be the expiratory tube **157**.

[0126] In some examples, the tube **750** includes two inspiratory tubes **152**. For instance, the first lumen **710** may be a first inspiratory tube **152** that provides inspiratory gas(es) to a left inspiratory lumen **220**

and/or from a first inspiratory flow control system **150** and/or a first set of inspiratory gas source(s) **160**. The second lumen **715** may be a second inspiratory tube **152** that provides inspiratory gas(es) to a right inspiratory lumen **225** and/or from a second inspiratory flow control system **150** and/or a second set of inspiratory gas source(s) **160**.

[0127] In some examples, the tube **750** includes two expiratory tubes **157**. For instance, the first lumen **710** may be a first expiratory tube **157** that provides expiratory gas(es) from a left expiratory lumen **520** and/or to a first expiratory flow control system **155** and/or a first set of expiratory gas output(s) **165**. The second lumen **715** may be a second expiratory tube **157** that provides expiratory gas(es) from a right expiratory lumen **525** and/or to a second expiratory flow control system **155** and/or a second set of expiratory gas output(s) **165**.

[0128] FIG. 8A is a graph diagram **800A** illustrating inspiratory flow **830A**, expiratory flow **835A**, and pressure changes **850** over time **815** in a ventilator system according to a first illustrative example. A flow graph **805A** and a pressure graph **810A** are illustrated in FIG. 8A. The flow graph **805A** and the pressure graph **810A** both include a shared horizontal time axis **815**. The time axis **815** is the same for FIGS. 8A-8E, and includes times marked at time zero (0), at time t.sub.A, at time t.sub.B after time t.sub.A, at time t.sub.C after time t.sub.F, at time t.sub.H after time t.sub.C, at time t.sub.E after time t.sub.E, at time t.sub.F after time t.sub.E, at time t.sub.G after time t.sub.F, and at time h after time t.sub.G. The timespan from time zero (0) to time t.sub.H is an example of portion of a longer period of time with multiple inspirations and multiple corresponding expirations.

[0129] The pressure graph **810** graphs pressure within a patient **105**'s lungs **130-135** (and/or another portion of the patient **105**'s airways) over time **815**. The pressure graph **810** includes a vertical pressure axis **825**. The vertical pressure axis **825** may measure pressure in centimeters of water (cmH.sub.2O) or another pressure unit. Graphed pressure changes **850** in pressure **825** are tracked over time **815**, and fluctuate from a value of zero (0) cmH.sub.2O to a value of p cmH.sub.2O. The graphed pressure changes **850** of the pressure graph **810A** span two (2) cycles of inspiration and expiration. The value of zero (0) cmH.sub.2O, within the context of the graphed pressure changes **850**, represent the pressure in the patient **105**'s airways when the patient **105** has fully exhaled, or been made to fully exhale by the pressurizer(s) of the ventilator system. The value of p cmH.sub.2O, within the context of the graphed pressure changes **850**, represent the pressure in the patient **105**'s airways when the patient **105** has fully inhaled, or been made to fully inhale by the pressurizer(s) of the ventilator system. In some examples, the pressure graphed in the pressure **825** may be a relative pressure rather than an absolute pressure. For instance, the pressure changes curve **850** reaching a pressure zero (0) may not mean that there is literally no pressure in the patient **105**'s lungs **130/135**, but may refer to patient **105**'s lungs **130/135** having a baseline pressure level (e.g., atmospheric pressure, or end expiratory pressure (EEP) or positive end expiratory pressure (PEEP)). Likewise, the pressure changes curve **850** reaching the pressure p may not mean that p is the total pressure in the patient **105**'s lungs, but may simply refer to pressure p added to the baseline pressure level.

[0130] In some examples, the inspiratory flows **830A-830E** represent sum of all inspiratory flows through all inspiratory lumens of a ventilator system (e.g., inspiratory lumens **220**, **225**, and/or **540**). In some examples, the inspiratory flows **830A-830E** represents individual inspiratory flows through an individual inspiratory lumen (e.g., inspiratory lumen **220**, **225**, or **540**). In some examples, the inspiratory flows **830A-830E** represent sum of all inspiratory flows through a subset of inspiratory lumens of a ventilator system (e.g., inspiratory lumens **220**, **225**, and/or **540**). In some examples, the expiratory flows **835A-835E** represent sum of all expiratory flows through all expiratory lumens of a ventilator system (e.g., expiratory lumens **520**, **525**, **510**, and/or **705**). In some examples, the expiratory flows **835A-835E** represents individual expiratory flows through an individual expiratory lumen (e.g., expiratory lumen **520**, **525**, **510**, or **705**). In some examples, the expiratory flows **835A-835E** represent sum of all expiratory flows through a subset of expiratory lumens of a ventilator system (e.g., expiratory lumens **520**, **525**, **510**, and/or **705**).

[0131] From time zero (0) to time t.sub.A, the patient **105** is inhaling (and/or is being made to inhale by the pressurizer(s) of the ventilator system) and thus increasing pressure from an end expiratory pressure (EEP) up to pressure p. The increase in pressure from time zero (0) to time t.sub.A may be caused by an absolute value of an inspiratory flow (of the inspiratory flows **830A-830E**) being higher than an absolute value of a corresponding expiratory flow (of the expiratory flows **835A-835E**) from time zero (0) to time t.sub.A. From time t.sub.A to time t.sub.B, the patient **105** is holding their breath (and/or is being made to hold their breath by the pressurizer(s) of the ventilator system) and thus maintaining pressure p. Maintenance of the pressure p to hold the patient's breath, as in time t.sub.A to time t.sub.B, may be referred to as inspiratory hold. The maintenance in pressure from time t.sub.A to time t.sub.B may be caused by an absolute value of an inspiratory flow (of the inspiratory flows **830A-830E**) matching, or being substantially equal to, an absolute value of the corresponding expiratory flow (of the expiratory flows **835A-835E**) from time t.sub.A to time t.sub.B. From time t.sub.B to time t.sub.D, the patient **105** is exhaling (and/or is being made to exhale by the pressurizer(s) of the ventilator system) thus reducing pressure from pressure p back down to the end expiratory pressure (EEP). The decrease in pressure from time t.sub.B to time t.sub.D may be caused by an absolute value of an inspiratory flow (of the inspiratory flows **830A-830E**) being lower than an absolute value of the corresponding expiratory flow (of the expiratory flows **835A-835E**) from time t.sub.B to time t.sub.D. Time zero (0) to time t.sub.D represents a single inhale-exhale cycle. A second inhale-exhale cycle occurs from time t.sub.D to time hi, and generally matches the first inhale-exhale cycle from time zero (0) to time t.sub.D.

[0132] The pressure in the patient **105**'s airways when the patient **105** has fully exhaled may be referred to as an end expiratory pressure (EEP). In some cases, the EEP may be zero (0) cmH.sub.2O. In some cases, the EEP may be higher than zero (0) cmH.sub.2O. In some cases, the EEP may be less than zero (0) cmH.sub.2O (e.g., may be a negative pressure). The value of the graphed pressure changes **850** at a given point in time may be a value relative to the pressure in the patient **105**'s airways when the patient **105** has fully exhaled (the EEP), rather than an absolute pressure value. The graphed pressure changes **850** in the pressure graph **810** are the same for FIGS. 8A-8E.

[0133] The flow graph **805A** of FIG. 8A tracks an inspiratory flow **830A** and an expiratory flow **835A** over time **815**. The inspiratory flow **830A** and the expiratory flow **835A** are tracked along a vertical flow axis **820**. The vertical flow axis **820** may measure flow in cubic centimeters per second (cc/s) or another flow unit. The vertical flow axis **820** identifies zero (0) cc/s, three identified positive values (f.sub.A, f.sub.B, and f.sub.C), and three identified negative values (f.sub.D, f.sub.E, and f.sub.F). The positive values (f.sub.A, f.sub.B, and f.sub.C) represent inspiratory flow into the patient **105**'s airways. The negative values (f.sub.D, f.sub.E, and f.sub.F) represent expiratory flow out of the patient **105**'s airways. These flow values are used in the inspiratory flows **830A-830E** and in the expiratory flows **835A-835E** of FIGS. 8A-8E. In some examples, flow values f.sub.A and f.sub.D may share an absolute value, for instance f.sub.D with f.sub.A being multiplied by -1 and vice versa. In some examples, flow values f.sub.B and f.sub.E may share an absolute value, for instance f.sub.B with f.sub.E being multiplied by -1 and vice versa. In some examples, flow values f.sub.C and f.sub.F may share an absolute value, for instance f.sub.C with f.sub.F being multiplied by -1 and vice versa.

[0134] From time zero (0) to time t.sub.A, during which the patient **105** is inhaling (and/or being made to inhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830A** provides relatively low continuous flow of inspiratory gas to the patient **105**'s airways at relatively low flow rate f.sub.A to provide the patient **105** with inspiratory gas to inhale during the inhalation from time zero (0) to time t.sub.A. From time t.sub.A to time t.sub.B, during which the patient **105** is holding his/her breath (and/or being made to hold his/her breath by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830A** provides zero (0) flow of inspiratory gas to the patient **105**'s airways at flow value zero (0) so as not to over pressurize the patient **105**'s airways. The period from time t.sub.A to time t.sub.B may be referred to as an "inspiratory hold," and may be when some of the gas exchange between the blood and alveoli gas (e.g., blood oxygenation, CO.sub.2 extraction) happens

in the patient **105**'s respiratory and circulatory systems, and/or where inspiratory flow may match expiratory flow for net zero flow to exchange expiratory gases (e.g., from the lungs **130/135** and including dead space **410** with suspected DCAs **425**) for clean inspiratory gases. From time zero (0) to time t.sub.B, the expiratory flow **835A** is zero (0) and thus is not evacuating and/or receiving expiratory gas from the patient **105**'s airways, for instance so as not to interfere with inhalation. Net flow from time zero (0) to time t.sub.A may be positive, producing the inhalation. Net flow time t.sub.A to time t.sub.B may be zero, producing the inspiratory hold. From time t.sub.B to time t.sub.D, during which the patient **105** is exhaling (and/or being made to exhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **835A** evacuates and/or receives a relatively high continuous flow of expiratory gas from the patient **105**'s airways at relatively high (high absolute value) flow rate f.sub.E. From time t.sub.B to time t.sub.D, the absolute value of the expiratory flow f.sub.E may be higher than the absolute value of the inspiratory flow f.sub.A, resulting in a net effect of expiration, which can help evacuate CO.sub.2-rich and O.sub.2-deficient and potentially DCA **425**-including expiratory gas from the patient **105**'s airways. From time t.sub.B to time t.sub.D, during which the patient **105** is exhaling (and/or being made to exhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830A** provides relatively low continuous flow of inspiratory gas to the patient **105**'s airways at relatively low flow rate f.sub.A to maintain continuous airflow to perform gas exchange (exchanging contaminated expiratory air for clean inspiratory air) and clear out dead space **410** (and any DCAs **425** suspended therein) from the patient **105**'s lungs **130/135** and airways generally. Net flow from time t.sub.B to time t.sub.D may be negative, producing the exhalation. The period of time from time zero (0) to time t.sub.H represents a single inhale-exhale cycle. A second inhale-exhale cycle occurs from time t.sub.D to time t.sub.H. The continuous inspiratory and expiratory flows can provide continuous clearance and removal of dead space **410** with any DCAs **425** suspended therein.

[0135] During the expiration phases (from time t.sub.B to time t.sub.D and from time t.sub.F to time t.sub.H), even though expiration happens, there is a continuous flow between inspiratory and expiratory lumens, which allows the ventilator system to clear out dead space **410** (along with any DCAs **425** included within the dead space **410**). Furthermore, because the inspiratory lumens are separate from the expiratory lumens, inspiration lumens remain noncontaminated or less contaminated with virions or other DCAs **425**, so still-healthy alveoli **325** (and their pneumocytes) or alveoli that already recovered have a chance to obtain noncontaminated air.

[0136] In the pressure graph **810** and the flow graphs **805A-805E** of FIGS. 8A-8E, the length of expiration phases (from time t.sub.B to time t.sub.D and from time t.sub.F to time t.sub.H) are longer than the length of the inspiration phases (from time zero to time t.sub.A and from time t.sub.D to time t.sub.E) so there is enough time for expiration, and in some cases to prevent negative issues such as intrinsic positive end expiratory pressure (PEEP). Intrinsic PEEP can also be referred to as autoPEEP or PEEPi. Intrinsic PEEP can occur when expiratory time is shorter than the time needed to fully deflate the lungs, preventing the lung and chest wall from reaching an elastic equilibrium point, also referred to as "gas trapping."

[0137] FIG. 8B is a graph diagram **800B** illustrating inspiratory flow **830B**, expiratory flow **835B**, and pressure changes **850** over time **815** in a ventilator system according to a second illustrative example. The pressure graph **810** of FIG. 8B matches the pressure graph **810** of FIG. 8A.

[0138] The flow graph **805B** of FIG. 8B tracks an inspiratory flow **830B** and an expiratory flow **835B** over time **815**, and along the vertical flow axis **820**. In the flow graph **805B**, the expiratory flow **835B** evacuates and/or receives a relatively low continuous flow of expiratory gas from the patient **105**'s airways at relatively low (low absolute value) flow rate f.sub.D from time zero (0) to time t.sub.A. In the flow graph **805B**, the expiratory flow **835B** evacuates and/or receives a relatively high flow of expiratory gas from the patient **105**'s airways at relatively high (relatively high absolute value) flow rate f.sub.E from time t.sub.A to time t.sub.D. Under the expiratory flow **835B** of FIG. 8B, the expiratory flow **835B** continuously evacuates at least some of the CO.sub.2-rich and O.sub.2-deficient and potentially DCAs **425**-including expiratory

gas from the patient **105**'s airways, though the rate varies slightly by time. This continuously maintained expiratory flow **835B** can allow the ventilator system to clear out dead space **410** (along with any DCAs **425** included within the dead space **410**).

[0139] From time zero (0) to time t.sub.A, during which the patient **105** is inhaling (and/or being made to inhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830B** provides relatively high continuous flow of inspiratory gas to the patient **105**'s airways at relatively high flow rate f.sub.B to ensure that the patient **105** has inspiratory gas to inhale during the inhalation from time zero (0) to time t.sub.A. Net flow time zero (0) to time t.sub.A may be positive, producing the inhalation. Net flow time t.sub.A to time B may be zero, producing the inspiratory hold. From time t.sub.A to time t.sub.B, during which the patient **105** is holding his/her breath (and/or being made to hold his/her breath by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830B** still provides the relatively high continuous flow of inspiratory gas to the patient **105**'s airways at relatively high flow rate f.sub.B matching the relatively high flow of expiratory gas (f.sub.E) from time t.sub.A to time t.sub.B to ensure clearance of dead space **410** (and any DCAs **425** therein) and help the patient's lungs **130-135** to perform gas exchange. From time t.sub.B to time t.sub.D, during which the patient **105** is exhaling (and/or being made to exhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830B** provides relatively low continuous flow of inspiratory gas to the patient **105**'s airways at relatively low flow rate f.sub.A to continue to perform gas exchange (exchanging contaminated expiratory air for clean inspiratory air) and continue to clear out dead space **410** (and any DCAs **425** suspended therein) from the patient **105**'s lungs **130/135** and airways generally. Net flow time t.sub.B to time t.sub.D may be negative, producing the exhalation. With the relatively low flow rate f.sub.A of inspiratory flow **830B** from time t.sub.B to time t.sub.D, and the relatively high absolute flow rate f.sub.E of expiratory flow **835B** from time t.sub.B to time t.sub.D, the net effect can be a decrease in pressure in the lungs as illustrated in the pressure changes **850**. Continuous inspiratory and expiratory flows can provide continuous clearance and removal of dead space **410** with any DCAs **425** suspended therein.

[0140] The period of time from time zero (0) to time t.sub.D represents a single inhale-exhale cycle. A second inhale-exhale cycle occurs from time t.sub.D to time t.sub.H.

[0141] FIG. 8C is a graph diagram **800C** illustrating inspiratory flow **830C**, expiratory flow **835C**, and pressure changes **850** over time **815** in a ventilator system according to a third illustrative example. The pressure graph **810** of FIG. 8C matches the pressure graphs **810** of FIGS. 8A and 8B.

[0142] The flow graph **805C** of FIG. 8C tracks an inspiratory flow **830C** and an expiratory flow **835C** over time **815**, and along the vertical flow axis **820**.

[0143] From time zero (0) to time t.sub.A, during which the patient **105** is inhaling (and/or being made to inhale his/her breath by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **835C** is approximately zero (0) or very low and the inspiratory flow **830C** is not zero. From time t.sub.A to time t.sub.B, during which the patient **105** is holding his/her breath (and/or being made to hold his/her breath by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **835C** evacuates and/or receives a relatively high continuous flow of expiratory gas from the patient **105**'s airways at relatively high (high absolute value) flow rate f.sub.E to help evacuate CO.sub.2-rich and O.sub.2-deficient and potentially DCA **425**-including expiratory gas from the patient **105**'s airways. From time t.sub.B to time to, during which the patient **105** is exhaling (and/or being made to exhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **835C** evacuates and/or receives a relatively low continuous flow of expiratory gas from the patient **105**'s airways at relatively low (low absolute value) flow rate f.sub.D to help evacuate CO.sub.2-rich and O.sub.2-deficient and potentially DCA **425**-including expiratory gas from the patient **105**'s airways. The high expiratory flow **835C** in FIG. 8C maintained during the inspiratory flow can allow the ventilator system to

rapidly clear out significant amounts dead space **410** (along with any DCAs **425** included within the dead space **410**), and can be replaced with high inspiratory flow as discussed below to perform gas exchange within the patient **105**'s lungs **130/135** and airways generally.

[0144] From time zero (0) to time t.sub.A, during which the patient **105** is inhaling (and/or being made to inhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830C** provides relatively low continuous flow of inspiratory gas to the patient **105**'s airways at relatively low flow rate f.sub.A to provide the patient **105** with inspiratory gas to inhale during the inhalation from time zero (0) to time t.sub.A. Net flow time zero (0) to time t.sub.A may be positive, producing the inhalation. From time t.sub.A to time t.sub.B, during which the patient **105** is holding his/her breath (and/or being made to hold his/her breath by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830C** provides a relatively high continuous flow of inspiratory gas to the patient **105**'s airways at relatively high flow rate f.sub.B to perform gas exchange (exchanging contaminated expiratory air for clean inspiratory air) and continue to clear out dead space **410** (and any DCAs **425** suspended therein) from the patient **105**'s lungs **130/135** and airways generally. Net flow from time t.sub.A to time to may be zero, producing the inspiratory hold. The relatively high flow rate f.sub.B for the inspiratory flow **830C** from time t.sub.A to time t.sub.B can be used to offset the relatively high flow rate f.sub.E for the expiratory flow **835C** from time t.sub.A to time t.sub.B. From time t.sub.B to time to, during which the patient **105** is exhaling (and/or being made to exhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830C** provides no flow, or very low continuous flow, of inspiratory gas to the patient **105**'s airways. Net flow time t.sub.B to time to may be negative, producing the exhalation. Because expiratory flow **835C** is still active from time t.sub.D to time t.sub.E, the clearance of dead space **410** and DCAs **425** continues from time t.sub.D to time t.sub.E. However, the clearance can be lower and/or slower during the time h.sub.B to t.sub.D in graph **805C** than as it was during the time t.sub.B to t.sub.D in ventilatory system modes of operation presented on graphs **805A-805B**, as there is no (or very low) inspiratory flow in ventilatory system mode as shown on graph **805C** during the time t.sub.B to t.sub.D. Continuous inspiratory and expiratory flows can provide continuous clearance and removal of dead space **410** with any DCAs **425** suspended therein.

[0145] The period of time from time zero (0) to time to represents a single inhale-exhale cycle. A second inhale-exhale cycle occurs from time t.sub.D to time t.sub.H.

[0146] FIG. 8D is a graph diagram **800D** illustrating inspiratory flow **830D**, expiratory flow **835D**, and pressure changes **850** over time **815** in a ventilator system according to a fourth illustrative example. The pressure graph **810** of FIG. 8D matches the pressure graphs **810** of FIGS. 8A-8C.

[0147] The flow graph **805D** of FIG. 8D tracks an inspiratory flow **830D** and an expiratory flow **835D** over time **815**, and along the vertical flow axis **820**. In the flow graph **805D**, the inspiratory flow **830D** provides relatively low continuous flow of inspiratory gas to the patient **105**'s airways at relatively low flow rate f.sub.A during the entire period of time **815** from time zero (0) onward, to continuously provide the patient **105** with inspiratory gas to inhale during inhalations and/or to perform gas exchange and dead space clearance with suspended DCAc.

[0148] From time zero (0) to time t.sub.A, during which the patient **105** is inhaling (and/or being made to inhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **830D** is approximately zero (0), or very low. Net flow from time zero (0) to time t.sub.A may be positive, producing the inhalation. From time t.sub.A to time t.sub.B, during which the patient **105** is holding his/her breath (and/or being made to hold his/her breath by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **835D** the expiratory flow **835D** evacuates and/or receives a relatively low continuous flow of expiratory gas from the patient **105**'s airways at relatively low (low absolute value) flow rate f.sub.D to evacuate CO.sub.2-rich and O.sub.2-deficient and potentially DCA **425**-including expiratory gas from the patient **105**'s airways. Net flow time t.sub.A to time t.sub.B may be

zero, producing the inspiratory hold. From time t.sub.B to time t.sub.D, during which the patient **105** is exhaling (and/or being made to exhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **835D** evacuates and/or receives a relatively high continuous flow of expiratory gas from the patient **105**'s airways at relatively high (high absolute value) flow rate f.sub.E producing exhalation and evacuating CO.sub.2-rich and O-deficient and maintain high clearance of dead space with suspended within DCA **425**-s. Net flow time t.sub.B to time t.sub.D may be negative, producing the exhalation. The high expiratory flow **835D** in FIG. 8D can allow the ventilator system to rapidly clear out significant amounts dead space **410** (along with any DCAs **425** included within the dead space **410**). Continuous inspiratory and expiratory flows can provide continuous clearance and removal of dead space **410** with any DCAs **425** suspended therein.

[0149] The period of time from time zero (0) to time t.sub.D represents a single inhale-exhale cycle. A second inhale-exhale cycle occurs from time t.sub.D to time t.sub.H.

[0150] In some examples, the inspiratory flow **830D** and/or the expiratory flow **835D** can be used with ventilator systems that are similar to the ventilator systems of FIGS. 4A-4C but that are modified (e.g., using one or more adapters and/or connector, for example connected **610** from FIG. 6.) to be more like the ventilator systems of FIGS. 5A-5C (e.g., by adding left inspiratory lumens **220** and right inspiratory lumens **225** and one or more expiratory lumens **510/520/525** separate from the inspiratory lumens **220-225** and/or separate from any expiratory lumens).

[0151] FIG. 8E is a graph diagram **800E** illustrating inspiratory flow **830E**, expiratory flow **835E**, and pressure changes **850** over time **815** in a ventilator system according to a fifth illustrative example. The pressure graph **810** of FIG. 8E matches the pressure graphs **810** of FIGS. 8A-8D.

[0152] From time zero (0) to time t.sub.A, during which the patient **105** is inhaling (and/or being made to inhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **835E** evacuates and/or receives a relatively low continuous flow of expiratory gas from the patient **105**'s airways at relatively low (low absolute value) flow rate f.sub.D to help evacuate CO.sub.2-rich and O.sub.2-deficient and potentially DCA **425**-including expiratory gas from the patient **105**'s airways. From time t.sub.A to time t.sub.B, during which the patient **105** is holding his/her breath (and/or being made to hold his/her breath by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **835E** evacuates and/or receives a relatively high continuous flow of expiratory gas from the patient **105**'s airways at relatively high (high absolute value) flow rate f.sub.E to help evacuate CO-rich and O.sub.2-deficient and potentially DCA **425**-including expiratory gas from the patient **105**'s airways. From time t.sub.B to time t.sub.D, during which the patient **105** is exhaling (and/or being made to exhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the expiratory flow **835C** evacuates and/or receives a very high continuous flow of expiratory gas from the patient **105**'s airways at very high (very high absolute value) flow rate f.sub.F to help evacuate CO.sub.2-rich and O.sub.2-deficient and potentially DCA **425**-including expiratory gas from the patient **105**'s airways. The high expiratory flow **835C** in FIG. 8E can allow the ventilator system to rapidly clear out significant amounts dead space **410** (along with any DCAs **425** included within the dead space **410**).

[0153] From time zero (0) to time t.sub.A, during which the patient **105** is inhaling (and/or being made to inhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830E** provides very high continuous flow of inspiratory gas to the patient **105**'s airways at very high flow rate f.sub.C to provide the patient **105** with inspiratory gas to inhale during the inhalation from time zero (0) to time t.sub.A and to offset the expiratory flow **835E**. Net flow from time zero (0) to time t.sub.A may be positive, producing the inhalation. From time t.sub.A to time t.sub.B, during which the patient **105** is holding his/her breath (and/or being made to hold his/her breath by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830E** provides a relatively high continuous flow of inspiratory gas to the patient **105**'s airways at relatively high flow rate f.sub.B to perform gas exchange

(exchanging contaminated expiratory air for clean inspiratory air) and continue to clear out dead space **410** (and any DCAs **425** suspended therein) from the patient **105**'s lungs **130/135** and airways generally. Net flow time $t_{sub.A}$ to time $t_{sub.B}$ may be zero, producing the inspiratory hold. From time $t_{sub.B}$ to time $t_{sub.D}$, during which the patient **105** is exhaling (and/or being made to exhale by the pressurizer(s) of the ventilator system) per the pressure changes **850**, the inspiratory flow **830E** provides relatively low continuous flow of inspiratory gas to the patient **105**'s airways at relatively low flow rate $f_{sub.A}$ to continue to perform gas exchange. Net flow time $t_{sub.B}$ to time $t_{sub.D}$ may be negative, producing the exhalation. Continuous inspiratory and expiratory flows can provide continuous clearance and removal of dead space **410** with any DCAs **425** suspended therein through the entire inhale-exhale cycle from time zero (0) to time $t_{sub.D}$.

[0154] The period of time from time zero (0) to time $t_{sub.D}$ represents a single inhale-exhale cycle. A second inhale-exhale cycle occurs from time $t_{sub.D}$ to time $t_{sub.H}$.

[0155] While the inspiratory flows **830A-830E** and the expiratory flows **835A-835E** of FIGS. 8A-8E are illustrated as step functions that instantaneously step between continuous flow rate values, it should be understood that changes in flow rate in the inspiratory flows **830A-830E** and the expiratory flows **835A-835E** may occur more gradually. Furthermore, it should be understood that flow rates illustrated as continuous in the inspiratory flows **830A-830E** and the expiratory flows **835A-835E** of FIGS. 8A-8E may include fluctuations and curves not illustrated in FIGS. 8A-8E.

[0156] In some examples, the inspiratory flow **830A** may be paired with any one of the expiratory flows **835A-835E**, or a combination thereof. In some examples, the inspiratory flow **830B** may be paired with any one of the expiratory flows **835A-835E**, or a combination thereof. In some examples, the inspiratory flow **830C** may be paired with any one of the expiratory flows **835A-835E**, or a combination thereof. In some examples, the inspiratory flow **830D** may be paired with any one of the expiratory flows **835A-835E**, or a combination thereof. In some examples, the inspiratory flow **830E** may be paired with any one of the expiratory flows **835A-835E**, or a combination thereof.

[0157] In some examples, the expiratory flow **835A** may be paired with any one of the inspiratory flows **830A-830E**, or a combination thereof. In some examples, the expiratory flow **835B** may be paired with any one of the inspiratory flows **830A-830E**, or a combination thereof. In some examples, the expiratory flow **835C** may be paired with any one of the inspiratory flows **830A-830E**, or a combination thereof. In some examples, the expiratory flow **835D** may be paired with any one of the inspiratory flows **830A-830E**, or a combination thereof. In some examples, the expiratory flow **835E** may be paired with any one of the inspiratory flows **830A-830E**, or a combination thereof.

[0158] FIG. 9A is a block diagram **900A** illustrating an architecture of an exemplary ventilator system that includes an inspiratory control system that provides inspiratory gas to a left lung **130** and a right lung **135** through a left inspiratory lumen **220** and a right inspiratory lumen **225**, and an expiratory control system that evacuates expiratory gas from the left lung **130** and the right lung **135** through one or more expiratory lumens **510/520/525**.

[0159] An inspiratory gas supply system of the ventilator system of FIG. 9A, illustrated in the lower-left corner of FIG. 9A, includes one or more gas sources **932**. The one or more gas sources **932** may correspond to the inspiratory gas sources **160** of FIG. 1. For example, the one or more inspiratory gas sources **160** can include an oxygen ($O_{sub.2}$) gas source, a nitrogen (N) gas source, a carbon dioxide ($CO_{sub.2}$) gas source, an argon (Ar) gas source, one or more gas sources for one or more drugs (in gaseous and/or aerosolized form), one or more gas sources for one or more other elemental gases, one or more gas sources for one or more other molecular gases, an pre-mixed atmospheric gas source, or a combination thereof.

[0160] The pre-mixed atmospheric gas source can include, for example, filtered atmospheric air. In some examples, a pre-mixed atmospheric gas can be sufficient to use as an inspiratory gas mixture, or as a portion of the inspiratory gas mixture (e.g., with some nitrogen (N) and/or oxygen (O.sub.2) added). In some examples, a pre-mixed atmospheric gas may include approximately 21% oxygen (O.sub.2), 78% nitrogen (N), and less than 1% of carbon dioxide (CO.sub.2). Filters by the inspiratory gas supply system may include n100, HEPA, or higher degree gas filtration filters, a UV light for decontamination, and other filters and cleaners.

[0161] Gas sources for individual elements or molecules, such as oxygen (O.sub.2), nitrogen (N), carbon dioxide (CO.sub.2), argon (Ar), or other elements or molecules discussed herein, can be stored in the gas source at a defined concentration. The concentration can be 100/0, or can be a value less than 100% (in which case the element or molecule may be mixed with atmospheric air, for example).

[0162] The inspiratory gas supply system may include a gas mixer **930** for mixing gases from the gas sources **932** to produce an inspiratory gas mixture, which may be known as an inspiratory gas, an inspiratory mixture, an inspiratory aerosol, or some combination thereof. The gas mixer **930** may include one or more gas equalizing systems, one or more proportional valves, one or more calibrated solenoid flow valves, or a combination thereof.

[0163] The gas mixer **930** may, for example, mix oxygen (O.sub.2), nitrogen (N), carbon dioxide (CO.sub.2), argon (Ar), one or more drugs (in gaseous and/or aerosolized form), one or more one or more other elemental gases, one or more other molecular gases, a pre-mixed atmospheric gas source, or a combination thereof. Even though it may seem counter-intuitive, it may be useful to include carbon dioxide (CO.sub.2) in the inspiratory gas mixture when carbon dioxide (CO.sub.2) is being evacuated at a high rate (due to continues or almost continues flow during the inhalation-exhalation cycle through both inspiratory and expiratory lumens) from the patient **105's** airways, as lack of carbon dioxide (CO.sub.2) can increase alkalinity, pushing pH too high, and can cause negative effects such as alkalosis.

[0164] In some examples, the gas mixer **930** can mix one or more liquids and/or one or more particulate solids into the one or more gases, for example in aerosolized and/or particularized and/or nebulized form. Sources for the liquids and/or solids can be stored along with the gas sources **932**. The one or more liquids can include water (H₂O), one or more drugs in liquid form, one or more other liquids, or a combination thereof. The one or more particulate solids can include one or more drugs in particulate solid form, one or more other particulate solids, or a combination thereof. The gas mixer **930** can include an aerosolizer and/or nebulizer and/or particulatizer to aerosolize and/or nebulize and/or particulate the one or more liquids and/or the one or more solids. The gas mixer **930** can mix the one or more aerosolized and/or particulate liquids and/or solids into the one or more inspiratory gases.

[0165] The gas mixer **930** can mix gases and/or liquids and/or particulate solids from the one or gas sources **932** at one or more predetermined ratios and/or proportions. The gas mixer **930** can mix inspiratory gases and/or liquids and/or particulate solids from the one or more gas sources **930** at one or more predetermined ratios and/or proportions to simulate the natural ratios and/or proportions of these gases in Earth's atmosphere or other ratios and/or proportions that may be selected or recommended by an operator, by an artificial intelligence algorithm (e.g., one or more trained machine learning models, one or more trained neural networks, or a combination thereof), or a combination thereof. The gas mixer **930** can mix inspiratory gases and/or liquids and/or particulate solids from the gas sources **932** at one or more predetermined ratios and/or proportions that increase or decrease a relative quantity of one or more specific gases (e.g., increased oxygen, decreased carbon monoxide) relative to the natural ratios and/or proportions of these gases in Earth's atmosphere or other ratios and/or proportions that may be selected or recommended by an operator, by an artificial intelligence algorithm (e.g., one or more trained machine learning models, one or more trained neural networks, or a combination thereof), or a combination thereof. The mixture mixed by the gas mixer **903** can be referred to as the inspiratory mixture, the inspiratory gas, the inspiratory gas mixture, the inspiratory fluid mixture, the inspiratory fluid, the inspiratory

substance, the inspiratory air, the inspiratory aerosol, or some combination thereof. The ratios at which the different gases are present in the inspiratory mixture may be set by a user **190** through an interface **175**.

[0166] In some examples, the gas sources **932** can include stable and known pressures of each of the gases provided to the gas mixer **930**. The gas mixer **930** can adjust flows of each gas by adjusting flow valves of for each of gases based on feedback loop based on sensor data from the capnometer **926** and/or other sensors (e.g., the inspiratory mixture sensors **910**, the capnometer **938**, the expiratory mixture sensors **940**, and/or the intratracheal sensors **934**).

[0167] The inspiratory gas supply system may include a gas property control **928**. The gas property control **928** can include a humidifier and/or a moisture exchanger and/or a moisture trap to control (e.g., increase or decrease) the humidity of the inspiratory gas before the inspiratory mixture is provided to the patient **105**'s airways. The gas property control **928** can include warmer and/or a heat exchanger to control (e.g., increase or decrease) the temperature of the inspiratory gas before the inspiratory mixture is provided to the patient **105**'s airways.

[0168] The inspiratory gas supply system may include a capnometer **926**, which may measure a concentration of carbon dioxide in the inspiratory mixture. Sensor data (e.g., readings/measurements) from the capnometer **926** may be provided to the gas mixer **930** as feedback. The gas mixer **930** may adjust the amount of carbon dioxide and/or other gases in the inspiratory mixture based on the sensor data from the capnometer **926**.

[0169] An inspiratory gas delivery system of the ventilator system of FIG. 9A, illustrated in the lower-middle of FIG. 9A, includes an inspiratory mixture pressurizer **914**. The inspiratory mixture pressurizer **914** can be electronically controlled, for example using the controller **170**. The inspiratory mixture pressurizer **914** provides pressure to the inspiratory mixture. The amount of pressure provided by the inspiratory mixture pressurizer **914** to the inspiratory mixture can be programmable, for example based on inputs from the user **190** to the interface **175**, based on automated pre-programmed reactions of the controller **170** to sensor data reaching/crossing thresholds or reaching/crossing into or out of a range, or a combination thereof. The amount of pressure provided by the inspiratory mixture pressurizer **914** to the inspiratory mixture can be based on sensor data from the capnometer **926**, the inspiratory mixture sensors **910**, the intratracheal sensors **934**, the capnometer **938**, and/or the expiratory mixture sensors **940**. The pressure programmed for the inspiratory mixture pressurizer **914** to apply may be defined in terms of pressure/time (as in the pressure graphs **810** of FIGS. 8A-8E) and/or flow/time (as in the flow graphs **805A-805E** of FIGS. 8A-8E). The inspiratory mixture pressurizer **914** can react to program, manual control by operator, alarms, thresholds, ranges, and safety settings including, but not limited to one or more maximum inspiratory mixture pressure thresholds, one or more minimum inspiratory mixture pressure thresholds, one or more safe inspiratory mixture pressure ranges, one or more unsafe inspiratory mixture pressure ranges, or a combination thereof. Multiple pre-set thresholds and ranges may exist because certain thresholds may differ based on whether a patient **105** has a healthy respiratory system or not, and what types of diseases or conditions a patient **105** may be suffering from. The thresholds may correspond to positive end expiratory pressure (PEEP). In some examples, a higher PEEP may be desirable. In some examples, a lower PEEP may be desirable.

[0170] The inspiratory gas delivery system may include one or more buffers **912**. The buffers **912** may store the inspiratory mixture while the inspiratory mixture pressurizer **914** pressurizes the inspiratory mixture. The buffers **912** may store additional inspiratory mixture in case the inspiratory gas delivery system does not receive the inspiratory mixture or receives less than needed of the inspiratory mixture for a short period from the inspiratory gas supply system.

[0171] The inspiratory gas delivery system may include one or more inspiratory mixture sensors **910**. The inspiratory mixture sensors **910** may include pressure sensors, pressure transducers, flow sensors, temperature sensors, humidity sensors, capnometers, oximeters, or combinations thereof.

[0172] The inspiratory gas delivery system may include a gas property control **908**. The gas property control **908** can include a humidifier and/or a moisture exchanger and/or a moisture trap to control (e.g., increase or decrease) the humidity of the inspiratory gas before the inspiratory mixture is provided to the patient **105**'s airways. The gas property control **908** can include warmer and/or a heat exchanger to control (e.g., increase or decrease) the temperature of the inspiratory gas before the inspiratory mixture is provided to the patient **105**'s airways.

[0173] The inspiratory gas delivery system may include a pressure release valve **906**. The pressure release valve **906** may release the inspiratory mixture into one or more inspiratory lumens. In the ventilator system of FIG. 9A, a single inspiratory tube or inspiratory lumen branches into a left inspiratory lumen **220**, which provides the inspiratory mixture to the left lung **130**, and a right inspiratory lumen **225**, which provides the inspiratory mixture to the right lung **135**. The inspiratory tube and/or inspiratory lumens are illustrated using thick dashed lines in FIGS. 9A-9B. The thick dashed lines include arrowheads pointing in the direction of inspiratory flow toward the lungs **130-135**.

[0174] The ventilator system of FIGS. 9A-9B includes one or more intratracheal sensors **934** that monitor pressure, flow, CO₂ level, oxygen level, humidity, temperature, and/or other properties at the carina of the trachea **115** and/or one or more other portions of the trachea **115**. The one or more intratracheal sensors **934** may be used to maintain desired positive end expiratory pressure (PEEP) where it is needed the most, still allowing the ventilator system of FIGS. 9A-9B to apply negative or reduced pressure. Another way to measure PEEP is to measure it by expiratory mixture sensors **940/950**. Negative pressures may need to be applied to expiratory lumen(s) (e.g., expiratory lumen **510** of FIG. 9A and/or expiratory lumens **520** and **525** of FIG. 9B) by the expiratory mixture pressurizers **994/954** to overcome the flow resistance in expiratory lumen(s) **520-525** as the expiratory mixture(s) is/are leaving the lungs **130-135** via airways and via expiratory lumen(s) **520-525**. Such negative, or lower than PEEP pressure, applied to expiratory lumens will allow for more efficient expiratory mixture(s) evacuation from lungs **130-135** via expiratory lumen(s) **520-525**. This sometimes may be necessary to maintain required shorter length of the expiratory phase, to maintain pre-determined and/or recommended and/or preset by operator higher respiratory rate. The intratracheal sensors **934** can include pressure sensors and/or one or more tips of one or more pressure transducers. The intratracheal sensors **934** can include pressure sensors as well as other sensors (e.g., flow, temperature, humidity, capnometer, oxygen sensor, and/or other gas properties).

[0175] The ventilator system of FIGS. 9A-9B includes one or more expiratory lumens that evacuate and/or receive expiratory gas(es) from the left lung **130** and/or the right lung **135**. The one or more expiratory lumens can include a single expiratory lumen **510** as in FIGS. 5A-5B. The a left expiratory lumen **520** and a right expiratory lumen **525** as in FIG. 5C. The one or more expiratory lumens are illustrated using thick solid lines in FIGS. 9A-9B. The thick solid lines include arrowheads pointing in the direction of expiratory flow away from the lungs **130-135**.

[0176] An expiratory gas receipt system of the ventilator system of FIG. 9A, illustrated in the upper-middle of FIG. 9A, can include a water trap **936** or moisture trap that traps water, moisture, and/or other liquids (e.g., mucous) that the expiratory gas receipt system can separate from the expiratory gas. The expiratory gas receipt system can include a capnometer **938**, which may measure carbon dioxide concentration in the expiratory gas(es). The sensor data from the capnometer **938** can be used for a feedback loop, for example to the expiratory mixture pressurizer **944**.

[0177] The expiratory gas receipt system can include one or more expiratory mixture sensors **940** that can measure properties of the expiratory gas(es). The one or more expiratory mixture sensors **940** may include pressure sensors, pressure transducers, flow sensors, temperature sensors, humidity sensors, capnometers, oximeters, or combinations thereof.

[0178] The expiratory gas receipt system can include an expiratory mixture pressurizer **944**. The expiratory mixture pressurizer **944** can provide pressure, for instance negative pressure (e.g., providing suction), to the one or more expiratory lumens **510/520/525**. Negative pressure can allow for receipt and/or evacuation of more expiratory gas(es) from the left lung **130** and/or the right lung **135**, and DCAs **425** included within. For example, negative pressure can allow for receipt and/or evacuation of more expiratory gas(es) from the dead spaces **410**, and DCAs **425** included within. Negative pressure can allow for flow of expiratory gas(es) from the lungs **130-135** to occur at a faster rate. The expiratory mixture pressurizer **944** can be electronically controlled, for example via a controller **170**. The expiratory mixture pressurizer **944** can include, for example, a rotary compressor, a turbine, a suction device, or a combination thereof. The expiratory gas receipt system can include a buffer **942**, which may for example be used by the expiratory mixture pressurizer **944** for providing negative pressure on the one or more expiratory lumens.

[0179] The amount of expiratory pressure provided by the expiratory mixture pressurizer **944** can be programmable, for example based on inputs from the user **190** to the interface **175**, based on automated pre-programmed reactions of the controller **170** to sensor data reaching/crossing thresholds or reaching/crossing into or out of a range, or a combination thereof. In some examples, the controller **170** that controls the expiratory mixture pressurizer **944** can adjust expiratory pressure based on sensor data from the capnometer **926**, the inspiratory mixture sensors **910**, the intratracheal sensors **934**, the capnometer **938**, the expiratory mixture sensors **940**, or a combination thereof. The amount of expiratory pressure provided by the expiratory mixture pressurizer **944** can be programmable pressure/time (as in the pressure graphs **810** of FIGS. 8A-8E) and/or flow/time (as in the flow graphs **805A-805E** of FIGS. 8A-8E). The expiratory mixture pressurizer **944** can react to alarms, thresholds, ranges, and safety settings including, but not limited to one or more maximum expiratory mixture pressure thresholds, one or more minimum expiratory mixture pressure thresholds, one or more safe expiratory mixture pressure ranges, one or more unsafe expiratory mixture pressure ranges, or a combination thereof. Multiple pre-set thresholds and ranges may exist because certain thresholds may differ based on whether a patient **105** has a healthy respiratory system or not, and what types of diseases or conditions a patient **105** may be suffering from. Expiratory pressure may be set to maintain a PEEP pressure above a threshold (e.g., a positive PEEP pressure) as measured at the intratracheal pressure sensors **934** or in any other way (for example as measured by expiratory mixture sensors **940/950**). An example minimum expiratory pressure may be 5 cmH.sub.2O, as less than that may be detrimental to pulmonary function or insufficient to maintain proper oxygenation in certain clinical scenarios. Specific expiratory pressures may be desirable to treat certain diseases. For example, to treat diseases such as ARDS, expiratory pressure of 12 cmH.sub.2O may be useful.

[0180] An expiratory gas removal system of the ventilator system of FIG. 9A, illustrated in the upper-left corner of FIG. 9A, can include a filtration system **956** that filters the expiratory gases, for example to remove DCAs **425** and/or harmful contaminants. The expiratory gas removal system can include an output **958**, which may include a gas sink/reservoir and/or an exhaust (e.g., to the atmosphere). In some examples, certain filtered and/or safe portions of the expiratory gases can be output using an exhaust, while dangerous portions of the expiratory gases (e.g., including DCAs **425** corresponding to highly infectious/contagious/deadly diseases) can be output to a sink or reservoir to prevent infecting or contaminating other individuals.

[0181] In some examples, the one or more expiratory lumens and/or one or more inspiratory lumens may include stiff walls to withstand positive pressure supplied by the inspiratory mixture pressurizer **914** and/or to withstand negative pressure supplied by the expiratory mixture pressurizer **944**. In some examples, the one or more expiratory lumens and/or one or more inspiratory lumens may, at least in some areas, be surrounded by a tube, such as the ETT **120**. The tube may include stiff walls to withstand positive pressure supplied by the inspiratory mixture pressurizer **914** and/or to withstand negative pressure supplied by the expiratory mixture pressurizer **944**.

[0182] In some examples, the inspiratory flow control system **150** of FIG. 1 may include at least a subset of the inspiratory gas supply system and/or at least a subset of the inspiratory gas delivery system of FIG. 9A. In some examples, the inspiratory gas source(s) **160** of FIG. 1 may include at least a subset of the inspiratory gas supply system and/or at least a subset of the inspiratory gas delivery system of FIG. 9A. In some examples, the expiratory flow control system **155** of FIG. 1 may include at least a subset of the expiratory gas receipt system and/or at least a subset of the expiratory gas removal system of FIG. 9A. In some examples, the expiratory output(s) **165** of FIG. 1 may include at least a subset of the expiratory gas receipt system and/or at least a subset of the expiratory gas removal system of FIG. 9A.

[0183] FIG. 9B is a block diagram **900B** illustrating an architecture of an exemplary ventilator system that includes a left inspiratory control system that provides inspiratory gas to a left lung **130** through a left inspiratory lumen **220**, a right inspiratory control system that provides inspiratory gas to a right lung **135** through a right inspiratory lumen **225**, a left expiratory control system that evacuates expiratory gas from a left lung **130** through a left expiratory lumen **520**, and a right expiratory control system that evacuates expiratory gas from a right lung **135** through a right expiratory lumen **525**. The ventilator system of FIG. 9B shares many components and traits with the ventilator system of FIG. 9A.

[0184] However, the ventilator system of FIG. 9B includes a left inspiratory lumen **220** with its own left inspiratory gas delivery system (with elements **916-924**) and a right inspiratory lumen **225** with its own right inspiratory gas delivery system (with elements **906-914**). The left inspiratory gas delivery system can include an inspiratory mixture pressurizer **924**, buffer **922**, inspiratory mixture sensors **920**, gas property control **918**, and pressure release valve **916**. These elements can function similarly to corresponding elements in the right inspiratory gas delivery system (and of FIG. 9A), such as the inspiratory mixture pressurizer **914**, the buffer **912**, the inspiratory mixture sensors **910**, gas property control **908**, and pressure release valve **906**.

[0185] While the ventilator system of FIG. 9B is illustrated with the left inspiratory gas delivery system and right inspiratory gas delivery system both supplied with inspiratory mixture by a shared inspiratory gas supply system (with elements **926-932**), this need not be the case. In some examples, the left inspiratory gas delivery system may include its own left inspiratory gas supply system, and the right inspiratory gas delivery system may include its own right inspiratory gas supply system.

[0186] The ventilator system of FIG. 9B also includes a left expiratory lumen **520** with its own left expiratory gas receipt system (with elements **936-944**) and a right inspiratory lumen **525** with its own inspiratory gas delivery system (with elements **946-954**). The right inspiratory gas delivery system can include a water trap **946**, capnometer **948**, expiratory mixture sensors **950**, buffer **952**, and/or expiratory mixture pressurizer **954**. These elements can function similarly to corresponding elements in the left expiratory gas delivery system (and of FIG. 9A), such as the water trap **936**, capnometer **938**, expiratory mixture sensors **940**, buffer **942**, and/or expiratory mixture pressurizer **944**.

[0187] While the ventilator system of FIG. 9B is illustrated with the left expiratory gas receipt system and right expiratory gas receipt system both outputting expiratory mixture to a shared expiratory gas removal system (with elements **956-958**), this need not be the case. In some examples, the left expiratory gas receipt system may include its own left expiratory gas removal system, and the right expiratory gas receipt system may include its own right expiratory gas removal system.

[0188] The expiratory Mixture collectively from all or some Expiratory Lumens, or separately from all or some Expiratory lumens, in all examples, can be analyzed, per clinical needs, for white cell count, epithelial cells count, red cell count, with culture, stains, microscopic examination, polymerase chain reaction, any other test, all quantitative and qualitative, in appropriate clinical scenarios, to diagnose, to follow up and compare disease activity and/or response to treatment in all, or some portions of the lungs.

[0189] The separate left inspiratory gas delivery system and right inspiratory gas delivery system separately supply pressurized inspiratory mixture to the left lung **130** and right lung **135**, respectively, through the left inspiratory lumen **220** and the right inspiratory lumen **225**, respectively. Because of the separate left inspiratory gas delivery system and right inspiratory gas delivery system, the left inspiratory mixture pressurizer **924** and the right inspiratory mixture pressurizer **914** can be set to provide different pressures for inspiratory gases to the left lung **130** and right lung **135**, respectively, through the left inspiratory lumen **220** and the right inspiratory lumen **225**, respectively. This may be helpful if one lung is in a different state than the other lung—for example, if one lung is more diseased or injured than the other lung, if one lung is smaller or larger than the other lung, if one lung is or more or less compliant or more or less capable than the other lung, or some combination thereof. Similarly, the left gas property control **918** and the right gas property control **908** can set higher or lower humidities, temperatures, or other gas properties for inspiratory mixture supplied to one lung than the other lung. In ventilator systems with a separate left inspiratory gas supply system and a separate right inspiratory gas supply system, the left lung **130** and the right lung **135** may even be provided with slightly different inspiratory mixtures (e.g., more oxygen to one lung than the other, more carbon dioxide to one lung than the other), based on different needs of the two lungs **130-135**.

[0190] For example, it may be beneficial to deliver more oxygen to a lung involved in pneumothorax, or to lung involved directly in the pneumonia process, while maintaining lower oxygen concentration in a healthier lung, to not stimulate creation of free radicals and high oxygen concentration injury and optimize shunting. In another clinical example of the unilateral left or lung pulmonary emboli or lung hemorrhage it may be useful, desired by the operator, or indicated, to provide oxygen to one lung but not the other lung.

[0191] Similarly, the separate left expiratory gas receipt system and right expiratory gas receipt system separately receive expiratory mixture from the left lung **130** and right lung **135**, respectively, through the left expiratory lumen **520** and the right expiratory lumen **525**, respectively. Because of the separate left expiratory gas receipt system and right expiratory gas receipt system, the left expiratory mixture pressurizer **944** and the right expiratory mixture pressurizer **954** can be set to provide different expiratory pressures to apply to the expiratory gases through the left expiratory lumen **520** and the right expiratory lumen **525**, respectively. This may be helpful if one lung is in a different state than the other lung—for example, if one lung is more diseased or injured than the other lung, if one lung is smaller or larger than the other lung, if one lung is or more or less compliant or more or less capable than the other lung, or some combination thereof. In ventilator systems with a separate left expiratory gas output system and a separate right expiratory gas output system, the expiratory gases received from the left lung **130** and the expiratory gases received from the right lung **135** may even be filtered differently and/or output to different types of outputs (e.g., exhaust, sink) based on the properties of the expiratory gases and/or lungs **130-135** (e.g., based on which of the lungs **130-135** is diseased and which of the lungs **130-135** is healthy). Different clinical testing can be applied to expiratory gas evacuated from different functional or structural portions of the lung, entire lung, or both lungs to allow for localization and identification of the problem, diseases, or clinical context. Different treatments can be applied to inspiratory gas inhaled into different portions of the lung to allow for directing the treatment to a given structural or functional portion of the lung, or the entire lung.

[0192] The amount of inspiratory pressure applied by the inspiratory mixture pressurizer **914** may be set based on sensor data from the capnometer **926**, the inspiratory mixture sensors **910**, the inspiratory mixture sensors **920**, the intratracheal sensors **934**, the capnometer **938**, the capnometer **948**, the expiratory mixture sensors **940**, the expiratory mixture sensors **950**, any other sensor or a combination thereof. The amount of inspiratory pressure applied by the inspiratory mixture pressurizer **924** may be set based on sensor data from the capnometer **926**, the inspiratory mixture sensors **910**, the inspiratory mixture sensors **920**, the intratracheal sensors **934**, the capnometer **938**, the capnometer **948**, the expiratory mixture sensors **940**, the expiratory mixture sensors **950**, any other sensor or a combination thereof. The amount of expiratory pressure applied by the expiratory mixture pressurizer **944** may be set

based on sensor data from the capnometer **926**, the inspiratory mixture sensors **910**, the inspiratory mixture sensors **920**, the intratracheal sensors **934**, the capnometer **938**, the capnometer **948**, the expiratory mixture sensors **940**, the expiratory mixture sensors **950**, any other sensors or a combination thereof. The amount of expiratory pressure applied by the expiratory mixture pressurizer **954** may be set based on sensor data from the capnometer **926**, the inspiratory mixture sensors **910**, the inspiratory mixture sensors **920**, the intratracheal sensors **934**, the capnometer **938**, the capnometer **948**, the expiratory mixture sensors **940**, the expiratory mixture sensors **950**, any other sensors, or a combination thereof.

[0193] In some examples, the inspiratory pressures applied by the inspiratory mixture pressurizers **914** and **924**, and the expiratory pressures applied by the expiratory mixture pressurizers **944** and **954**, can be set based on certain criteria. These criteria can include, for example, to match as closely as possible, breath by breath, the amount of the expiratory mixture exiting the right lung **135** through the right expiratory lumen **525** with the amount of the inspiratory mixture entering the right lung **135** through the right inspiratory lumen **225**. These may be determined by matching areas of inspiratory flow and expiratory flow curves (graphed as flow/time). These criteria can include, for example, to match as closely as possible, breath by breath, the amount of the expiratory mixture exiting the left lung **130** through the left expiratory lumen **520** with the amount of the inspiratory mixture entering the left lung **130** through the left inspiratory lumen **220**. These may be determined by matching areas of inspiratory flow and expiratory flow curves (graphed as flow/time). These criteria can include maintaining positive expiratory pressure at the position of intratracheal pressure sensors **934**. This would functionally separate the left lung **130** from the right lung **135**, by minimizing the left-to-right and right-to-left flow between the lungs.

[0194] In some examples, the ventilator system may output a warning (e.g., through interface **175**), or may automatically adjust inspiratory pressures and/or expiratory pressures, when certain thresholds are reached and/or crossed. One threshold may be if (Expiratory Mixture volume from right lung **135**/Inspiratory Mixture volume to right lung **135**) approaches, reaches, or crosses a certain threshold $T_{sub.1}$. Another threshold may be if (Expiratory Mixture volume from left lung **130**/Inspiratory Mixture volume to left lung **130**) approaches, reaches, or crosses the threshold $T_{sub.1}$. Another threshold may be if (Expiratory Mixture volume from right lung **135**/Inspiratory Mixture volume to right lung **135**) approaches, reaches, or crosses the threshold $1/T_{sub.1}$. Another threshold may be if (Expiratory Mixture volume from left lung **130**/Inspiratory Mixture volume to left lung **130**) approaches, reaches, or crosses the threshold $1/T_{sub.1}$. The value of $T_{sub.1}$ may be set automatically by the controller **170** and/or by the user **190** through the interface **175**. These thresholds, warnings and automatic adjustments, or any combination of thereof, may warn operator of undesired poor functional separation between the left vs. right lung, may warn operator about presence of significant leak of left-to-right or right-to-left of inspiratory gasses, and may alleviate this leak.

[0195] Another threshold may be if (Expiratory Mixture volume from right lung **135**—Inspiratory Mixture volume to right lung **135**) approaches, reaches, or crosses a certain threshold $T_{sub.2}$. Another threshold may be if (Expiratory Mixture volume from left lung **130**—Inspiratory Mixture volume to left lung **130**) approaches, reaches, or crosses the threshold $T_{sub.2}$. Another threshold may be if (Expiratory Mixture volume from right lung **135**—Inspiratory Mixture volume to right lung **135**) approaches, reaches, or crosses the threshold $1/T_{sub.2}$. Another threshold may be if (Expiratory Mixture volume from left lung **130**—Inspiratory Mixture volume to left lung **130**) approaches, reaches, or crosses the threshold $1/T_{sub.2}$. The value of $T_{sub.2}$ may be set automatically by the controller **170** and/or by the user **190** through the interface **175**. These thresholds, and based on them warnings and automatic adjustments, or any combination of thereof, may warn operator of undesired poor functional separation between the left vs. right lung, may warn operator about presence of significant leak of left-to-right or right-to-left of inspiratory gasses, and may alleviate this leak.

[0196] Another threshold may be if (Expiratory Mixture volume from right lung **135**) approaches, reaches, or crosses a certain threshold T.sub.3. Another threshold may be if (Expiratory Mixture volume from right lung **135**) approaches, reaches, or crosses the threshold T.sub.3. Another threshold may be if (Expiratory Mixture volume from right lung **135**) approaches, reaches, or crosses the threshold 1/T.sub.3. Another threshold may be if (Expiratory Mixture volume from left lung **130**) approaches, reaches, or crosses the threshold 1/T.sub.3. Another threshold may be if (Inspiratory Mixture volume to right lung **135**) approaches, reaches, or crosses the threshold T.sub.3. Another threshold may be if (Inspiratory Mixture volume to right lung **135**) approaches, reaches, or crosses the threshold T.sub.3. Another threshold may be if (Inspiratory Mixture volume to right lung **135**) approaches, reaches, or crosses the threshold 1/T.sub.3. Another threshold may be if (Inspiratory Mixture volume to left lung **130**) approaches, reaches, or crosses the threshold 1/T.sub.3. The value of T.sub.3 may be set automatically by the controller **170** and/or by the user **190** through the interface **175**. These thresholds, and based on them warnings and automatic adjustments, or any combination of thereof, may warn operator of undesired poor functional separation between the left vs. right lung, may warn operator about presence of significant leak of left-to-right or right-to-left of inspiratory gasses, and may alleviate this leak.

[0197] Detection that any of the thresholds above are approached, reached, or crossed may automatically cause, or may cause users **190** to perform, change to a different mode of ventilation, PEEP adjustments, use of different size(s) of endotracheal tube, use of different size(s) of inspiratory lumen(s), use of different size(s) of expiratory lumen(s), changes to the positioning of patient, or a combination thereof.

[0198] In an illustrative example, a patient **105**'s left lung **130** may be more diseased and have lower compliance than the patient **105**'s right lung **135**. If inspiratory pressures and/or expiratory pressures are set identically for the left lung **130** and right lung **135**, the controller **170** may detect that there is more Gas "Expired" by the "more compliant side" (in this case the right side) even though the same amount of Gas was "inspired" by both sides due to same applied pressure. The controller **170** can determine this mismatch as a sign of poor functional separation between the lungs and can first attempt to neutralize it by applying higher end expiratory pressure to the right expiratory lumen **525** and lower end expiratory pressure to the left expiratory lumen **520**. This should decrease or eliminate the mismatch and improve functional separation between the left and right lung. The controller **170** can monitor the pressure at intratracheal pressure sensors **934** to make sure this matches an expected value (for example preset PEEP pressure) or range (e.g., at a preset programmed by the user **190**). If the intratracheal pressure sensors **934** is lower than the expected value or range, the controller **170** can increase both pressures provided by right expiratory mixture pressurizer **954** for right lung **135** and left expiratory mixture pressurizer **944** for left lung **135**, maintaining the earlier established pressure difference between pressures provided by right expiratory mixture pressurizer **954** (end expiratory pressure for the right expiratory mixture pressurizer **954**) for right lung **135** and left expiratory mixture pressurizer **944** (end expiratory pressure for the right expiratory mixture pressurizer **944**) for left lung to functionally separate left and right lung.

[0199] If the pressure detected the intratracheal sensors **934** is above the expected pressure (for example preset PEEP), the controller **170** can decrease both (for example end expiratory pressures) provided by right expiratory mixture pressurizer **954** for right lung **135** and left expiratory mixture pressurizer **944** for left lung **135**, maintaining the earlier established pressure difference between pressures provided by right expiratory mixture pressurizer **954** for right lung **135** and left expiratory mixture pressurizer **944** for left lung to functionally separate left and right lung.

[0200] If the controller **170** cannot eliminate the mismatch as discussed above, and the criteria for an alarm or warning triggers, and the user **190** (e.g., a health care provider), may decide to change a position of the patient **105**, for example by putting the patient **105** on his/her right side, to decrease compliance of the right lung **135**.

[0201] In some examples, negative or lower than PEEP pressures may need to be applied to expiratory lumen(s) (e.g., expiratory lumen **510** of FIG. 9A, and/or expiratory lumens **520** and **525** of FIG. 9B) by the expiratory mixture pressurizer (**994** and/or **954**) to overcome the flow resistance in expiratory lumen(s) as the expiratory mixture(s) is/are leaving the lungs via airways and via expiratory lumen(s). Such negative or lower than PEEP pressure will allow for efficient expiratory mixture(s) evacuation from lungs **130-135** via the expiratory lumen(s). It may be useful to maintain required shorter length of the expiratory phase, as it may be useful to maintain higher respiratory rates that are pre-determined, recommended, and/or preset by an operator, and/or to prevent a phenomena referred to as “auto-PEEPing.”

[0202] Pressure data from pressure sensors and/or transducer(s) (e.g., of the inspiratory mixture sensors **910**, the inspiratory mixture sensors **920**, the intratracheal sensors **934**, the expiratory mixture sensors **940**, and/or the expiratory mixture sensors **950**) can be used to maintain a desired (e.g., selected by operator) level of PEEP. Similarly, pressure data can also be used to trigger alarms in case of high pressures (e.g., exceeding a threshold) or low pressures (e.g., less than a threshold). The readings from various sensors (e.g., capnometer **926**, the inspiratory mixture sensors **910**, the inspiratory mixture sensors **920**, the intratracheal sensors **934**, the capnometer **938**, the capnometer **948**, the expiratory mixture sensors **940**, the expiratory mixture sensors **950**, or a combination thereof), which may include pressure sensor(s), pressure transducer(s), temperature sensor(s), and/or capnometer(s), can be used to calculate the inspiratory mixture(s) flow rate(s) (which depend on pressures applied by inspiratory mixture pressurizer(s) **914/924**) and expiratory mixture(s) flow rate(s) (which depend on pressures applied by expiratory mixture Pressurizer(s) **944/954**) to maintain functional separation of the portions of the lungs.

[0203] Functional separation of the left lung **130** from the right lung **135** may be beneficial, in many clinical scenarios to prevent DCAs **425** from freely crossing between the left lung **130** from the right lung **135**. For example, if patient has COVID-19 caused pneumonia in the left lung **130**, it may be desired to functionally separate the left lung **130** from the right lung **135** to prevent DCAs **435** (e.g., COVID-19 virions) from moving from left lung **130** from the right lung **135**.

[0204] The ventilator system pictured on FIG. 9B allows one or more operators (e.g., users **190**) to functionally separate the left lung **130** from the right lung **135**, by assuring that all (most) of the inspiratory mixture entering the left lung **130** via left inspiratory lumen **220** exits from the left lung **130** by the left expiratory lumen **520**, and as little as possible of this inspiratory mixture exits through the right expiratory lumen **525** or enters right main bronchus **215** or right lung **135**. Likewise, the ventilator system can assure that all (most) of the inspiratory mixture entering the right lung **135** via right inspiratory lumen **225** exits from the right lung **135** by the right expiratory lumen **525**, and as little as possible of this inspiratory mixture exits through the left expiratory lumen **520** or enters the left main bronchus **210** or left lung **130**. In many clinical scenarios, the compliance of left lung **130** and right lung **135** differ. Thus, it can be useful to provide different pressures for the left inspiratory mixture pressurizer **924** and the right inspiratory mixture pressurizer **914**, it can be useful to provide different pressures for the left expiratory mixture pressurizer **944** and the right inspiratory mixture pressurizer **954**, to strengthen and maintain the functional separation between the left lung **130** and the right lung **135**.

[0205] In order to preserve functional separation between the left lung **130** and right lung **135**, if indicated, the controller **170** can perform a real-time analysis of sensor data from various sensors (e.g., capnometer **926**, the inspiratory mixture sensors **910**, the inspiratory mixture sensors **920**, the intratracheal sensors **934**, the capnometer **938**, the capnometer **948**, the expiratory mixture sensors **940**, the expiratory mixture sensors **950**, or a combination thereof). The controller **170** can test the compliance of the left lung **130** and right lung **135** by applying various inspiratory pressures, expiratory pressures, CO.sub.2 concentrations, temperatures, inspiratory mixture flow rates, and/or expiratory mixture flow rates.

[0206] In some examples, the controller **170** may detects that, even though same pressure is provided by the inspiratory pressurizers **914** and **924**, different expiratory pressures may be used or detected. In an

illustrative example, during each breath, 500 cc of inspiratory mixture is provided via right inspiratory lumen **225**, 430 cc is received via right expiratory lumen **525**, 530 cc of inspiratory mixture is provided via left inspiratory lumen **220**, and 600 cc is received via left expiratory lumen **520**. In this example, the controller **170** may determine that there is insufficient functional separation between the right lung **135** and the left lung **130**, and will attempt to correct this in at least one of several ways. The controller **170** can increase the negative pressure (e.g., increase absolute value of the negative pressure) applied to the right expiratory lumen **525** to increase expiratory flow rate through it the right expiratory lumen **525**, decrease the pressure applied to right inspiratory lumen **225** to increase inspiratory flow rate through the right inspiratory lumen **225**, or a combination thereof.

[0207] If the controller **170** can't find a solution to resolve inadequate functional separation of the left lung **130** and the right lung **135** (or portions thereof) based on pressure, or if capnometer sensor data is more reliable or readily available, then the controller **170** can base its actions on capnometer data from capnometers (e.g., capnometers **926**, **934**, **938**, and/or **948**). The controller **170** can, increase, for a brief period, the CO.sub.2 concentration of the inspiratory mixture to the right lung **135** and measure a time elapsed until a peak CO.sub.2 concentration is detected corresponding to the CO.sub.2 concentration increase. The intratracheal sensors **934** may include a capnometer, which may be useful for this purpose. If the time to detected CO.sub.2 partial pressure peak is long (e.g., longer than a threshold) and peak is low (e.g., lower than a threshold), the controller **170** may determine that there is little (e.g., less than a threshold) inspiratory mixture crossing from the right lung **135** to the left lung **130**. If the time to detected CO.sub.2 partial pressure peak is short (e.g., shorter than a threshold), and peak is high (e.g., higher than a threshold), the controller **170** may determine that there is a lot of (e.g., more than a threshold) inspiratory mixture crossing from the right lung **135** to the left lung **130**.

[0208] The controller **170** can then repeat by the attempt by increasing, for a brief period, the CO concentration of the inspiratory mixture to the left lung **130** and measure the time elapsed until peak CO.sub.2 is detected by the capnometers. If the time to detected CO.sub.2 partial pressure peak is long (e.g., longer than a threshold), and peak is low (e.g., lower than a threshold), the controller **170** may determine that there is little (e.g., less than a threshold) inspiratory mixture crossing from the left lung **130** to the right lung **135**. If the time to detected CO.sub.2 partial pressure peak is short (e.g., shorter than a threshold), and peak is high (e.g., higher than a threshold), the controller **170** may determine that there is a lot of (e.g., more than a threshold) inspiratory mixture crossing from the left lung **130** to the right lung **135**.

[0209] The controller **170** can further try to adjust the pressures of inspiratory pressurizers **914/924** and the expiratory pressurizers **944/954** to maintain minimal peak and longest possible time to peak.

[0210] Instead of increasing CO.sub.2 in the inspiratory mixture(s) and detecting the peak in CO.sub.2 at the capnometer(s) corresponding to the increase in CO.sub.2, the controller **170** may instead decrease CO.sub.2 in the inspiratory mixture(s) and detect a corresponding dip in the peak in CO.sub.2 at the capnometer(s).

[0211] Instead of increasing CO.sub.2 in the inspiratory mixture(s) and detecting the peak in CO.sub.2 at the capnometer(s) corresponding to the increase in CO.sub.2, the controller **170** may instead increase or decrease temperature of the inspiratory mixture(s) and detect a corresponding peak or dip in temperature at one or more thermometers, such as a thermometer of the intratracheal sensors **934**.

[0212] The intratracheal pressure sensor **934**, may be used to warn the operator of flow issues, within the inspiratory and expiratory lumen, for example due to mucus plugging. In such scenarios, the gradient of the pressure between the inspiratory or expiratory pressurizers vs. intratracheal sensors would be out of proportion higher than baseline gradient, recorded earlier during normal operation. This can be sensed by sensor and software and can trigger warning similarly to warning described earlier.

[0213] The intratracheal pressure sensor **934** can allow to accurate titration of PEEP exactly in position, where it really should be measured. This would provide most accurately PEEP, regardless of biases caused by example of flow and resistance via inspiratory or expiratory lumens.

[0214] In some examples, the inspiratory flow control system **150** of FIG. 1 may include at least a subset of the inspiratory gas supply system and/or at least a subset of the inspiratory gas delivery systems of FIG. 9A. In some examples, the inspiratory gas source(s) **160** of FIG. 1 may include at least a subset of the inspiratory gas supply system and/or at least a subset of the inspiratory gas delivery systems of FIG. 9A. In some examples, the expiratory flow control system **155** of FIG. 1 may include at least a subset of the expiratory gas receipt systems and/or at least a subset of the expiratory gas removal system of FIG. 9A. In some examples, the expiratory output(s) **165** of FIG. 1 may include at least a subset of the expiratory gas receipt systems and/or at least a subset of the expiratory gas removal system of FIG. 9A.

[0215] FIG. 10 is a flow diagram illustrating exemplary operations **1000** for airflow control. The operations **1000** may be performed by a ventilator system. The ventilator system that performs the operations **1000** may include the ventilator systems of FIG. 1, the ventilator system of FIG. 2, the ventilator system of FIG. 4A, the ventilator system of FIG. 4B, the ventilator system of FIG. 4C, the ventilator system of FIG. 5A, the ventilator system of FIG. 5B, the ventilator system of FIG. 5C, the ventilator system of FIG. 6, the ETT **120** of FIG. 7A, a ventilator system providing pressure changes **850**, a ventilator system providing inspiratory flow **830A**, a ventilator system providing inspiratory flow **830B**, a ventilator system providing inspiratory flow **830C**, a ventilator system providing inspiratory flow **830D**, a ventilator system providing inspiratory flow **830E**, a ventilator system providing expiratory flow **835A**, a ventilator system providing expiratory flow **835B**, a ventilator system providing expiratory flow **835C**, a ventilator system providing expiratory flow **835D**, a ventilator system providing expiratory flow **835E**, the ventilator system of FIG. 9A, the a ventilator system of FIG. 9B, one or more components of any of the previously-listed ventilator systems or elements, or a combination thereof.

[0216] At operation **1005**, the ventilator system receives a first inspiratory gaseous volume into a first inspiratory lumen. At operation **1010**, the ventilator system provides the first inspiratory gaseous volume to a first portion of an airway (e.g., of a patient **105**) using the first inspiratory lumen while the first inspiratory lumen is at least partially inserted into the airway.

[0217] At operation **1015**, the ventilator system receives a second inspiratory gaseous volume into a second inspiratory lumen. At operation **1020**, the ventilator system provides the second inspiratory gaseous volume to a second portion of the airway using the second inspiratory lumen while the second inspiratory lumen is at least partially inserted into the airway. In some examples, the ventilator system can provide the first inspiratory gaseous volume to the first portion of the airway using the first inspiratory lumen (as in operation **1010**) contemporaneously with providing the second inspiratory gaseous volume to the second portion of the airway using the second inspiratory lumen (as in operation **1020**).

[0218] According to a first illustrative embodiment of operations **1005-1020**, examples of the first inspiratory lumen of operations **1005** and **1010** may include the left inspiratory lumen **220** of FIGS. 5A-5C, 6, 7A, 9A, and 9B. According to the first illustrative embodiment of operations **1005-1020**, examples of the first portion of the airway of operations **1005** and **1010** include the left lung **130**, the left primary bronchus **210**, one or more left secondary bronchi **310**, one or more tertiary bronchi in the left lung **130**, one or more 4th order bronchi in the left lung **130**, one or more 5th order bronchi in the left lung **130**, one or more 6th order bronchi in the left lung **130**, one or more bronchioles **320** in the left lung **130**, one or more alveoli **325** in the left lung **130**, a left portion of the trachea **115**, or a combination thereof.

[0219] According to the first illustrative embodiment of operations **1005-1020**, examples of the second inspiratory lumen of operations **1015** and **1020** may include the right inspiratory lumen **225** of FIGS. 5A-5C, 6, 7A, 9A, and 9B. According to the first illustrative embodiment of operations **1005-1020**, examples of the second portion of the airway of operations **1015** and **1020** include the right lung **135**, the right

primary bronchus **215**, one or more right secondary bronchi **315**, one or more tertiary bronchi in the right lung **135**, one or more 4th order bronchi in the right lung **135**, one or more 5th order bronchi in the right lung **135**, one or more 6th order bronchi in the right lung **135**, one or more bronchioles **320** in the right lung **135**, one or more alveoli **325** in the right lung **135**, a right portion of the trachea **115**, or a combination thereof.

[0220] According to a second illustrative embodiment of operations **1005-1020**, examples of the first inspiratory lumen of operations **1005** and **1010** may include the right inspiratory lumen **225** of FIGS. 5A-5C, 6, 7A, 9A, and 9B. According to the second illustrative embodiment of operations **1005-1020**, examples of the second portion of the airway of operations **1005** and **1010** include the right lung **135**, the right primary bronchus **215**, one or more right secondary bronchi **315**, one or more tertiary bronchi in the right lung **135**, one or more 4th order bronchi in the right lung **135**, one or more 5th order bronchi in the right lung **135**, one or more 6th order bronchi in the right lung **135**, one or more bronchioles **320** in the right lung **135**, one or more alveoli **325** in the right lung **135**, a right portion of the trachea **115**, or a combination thereof.

[0221] According to the second illustrative embodiment of operations **1005-1020**, examples of the second inspiratory lumen of operations **1015** and **1020** may include the left inspiratory lumen **220** of FIGS. 5A-5C, 6, 7A, 9A, and 9B. According to the second illustrative embodiment of operations **1005-1020**, examples of the second portion of the airway of operations **1015** and **1020** include the left lung **130**, the left primary bronchus **210**, one or more left secondary bronchi **310**, one or more tertiary bronchi in the left lung **130**, one or more 4th order bronchi in the left lung **130**, one or more 5th order bronchi in the left lung **130**, one or more 6th order bronchi in the left lung **130**, one or more bronchioles **320** in the left lung **130**, one or more alveoli **325** in the left lung **130**, a left portion of the trachea **115**, or a combination thereof.

[0222] At operation **1025**, the ventilator system evacuates an expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens while the one or more expiratory lumens are at least partially inserted into the airway. In some examples, the ventilator system can evacuate the expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using the one or more expiratory lumens (as in operation **1025**) contemporaneously with providing the first inspiratory gaseous volume to the first portion of the airway using the first inspiratory lumen (as in operation **1010**) and/or with providing the second inspiratory gaseous volume to the second portion of the airway using the second inspiratory lumen (as in operation **1020**).

[0223] Examples of the one or more expiratory lumens of operation **1025** can include the expiratory lumen **510** of FIGS. 5A-5B, the expiratory lumen **510** of FIG. 6, the expiratory lumen **510** of FIG. 7A, the expiratory lumen **510** of FIG. 9A, the left expiratory lumen **520** of FIG. 5C, the left expiratory lumen **520** of FIG. 9A, the left expiratory lumen **520** of FIG. 9B, the right expiratory lumen **525** of FIG. 5C, the right expiratory lumen **525** of FIG. 9A, the right expiratory lumen **525** of FIG. 9B, or a combination thereof.

[0224] In some examples, the first portion of the airway includes a first lung, and the second portion of the airway includes a second lung distinct from the first lung. For instance, according to the first illustrative embodiment of operations **1005-1020**, the first lung may be the left lung **130**, and the second lung may be the right lung **135**. According to the second illustrative embodiment of operations **1005-1020**, the first lung may be the right lung **135**, and the second lung may be the left lung **130**.

[0225] In some examples, the first inspiratory lumen is configured to provide the first inspiratory gaseous volume to a first lobe of the first lung, and the one or more expiratory lumens are configured to evacuate the expiratory gaseous volume from a second lobe of the first lung. In some cases, the ventilator systems of FIGS. 5A-5D may be used to provide this difference in lobe for inspiratory air provision versus expiratory air evacuation. The first lobe is different than the second lobe. For instance, if the first lobe is a superior lobe, then the second lobe can be a middle lobe or an inferior lobe, and vice versa. If the first

lobe is a middle lobe, then the second lobe can be a superior lobe or an inferior lobe, or vice versa. If the first lobe is an inferior lobe, then the second lobe can be a superior lobe or a middle lobe, or vice versa.

[0226] In some examples, the second inspiratory lumen is configured to provide the second inspiratory gaseous volume to a first lobe of the second lung, and the one or more expiratory lumens are configured to evacuate the expiratory gaseous volume from a second lobe of the second lung. In some cases, the ventilator systems of FIGS. 5A-5D may be used to provide this difference in lobe for inspiratory air provision versus expiratory air evacuation. The first lobe is different than the second lobe. For instance, if the first lobe is a superior lobe, then the second lobe can be a middle lobe or an inferior lobe, and vice versa. If the first lobe is a middle lobe, then the second lobe can be a superior lobe or an inferior lobe, or vice versa. If the first lobe is an inferior lobe, then the second lobe can be a superior lobe or a middle lobe, or vice versa.

[0227] In some examples, the first portion of the airway includes a first lobe of the first lung, and the second portion of the airway includes a second lobe of the second lung. The first lobe can be different than the second lobe. For instance, if the first lobe is a superior lobe, then the second lobe can be a middle lobe or an inferior lobe, and vice versa. If the first lobe is a middle lobe, then the second lobe can be a superior lobe or an inferior lobe, or vice versa. If the first lobe is an inferior lobe, then the second lobe can be a superior lobe or a middle lobe, or vice versa. In some cases, the ventilator systems of FIGS. 5A-5D may be used to provide this difference in lobe based on lung.

[0228] In some examples, the first portion of the airway includes a first bronchus, and the second portion of the airway includes a second bronchus distinct from the first bronchus. The first and second bronchi may each (or both) be primary, secondary, tertiary, 4.sup.th order, 5.sup.th order, or 6.sup.th order bronchi. For instance, according to the first illustrative embodiment of operations **1005-1020**, the first bronchus may be a bronchus in the left lung **130**, and the second bronchus may be a bronchus in the right lung **135**. According to the second illustrative embodiment of operations **1005-1020**, the first bronchus may be a bronchus in the right lung **135**, and the second bronchus may be a bronchus in the left lung **130**.

[0229] In some examples, the first inspiratory lumen receives the first inspiratory gaseous volume from a first gas source, and second inspiratory lumen receives the second inspiratory gaseous volume from the first gas source. In some examples, the first inspiratory lumen receives the first inspiratory gaseous volume from a first gas source, and wherein second inspiratory lumen receives the second inspiratory gaseous volume from a second gas source. The first gas source can include, for example, the inspiratory gas source(s) **160** of FIG. 1, the inspiratory flow control system(s) **150** of FIG. 1, the inspiratory tube(s) **152** of FIG. 1, the inspiratory gas supply system of FIG. 9A, the inspiratory gas supply system(s) of FIG. 9B, the inspiratory gas delivery system of FIG. 9A, the inspiratory gas delivery system(s) of FIG. 9B, one or more components of one of the previously listed elements, or a combination thereof. The second gas source can include, for example, the inspiratory gas source(s) **160** of FIG. 1, the inspiratory flow control system(s) **150** of FIG. 1, the inspiratory tube(s) **152** of FIG. 1, the inspiratory gas supply system of FIG. 9A, the inspiratory gas supply system(s) of FIG. 9B, the inspiratory gas delivery system of FIG. 9A, the inspiratory gas delivery system(s) of FIG. 9B, one or more components of one of the previously listed elements, or a combination thereof.

[0230] In some examples, the first inspiratory gaseous volume and the second inspiratory gaseous volume both include an inspiratory mixture of a plurality of gases that are mixed according to one or more predetermined ratios. The plurality of gases may be stored and provided for mixing by the inspiratory gas source(s) **160** and/or the gas sources **932**. The plurality of gases may be mixed to form the inspiratory mixture by the inspiratory flow control system(s) **150** and/or the gas mixer **930**. In some examples, the inspiratory mixture may include at least one of oxygen (O.sub.2), carbon dioxide (CO.sub.2), nitrogen (N), argon (Ar), one or more drugs (in gaseous and/or aerosolized form), one or more one or more other elemental gases, one or more other molecular gases, a pre-mixed atmospheric gas source, or a combination thereof

[0231] In some examples, the ventilator system can include an endotracheal tube **120**. The endotracheal tube can include at least the first inspiratory lumen, the second inspiratory lumen, and the expiratory lumen. Examples of arrangements of the first inspiratory lumen, the second inspiratory lumen, and the expiratory lumen in the ETT **120** are illustrated in FIGS. 5A, 5B, 5C, 6, 7A, and 7B.

[0232] In some examples, the first inspiratory lumen passes through the endotracheal tube and extends beyond a tip of the endotracheal tube toward the first portion of the airway, wherein the second inspiratory lumen passes through the endotracheal tube and extends beyond the tip of the endotracheal tube toward the second portion of the airway.

[0233] In some examples, the tip **125** of the endotracheal tube **120** includes the tip of the expiratory lumen of operation **1025**. For example, the expiratory lumen **510** of FIGS. 5A, 5B, and/or **6** may be examples of the expiratory lumen of operation **1025** where the tip of the expiratory lumen is the tip **125** of the endotracheal tube **120**.

[0234] In some examples, the ventilator system includes one or more inspiratory flow control mechanisms that control flow of the first inspiratory gaseous volume to the first portion of the airway through the first inspiratory lumen and that control flow of second inspiratory gaseous volume to the second portion of the airway through the second inspiratory lumen. Examples of the one or more inspiratory flow control mechanisms can include, for instance, the inspiratory gas source(s) **160** of FIG. 1, the inspiratory flow control system(s) **150** of FIG. 1, the inspiratory tube(s) **152** of FIG. 1, the inspiratory gas supply system of FIG. 9A, the inspiratory gas supply system(s) of FIG. 9B, the inspiratory gas delivery system of FIG. 9A, the inspiratory gas delivery system(s) of FIG. 9B, the pressurizer(s) **145**, the controllers **170**, one or more components of one of the previously listed elements, or a combination thereof.

[0235] In some examples, the one or more expiratory lumens include a first expiratory lumen configured to evacuate a first expiratory gaseous volume from the first portion of the airway and a second expiratory lumen configured to evacuate a second expiratory gaseous volume from the second portion of the airway. In some examples, the first expiratory lumen passes through the endotracheal tube and extends beyond a tip of the endotracheal tube toward the first portion of the airway. In some examples, the second expiratory lumen passes through the endotracheal tube and extends beyond the tip of the endotracheal tube toward the second portion of the airway. Examples of the first expiratory lumen include the left expiratory lumen **520** and the right expiratory lumen **525**. Examples of the second expiratory lumen include the left expiratory lumen **520** and the right expiratory lumen **525**.

[0236] In some examples, a first expiratory mixture pressurizer provides suction to evacuate the first expiratory gaseous volume from the first portion of the airway through the first expiratory lumen. In some examples, a second expiratory mixture pressurizer that provides suction to evacuate the second expiratory gaseous volume from the second portion of the airway through the second expiratory lumen. Examples of the first expiratory mixture pressurizer include the expiratory mixture pressurizer **944** and the expiratory mixture pressurizer **954**. Examples of the second expiratory mixture pressurizer include the expiratory mixture pressurizer **944** and the expiratory mixture pressurizer **954**.

[0237] In some examples, the one or more expiratory lumens of the ventilator system also include a third expiratory lumen configured to evacuate a third expiratory gaseous volume from a third portion of the airway. In some examples, the third expiratory lumen may branch off of the first expiratory lumen or the second expiratory lumen. In some examples, the third portion of the airway may include, for example, one or more bronchi that the third expiratory lumen evacuates more expiratory gas from than the first expiratory lumen and/or the second expiratory lumen do.

[0238] In some examples, the ventilator system includes one or more expiratory flow control mechanisms that control flow of the expiratory gaseous volume from the first portion of the airway and from the second portion of the airway to an expiratory air output through the one or more expiratory lumens. Examples of the one or more expiratory flow control mechanisms can include, for instance, the expiratory gas output(s)

165 of FIG. 1, the expiratory flow control system(s) **155** of FIG. 1, the expiratory tube(s) **157** of FIG. 1, the expiratory gas receipt system of FIG. 9A, the expiratory gas receipt system(s) of FIG. 9B, the expiratory gas removal system of FIG. 9A, the expiratory gas removal system(s) of FIG. 9B, the pressurizer(s) **145**, the controllers **170**, one or more components of one of the previously listed elements, or a combination thereof.

[0239] In some examples, the ventilator system includes one or more inspiratory flow control mechanisms that provide the first inspiratory gaseous volume to the first inspiratory lumen and that provide the second inspiratory gaseous volume to the second inspiratory lumen. Examples of the one or more inspiratory flow control mechanisms can include, for instance, the inspiratory flow control system(s) **150**, the inspiratory gas source(s) **160**, the inspiratory gas provision system **490**, the gas sources **932**, the gas mixer(s) **930**, the gas property control(s) **928**, the capnometer(s) **926**, the inspiratory mixture pressurizer **914**, the buffer **912**, the inspiratory mixture sensors **910**, the gas property control **908**, the pressure release valve **906**, the inspiratory mixture pressurizer **924**, the buffer **922**, the inspiratory mixture sensors **920**, the gas property control **918**, the pressure release valve **916**, or a combination thereof.

[0240] In some examples, the ventilator system includes a controller. The controller can include, for example, a memory storing instructions, and a processor that executes the instructions. Examples of the controller include the controller **170** and/or the controller **480**. Execution of the instructions can cause the processor to maintain net inspiratory flow at a first level during a first portion of each of a plurality of respiratory cycles. Net inspiratory flow corresponds to provision of both the first inspiratory gaseous volume and the second inspiratory gaseous volume.

[0241] Examples of net inspiratory flow include inspiratory flows **830A-830E**. Execution of the instructions can cause the processor to maintain net expiratory flow at a second level during the first portion of each of the plurality of respiratory cycles, wherein net expiratory flow corresponds to provision of pressurized suction to control flow of the expiratory gaseous volume. Examples of net expiratory flow include expiratory flows **835A-835E**.

[0242] In some examples, the first portion of each of the plurality of respiratory cycles is an inspiration (e.g., time zero (0) to time $t_{sub.A}$ or time $t_{sub.D}$ time $t_{sub.E}$), and an absolute value of the net inspiratory flow is greater than an absolute value of the net expiratory flow. In some examples, the first portion of each of the plurality of respiratory cycles is an expiration (e.g., time $t_{sub.B}$ to time $t_{sub.D}$ or time $t_{sub.F}$ to time $t_{sub.H}$), and an absolute value of the net inspiratory flow is less than an absolute value of the net expiratory flow. In some examples, the first portion of each of the plurality of respiratory cycles is an hold (e.g., inspiratory hold, expiratory hold, or pause) (e.g., time $t_{sub.A}$ to time $t_{sub.B}$ or time $t_{sub.E}$ to time $t_{sub.F}$), and wherein an absolute value of the net inspiratory flow is equal to an absolute value of the net expiratory flow.

[0243] In some examples, the ventilator system includes an intratracheal sensor that measures an intratracheal pressure in a trachea of the patient. An example of the intratracheal sensor includes the intratracheal sensors **934**. In some examples, the ventilator system includes one or more pressurizers. The one or more pressurizers are configured to provide airflow pressure based on the intratracheal pressure measured by the intratracheal sensor. The airflow pressure includes at least one of a first inspiratory pressure to provide the first inspiratory gaseous volume to the first portion of the airway via the first inspiratory lumen, a second inspiratory pressure to provide the second inspiratory gaseous volume to the second portion of the airway via the second inspiratory lumen, an expiratory pressure to evacuate the expiratory gaseous volume from at least one of the first portion of the airway and the second portion of the airway via the one or more expiratory lumens, or a combination thereof. The one or more pressurizers may include, for example, the pressurizers **145**, the inspiratory mixture pressurizer **914**, the inspiratory mixture pressurizer **924**, the expiratory mixture pressurizer **944**, the expiratory mixture pressurizer **954**, or a combination thereof.

[0244] In some examples, the ventilator system includes one or more markers along at least one of the first inspiratory lumen, the second inspiratory lumen, the one or more expiratory lumens, or a combination thereof. The one or more markers can be radiopaque, radioactive, emissive of a magnetic field, emissive of one or more electromagnetic signals, or some combination thereof. The one or more markers can thus be used to locate the first inspiratory lumen, the second inspiratory lumen, and/or the one or more expiratory lumens within the patient **105**'s body, for example via a scan and/or via triangulation, to determine whether the lumens are positioned correctly in the patient **105**'s body (e.g., in the first portion of the airway, in the second portion of the airway, etc.).

[0245] In some examples, the ventilator system includes a third inspiratory lumen that is configured to receive a third inspiratory gaseous volume and to provide the third inspiratory gaseous volume to a third portion of the airway while the third inspiratory lumen is at least partially inserted into the airway. In some examples, the third inspiratory lumen may branch off of the first inspiratory lumen or the second inspiratory lumen. In some examples, the third portion of the airway may include, for example, one or more bronchi that the third inspiratory lumen provides more inspiratory gas to than the first inspiratory lumen and/or the second inspiratory lumen do.

[0246] In some examples, the ventilator system includes a microfilter adapter that includes a microfilter medium and one or more one-way airflow valves. The microfilter adapter passes airflow through the one or more one-way airflow valves and filters the airflow through the microfilter medium. The airflow includes at least one of the first inspiratory gaseous volume, the second inspiratory gaseous volume, and the expiratory gaseous volume. Examples of the microfilter adapter include the microfilter adapter **460**. Examples of the microfilter medium include the microfilter medium **465**. The microfilter adapter can be positioned in the ventilator system similarly to the adapter **450** and/or the adapter **455**. In some examples, the ventilator system includes another type of adapter in addition to or instead of the microfilter adapter, such as the connector **610**, which may provide the first inspiratory lumen and the second inspiratory lumen. In some examples, the ventilator system includes another type of adapter in addition to or instead of the microfilter adapter, such as the airflow rerouting adapter **470**.

[0247] FIG. 11 illustrates an exemplary computing system **1100** that may be used to implement some aspects of the technology. For example, any of the computing devices, computing systems, network devices, network systems, servers, and/or arrangements of circuitry described herein may include at least one computing system **1100**, or may include at least one component of the computer system **1100** identified in FIG. 11. The computing system **1100** of FIG. 11 includes one or more processors **1110** and memory units **1120**. Each of the processor(s) **1110** may refer to one or more processors, controllers, microcontrollers, central processing units (CPUs), graphics processing units (GPUs), arithmetic logic units (ALUs), accelerated processing units (APUs), digital signal processors (DSPs), application specific integrated circuits (ASICs), field-programmable gate arrays (FPGAs), or combinations thereof. Each of the processor(s) **1110** may include one or more cores, either integrated onto a single chip or spread across multiple chips connected or coupled together. Memory **1120** stores, in part, instructions and data for execution by processor **1110**. Memory **1120** can store the executable code when in operation. The system **1100** of FIG. 11 further includes a mass storage device **1130**, portable storage medium drive(s) **1140**, output devices **1150**, user input devices **1160**, a graphics display **1170**, and peripheral devices **1180**.

[0248] The components shown in FIG. 11 are depicted as being connected via a single bus **1190**. However, the components may be connected through one or more data transport means. For example, processor unit **1110** and memory **1120** may be connected via a local microprocessor bus, and the mass storage device **1130**, peripheral device(s) **1180**, portable storage device **1140**, and display system **1170** may be connected via one or more input/output (I/O) buses.

[0249] Mass storage device **1130**, which may be implemented with a magnetic disk drive or an optical disk drive, is a non-volatile storage device for storing data and instructions for use by processor unit **1110**.

Mass storage device **1130** can store the system software for implementing some aspects of the subject technology for purposes of loading that software into memory **1120**.

[0250] Portable storage device **1140** operates in conjunction with a portable non-volatile storage medium, such as a floppy disk, compact disk or Digital video disc, to input and output data and code to and from the computer system **1100** of FIG. 11. The system software for implementing aspects of the subject technology may be stored on such a portable medium and input to the computer system **1100** via the portable storage device **1140**.

[0251] The memory **1120**, mass storage device **1130**, or portable storage **1140** may in some cases store sensitive information, such as transaction information, health information, or cryptographic keys, and may in some cases encrypt or decrypt such information with the aid of the processor **1110**. The memory **1120**, mass storage device **1130**, or portable storage **1140** may in some cases store, at least in part, instructions, executable code, or other data for execution or processing by the processor **1110**.

[0252] Output devices **1150** may include, for example, communication circuitry for outputting data through wired or wireless means, display circuitry for displaying data via a display screen, audio circuitry for outputting audio via headphones or a speaker, printer circuitry for printing data via a printer, or some combination thereof. The display screen may be any type of display discussed with respect to the display system **1170**. The printer may be inkjet, laserjet, thermal, or some combination thereof. In some cases, the output device circuitry **1150** may allow for transmission of data over an audio jack/plug, a microphone jack/plug, a universal serial bus (USB) port/plug, an Apple® Lightning® port/plug, an Ethernet port/plug, a fiber optic port/plug, a proprietary wired port/plug, a BLUETOOTH® wireless signal transfer, a BLUETOOTH® low energy (BLE) wireless signal transfer, an IBEACON® wireless signal transfer, a radio-frequency identification (RFID) wireless signal transfer, near-field communications (NFC) wireless signal transfer, dedicated short range communication (DSRC) wireless signal transfer, 802.11 Wi-Fi wireless signal transfer, wireless local area network (WLAN) signal transfer, Visible Light Communication (VLC), Worldwide Interoperability for Microwave Access (WiMAX), Infrared (IR) communication wireless signal transfer, Public Switched Telephone Network (PSTN) signal transfer, Integrated Services Digital Network (ISDN) signal transfer, 3G/4G/5G/LTE cellular data network wireless signal transfer, ad-hoc network signal transfer, radio wave signal transfer, microwave signal transfer, infrared signal transfer, visible light signal transfer, ultraviolet light signal transfer, wireless signal transfer along the electromagnetic spectrum, or some combination thereof. Output devices **1150** may include any ports, plugs, antennae, wired or wireless transmitters, wired or wireless transceivers, or any other components necessary for or usable to implement the communication types listed above, such as cellular Subscriber Identity Module (SIM) cards.

[0253] Input devices **1160** may include circuitry providing a portion of a user interface. Input devices **1160** may include an alpha-numeric keypad, such as a keyboard, for inputting alpha-numeric and other information, or a pointing device, such as a mouse, a trackball, stylus, or cursor direction keys. Input devices **1160** may include touch-sensitive surfaces as well, either integrated with a display as in a touchscreen, or separate from a display as in a trackpad. Touch-sensitive surfaces may in some cases detect localized variable pressure or force detection. In some cases, the input device circuitry may allow for receipt of data over an audio jack, a microphone jack, a universal serial bus (USB) port/plug, an Apple® Lightning® port/plug, an Ethernet port/plug, a fiber optic port/plug, a proprietary wired port/plug, a wired local area network (LAN) port/plug, a BLUETOOTH® wireless signal transfer, a BLUETOOTH® low energy (BLE) wireless signal transfer, an IBEACON® wireless signal transfer, a radio-frequency identification (RFID) wireless signal transfer, near-field communications (NFC) wireless signal transfer, dedicated short range communication (DSRC) wireless signal transfer, 802.11 Wi-Fi wireless signal transfer, wireless local area network (WLAN) signal transfer, Visible Light Communication (VLC), Worldwide Interoperability for Microwave Access (WiMAX), Infrared (IR) communication wireless signal transfer, Public Switched Telephone Network (PSTN) signal transfer, Integrated Services Digital Network (ISDN) signal transfer, 3G/4G/5G/LTE cellular data network wireless signal transfer, personal area network (PAN) signal transfer, wide area network (WAN) signal transfer, ad-hoc network signal transfer, radio wave

signal transfer, microwave signal transfer, infrared signal transfer, visible light signal transfer, ultraviolet light signal transfer, wireless signal transfer along the electromagnetic spectrum, or some combination thereof. Input devices **1160** may include any ports, plugs, antennae, wired or wireless receivers, wired or wireless transceivers, or any other components necessary for or usable to implement the communication types listed above, such as cellular SIM cards.

[0254] Input devices **1160** may include receivers or transceivers used for positioning of the computing system **1100** as well. These may include any of the wired or wireless signal receivers or transceivers. For example, a location of the computing system **1100** can be determined based on signal strength of signals as received at the computing system **1100** from three cellular network towers, a process known as cellular triangulation. Fewer than three cellular network towers can also be used—even one can be used—though the location determined from such data will be less precise (e.g., somewhere within a particular circle for one tower, somewhere along a line or within a relatively small area for two towers) than via triangulation. More than three cellular network towers can also be used, further enhancing the location's accuracy. Similar positioning operations can be performed using proximity beacons, which might use short-range wireless signals such as BLUETOOTH® wireless signals, BLUETOOTH® low energy (BLE) wireless signals, IBEACON® wireless signals, personal area network (PAN) signals, microwave signals, radio wave signals, or other signals discussed above. Similar positioning operations can be performed using wired local area networks (LAN) or wireless local area networks (WLAN) where locations are known of one or more network devices in communication with the computing system **1100** such as a router, modem, switch, hub, bridge, gateway, or repeater. These may also include Global Navigation Satellite System (GNSS) receivers or transceivers that are used to determine a location of the computing system **1100** based on receipt of one or more signals from one or more satellites associated with one or more GNSS systems. GNSS systems include, but are not limited to, the US-based Global Positioning System (GPS), the Russia-based Global Navigation Satellite System (GLONASS), the China-based BeiDou Navigation Satellite System (BDS), and the Europe-based Galileo GNSS. Input devices **1160** may include receivers or transceivers corresponding to one or more of these GNSS systems.

[0255] Display system **1170** may include a liquid crystal display (LCD), a plasma display, an organic light-emitting diode (OLED) display, a low-temperature poly-silicon (LTPO) display, an electronic ink or “e-paper” display, a projector-based display, a holographic display, or another suitable display device. Display system **1170** receives textual and graphical information, and processes the information for output to the display device. The display system **1170** may include multiple-touch touchscreen input capabilities, such as capacitive touch detection, resistive touch detection, surface acoustic wave touch detection, or infrared touch detection. Such touchscreen input capabilities may or may not allow for variable pressure or force detection.

[0256] Peripherals **1180** may include any type of computer support device to add additional functionality to the computer system. For example, peripheral device(s) **1180** may include one or more additional output devices of any of the types discussed with respect to output device **1150**, one or more additional input devices of any of the types discussed with respect to input device **1160**, one or more additional display systems of any of the types discussed with respect to display system **1170**, one or more memories or mass storage devices or portable storage devices of any of the types discussed with respect to memory **1120** or mass storage **1130** or portable storage **1140**, a modem, a router, an antenna, a wired or wireless transceiver, a printer, a bar code scanner, a quick-response (“QR”) code scanner, a magnetic stripe card reader, a integrated circuit chip (ICC) card reader such as a smartcard reader or a EUROPAY®-MASTERCARD®-VISA® (EMV) chip card reader, a near field communication (NFC) reader, a document/image scanner, a visible light camera, a thermal/infrared camera, an ultraviolet-sensitive camera, a night vision camera, a light sensor, a phototransistor, a photoresistor, a thermometer, a thermistor, a battery, a power source, a proximity sensor, a laser rangefinder, a sonar transceiver, a radar transceiver, a lidar transceiver, a network device, a motor, an actuator, a pump, a conveyer belt, a robotic arm, a rotor, a drill, a chemical assay device, or some combination thereof.

[0257] The components contained in the computer system **1100** of FIG. 11 can include those typically found in computer systems that may be suitable for use with some aspects of the subject technology and represent a broad category of such computer components that are well known in the art. That said, the computer system **1100** of FIG. 11 can be customized and specialized for the purposes discussed herein and to carry out the various operations discussed herein, with specialized hardware components, specialized arrangements of hardware components, and/or specialized software. Thus, the computer system **1100** of FIG. 11 can be a personal computer, a hand held computing device, a telephone (“smartphone” or otherwise), a mobile computing device, a workstation, a server (on a server rack or otherwise), a minicomputer, a mainframe computer, a tablet computing device, a wearable device (such as a watch, a ring, a pair of glasses, or another type of jewelry or clothing or accessory), a video game console (portable or otherwise), an e-book reader, a media player device (portable or otherwise), a vehicle-based computer, another type of computing device, or some combination thereof. The computer system **1100** may in some cases be a virtual computer system executed by another computer system. The computer can also include different bus configurations, networked platforms, multi-processor platforms, etc. Various operating systems can be used including Unix®, Linux®, FreeBSD®, FreeNAS®, pfSense®, Windows®, Apple® Macintosh OS® (“MacOS®”), Palm OS®, Google® Android®, Google® Chrome OS®, Chromium® OS®, OPENSTEP®, XNU®, Darwin®, Apple® iOS®, Apple® tvOS®, Apple® watchOS®, Apple® audioOS®, Amazon® Fire OS®, Amazon® Kindle OS®, variants of any of these, other suitable operating systems, or combinations thereof. The computer system **1100** may also use a Basic Input/Output System (BIOS) or Unified Extensible Firmware Interface (UEFI) as a layer upon which the operating system(s) are run.

[0258] In some cases, the computer system **1100** may be part of a multi-computer system that uses multiple computer systems **1100**, each for one or more specific tasks or purposes. For example, the multi-computer system may include multiple computer systems **1100** communicatively coupled together via at least one of a personal area network (PAN), a local area network (LAN), a wireless local area network (WLAN), a municipal area network (MAN), a wide area network (WAN), or some combination thereof. The multi-computer system may further include multiple computer systems **1100** from different networks communicatively coupled together via the internet (also known as a “distributed” system).

[0259] Some aspects of the subject technology may be implemented in an application that may be operable using a variety of devices. Non-transitory computer-readable storage media refer to any medium or media that participate in providing instructions to a central processing unit (CPU) for execution and that may be used in the memory **1120**, the mass storage **1130**, the portable storage **1140**, or some combination thereof. Such media can take many forms, including, but not limited to, non-volatile and volatile media such as optical or magnetic disks and dynamic memory, respectively. Some forms of non-transitory computer-readable media include, for example, a floppy disk, a flexible disk, a hard disk, magnetic tape, a magnetic strip/stripe, any other magnetic storage medium, flash memory, memristor memory, any other solid-state memory, a compact disc read only memory (CD-ROM) optical disc, a rewritable compact disc (CD) optical disc, digital video disk (DVD) optical disc, a blu-ray disc (BDD) optical disc, a holographic optical disc, another optical medium, a secure digital (SD) card, a micro secure digital (microSD) card, a Memory Stick® card, a smartcard chip, a EMV chip, a subscriber identity module (SIM) card, a mini/micro/nano/pico SIM card, another integrated circuit (IC) chip/card, random access memory (RAM), static RAM (SRAM), dynamic RAM (DRAM), read-only memory (ROM), programmable read-only memory (PROM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), flash EPROM (FLASHEPROM), cache memory (L1/L2/L3/L4/L5/L15), resistive random-access memory (RRAM/ReRAM), phase change memory (PCM), spin transfer torque RAM (STT-RAM), another memory chip or cartridge, or a combination thereof.

[0260] Various forms of transmission media may be involved in carrying one or more sequences of one or more instructions to a processor **1110** for execution. A bus **1190** carries the data to system RAM or another memory **1120**, from which a processor **1110** retrieves and executes the instructions. The

instructions received by system RAM or another memory **1120** can optionally be stored on a fixed disk (mass storage device **1130**/portable storage **1140**) either before or after execution by processor **1110**. Various forms of storage may likewise be implemented as well as the necessary network interfaces and network topologies to implement the same.

[0261] While various flow diagrams provided and described above may show a particular order of operations performed by some embodiments of the subject technology, it should be understood that such order is exemplary. Alternative embodiments may perform the operations in a different order, combine certain operations, overlap certain operations, or some combination thereof. It should be understood that unless disclosed otherwise, any process illustrated in any flow diagram herein or otherwise illustrated or described herein may be performed by a machine, mechanism, and/or computing system **1100** discussed herein, and may be performed automatically (e.g., in response to one or more triggers/conditions described herein), autonomously, semi-autonomously (e.g., based on received instructions), or a combination thereof. Furthermore, any action described herein as occurring in response to one or more particular triggers/conditions should be understood to optionally occur automatically response to the one or more particular triggers/conditions.

[0262] The foregoing detailed description of the technology has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the technology to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. The described embodiments were chosen in order to best explain the principles of the technology, its practical application, and to enable others skilled in the art to utilize the technology in various embodiments and with various modifications as are suited to the particular use contemplated. It is intended that the scope of the technology be defined by the claims.

[0263] Illustrative aspects of the disclosure include:

[0264] Aspect 1. An apparatus for airflow control, the apparatus comprising: a first inspiratory lumen that is configured to receive a first inspiratory gaseous volume and to provide the first inspiratory gaseous volume to a first portion of an airway of a patient while the first inspiratory lumen is at least partially inserted into the airway; a second inspiratory lumen that is configured to receive a second inspiratory gaseous volume and to provide the second inspiratory gaseous volume to a second portion of the airway while the second inspiratory lumen is at least partially inserted into the airway; and one or more expiratory lumens that are configured to evacuate an expiratory gaseous volume from at least one of the first portion of the airway and the second portion of the airway while the one or more expiratory lumens are at least partially inserted into the airway.

[0265] Aspect 2. The apparatus of Aspect 1, wherein the first portion of the airway includes a first lung, wherein the second portion of the airway includes a second lung distinct from the first lung.

[0266] Aspect 3. The apparatus of Aspect 2, wherein the first inspiratory lumen is configured to provide the first inspiratory gaseous volume to a first lobe of the first lung, wherein the one or more expiratory lumens are configured to evacuate the expiratory gaseous volume from a second lobe of the first lung, wherein the first lobe is different than the second lobe.

[0267] Aspect 4. The apparatus of any of Aspects 1 to 3, wherein the first portion of the airway includes a first bronchus, wherein the second portion of the airway includes a second bronchus distinct from the first bronchus.

[0268] Aspect 5. The apparatus of any of Aspects 1 to 4, wherein the first inspiratory lumen receives the first inspiratory gaseous volume from a first gas source, and wherein second inspiratory lumen receives the second inspiratory gaseous volume from the first gas source.

[0269] Aspect 6. The apparatus of any of Aspects 1 to 5, wherein the first inspiratory lumen receives the first inspiratory gaseous volume from a first gas source, and wherein second inspiratory lumen receives

the second inspiratory gaseous volume from a second gas source.

[0270] Aspect 7. The apparatus of any of Aspects 1 to 6, wherein the first inspiratory gaseous volume and the second inspiratory gaseous volume both include an inspiratory mixture of a plurality of gases that are mixed according to one or more predetermined ratios.

[0271] Aspect 8. The apparatus of Aspect 7, wherein the inspiratory mixture includes carbon dioxide.

[0272] Aspect 9. The apparatus of any of Aspects 1 to 8, further comprising an endotracheal tube, wherein the endotracheal tube includes at least the first inspiratory lumen, the second inspiratory lumen, and the one or more expiratory lumens.

[0273] Aspect 10. The apparatus of Aspect 9, wherein the first inspiratory lumen passes through the endotracheal tube and extends beyond a tip of the endotracheal tube toward the first portion of the airway, wherein the second inspiratory lumen passes through the endotracheal tube and extends beyond the tip of the endotracheal tube toward the second portion of the airway.

[0274] Aspect 11. The apparatus of Aspect 10, wherein the tip of the endotracheal tube includes the tip of the one or more expiratory lumens.

[0275] Aspect 12. The apparatus of any of Aspects 1 to 11, wherein the one or more expiratory lumens include a first expiratory lumen configured to evacuate a first expiratory gaseous volume from the first portion of the airway and a second expiratory lumen configured to evacuate a second expiratory gaseous volume from the second portion of the airway.

[0276] Aspect 13. The apparatus of Aspect 12, wherein the first expiratory lumen passes through an endotracheal tube and extends beyond a tip of the endotracheal tube toward the first portion of the airway, wherein the second expiratory lumen passes through the endotracheal tube and extends beyond the tip of the endotracheal tube toward the second portion of the airway.

[0277] Aspect 14. The apparatus of any of Aspects 12 to 13, further comprising: a first expiratory mixture pressurizer that provides suction to evacuate the first expiratory gaseous volume from the first portion of the airway through the first expiratory lumen and a second expiratory mixture pressurizer that provides suction to evacuate the second expiratory gaseous volume from the second portion of the airway through the second expiratory lumen.

[0278] Aspect 15. The apparatus of any of Aspects 12 to 14, wherein the one or more expiratory lumens also include a third expiratory lumen configured to evacuate a third expiratory gaseous volume from a third portion of the airway.

[0279] Aspect 16. The apparatus of any of Aspects 1 to 15, further comprising: one or more inspiratory flow control mechanisms that control flow of the first inspiratory gaseous volume to the first portion of the airway through the first inspiratory lumen and that control flow of second inspiratory gaseous volume to the second portion of the airway through the second inspiratory lumen.

[0280] Aspect 17. The apparatus of any of Aspects 1 to 16, further comprising: one or more expiratory flow control mechanisms that provide pressurized suction to control flow of the expiratory gaseous volume from at least one of the first portion of the airway and the second portion of the airway to an expiratory air output through the one or more expiratory lumens.

[0281] Aspect 18. The apparatus of Aspect 17, further comprising: one or more inspiratory flow control mechanisms that provide the first inspiratory gaseous volume to the first inspiratory lumen and that provide the second inspiratory gaseous volume to the second inspiratory lumen; a memory storing instructions; and a processor that executes the instructions, wherein execution of the instructions by the processor causes the processor to: maintain net inspiratory flow at a first level during a first portion of

each of a plurality of respiratory cycles, wherein the net inspiratory flow corresponds to provision of both the first inspiratory gaseous volume and the second inspiratory gaseous volume, and maintain net expiratory flow at a second level during the first portion of each of the plurality of respiratory cycles, wherein the net expiratory flow corresponds to provision of pressurized suction to control flow of the expiratory gaseous volume.

[0282] Aspect 19. The apparatus of Aspect 18, wherein the first portion of each of the plurality of respiratory cycles is an inspiration, and wherein an absolute value of the net inspiratory flow is greater than an absolute value of the net expiratory flow.

[0283] Aspect 20. The apparatus of Aspect 18, wherein the first portion of each of the plurality of respiratory cycles is an expiration, and wherein an absolute value of the net inspiratory flow is less than an absolute value of the net expiratory flow.

[0284] Aspect 21. The apparatus of Aspect 18, wherein the first portion of each of the plurality of respiratory cycles is a hold, and wherein an absolute value of the net inspiratory flow is equal to an absolute value of the net expiratory flow.

[0285] Aspect 22. The apparatus of any of Aspects 1 to 21, further comprising: an intratracheal sensor that measures an intratracheal pressure in a trachea of the patient; and one or more pressurizers, wherein the one or more pressurizers are configured to provide airflow pressure based on the intratracheal pressure, wherein the airflow pressure includes at least one of a first inspiratory pressure to provide the first inspiratory gaseous volume to the first portion of the airway via the first inspiratory lumen, a second inspiratory pressure to provide the second inspiratory gaseous volume to the second portion of the airway via the second inspiratory lumen, and an expiratory pressure to evacuate the expiratory gaseous volume from at least one of the first portion of the airway and the second portion of the airway via the one or more expiratory lumens.

[0286] Aspect 23. The apparatus of any of Aspects 1 to 22, further comprising: one or more markers along at least one of the first inspiratory lumen, the second inspiratory lumen, and the one or more expiratory lumens, wherein the one or more markers are at least one of radiopaque, radioactive, emissive of a magnetic field, and emissive of one or more electromagnetic signals.

[0287] Aspect 24. The apparatus of any of Aspects 1 to 23, further comprising: a third inspiratory lumen that is configured to receive a third inspiratory gaseous volume and to provide the third inspiratory gaseous volume to a third portion of the airway while the third inspiratory lumen is at least partially inserted into the airway.

[0288] Aspect 25. The apparatus of any of Aspects 1 to 24, further comprising: a microfilter adapter that includes a microfilter medium and one or more one-way airflow valves, wherein the microfilter adapter passes airflow through the one or more one-way airflow valves and filters the airflow through the microfilter medium, wherein the airflow includes at least one of the first inspiratory gaseous volume, the second inspiratory gaseous volume, and the expiratory gaseous volume.

[0289] Aspect 26. A method for airflow control, the method comprising: receiving a first inspiratory gaseous volume into a first inspiratory lumen; providing the first inspiratory gaseous volume to a first portion of an airway using the first inspiratory lumen while the first inspiratory lumen is at least partially inserted into the airway of a patient; receiving a second inspiratory gaseous volume into a second inspiratory lumen; providing the second inspiratory gaseous volume to a second portion of the airway using the second inspiratory lumen while the second inspiratory lumen is at least partially inserted into the airway; and evacuating an expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens while the one or more expiratory lumens are at least partially inserted into the airway.

[0290] Aspect 27. The method of Aspect 26, wherein the first portion of the airway includes a first lung, wherein the second portion of the airway includes a second lung distinct from the first lung.

[0291] Aspect 28. The method of Aspect 27, wherein providing the first inspiratory gaseous volume using the first inspiratory lumen includes providing the first inspiratory gaseous volume to the a first lobe of the first lung using the first inspiratory lumen, wherein evacuating the expiratory gaseous volume using one or more expiratory lumens includes evacuating the expiratory gaseous volume from a second lobe of the first lung using one or more expiratory lumens, wherein the first lobe is different than the second lobe.

[0292] Aspect 29. The method of any of Aspects 26 to 28, wherein the first portion of the airway includes a first bronchus, wherein the second portion of the airway includes a second bronchus distinct or from the first bronchus.

[0293] Aspect 30. The method of any of Aspects 26 to 29, wherein receiving the first inspiratory gaseous volume into the first inspiratory lumen includes receiving the first inspiratory gaseous volume into the first inspiratory lumen from a first gas source, wherein receiving the second inspiratory gaseous volume into the second inspiratory lumen includes receiving the second inspiratory gaseous volume into the second inspiratory lumen from the first gas source.

[0294] Aspect 31. The method of any of Aspects 26 to 30, wherein receiving the first inspiratory gaseous volume into the first inspiratory lumen includes receiving the first inspiratory gaseous volume into the first inspiratory lumen from a first gas source, wherein receiving the second inspiratory gaseous volume into the second inspiratory lumen includes receiving the second inspiratory gaseous volume into the second inspiratory lumen from a second gas source.

[0295] Aspect 32. The method of any of Aspects 26 to 31, further comprising: mixing a plurality of gases into an inspiratory mixture according to one or more predetermined ratios, wherein the first inspiratory gaseous volume and the second inspiratory gaseous volume both include the inspiratory mixture.

[0296] Aspect 33. The method of Aspect 32, wherein the inspiratory mixture includes carbon dioxide.

[0297] Aspect 34. The method of any of Aspects 26 to 33, wherein an endotracheal tube includes at least the first inspiratory lumen, the second inspiratory lumen, and the one or more expiratory lumens.

[0298] Aspect 35. The method of Aspect 34, wherein the first inspiratory lumen passes through the endotracheal tube and extends beyond a tip of the endotracheal tube toward the first portion of the airway, wherein the second inspiratory lumen passes through the endotracheal tube and extends beyond the tip of the endotracheal tube toward the second portion of the airway.

[0299] Aspect 36. The method of Aspect 35, wherein the tip of the endotracheal tube includes the tip of the one or more expiratory lumens.

[0300] Aspect 37. The method of any of Aspects 26 to 36, wherein the one or more expiratory lumens include a first expiratory lumen and a second expiratory lumen, wherein evacuating the expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens includes evacuating a first portion of the expiratory gaseous volume from the first portion of the airway using the first expiratory lumen and evacuating a second portion of the expiratory gaseous volume from the second portion of the airway using the second expiratory lumen.

[0301] Aspect 38. The method of Aspect 37, wherein the first expiratory lumen passes through an endotracheal tube and extends beyond a tip of the endotracheal tube toward the first portion of the airway, wherein the second expiratory lumen passes through the endotracheal tube and extends beyond the tip of the endotracheal tube toward the second portion of the airway.

[0302] Aspect 39. The method of any of Aspects 37 to 38, further comprising: providing primary suction, using a first expiratory mixture pressurizer, to evacuate the first expiratory gaseous volume from the first portion of the airway through the first expiratory lumen; and providing secondary suction, using a second expiratory mixture pressurizer, to evacuate the second expiratory gaseous volume from the second portion of the airway through the second expiratory lumen.

[0303] Aspect 40. The method of any of Aspects 37 to 39, further comprising: evacuating a third expiratory gaseous volume from a third portion of the airway using a third expiratory lumens while the third expiratory lumen is at least partially inserted into the airway, wherein the one or more expiratory lumens also include the third expiratory lumen.

[0304] Aspect 41. The method of any of Aspects 26 to 40, further comprising: controlling flow, of the first inspiratory gaseous volume to the first portion of the airway through the first inspiratory lumen and of the second inspiratory gaseous volume to the second portion of the airway through the second inspiratory lumen.

[0305] Aspect 42. The method of any of Aspects 26 to 41, further comprising: providing pressurized suction, using one or more expiratory flow control mechanisms, to control flow of the expiratory gaseous volume from at least one of the first portion of the airway and the second portion of the airway to an expiratory air output through the one or more expiratory lumens.

[0306] Aspect 43. The method of Aspect 42, further comprising: maintaining net inspiratory flow at a first level during a first portion of each of a plurality of respiratory cycles, wherein the net inspiratory flow corresponds to provision of both the first inspiratory gaseous volume and the second inspiratory gaseous volume using one or more inspiratory flow control mechanisms, and maintaining net expiratory flow at a second level during the first portion of each of the plurality of respiratory cycles, wherein the net expiratory flow corresponds to provision of the pressurized suction to control the flow of the expiratory gaseous volume using the one or more expiratory flow control mechanisms.

[0307] Aspect 44. The method of Aspect 43, wherein the first portion of each of the plurality of respiratory cycles is an inspiration, and wherein an absolute value of the net inspiratory flow is greater than an absolute value of the net expiratory flow.

[0308] Aspect 45. The method of Aspect 43, wherein the first portion of each of the plurality of respiratory cycles is an expiration, and wherein an absolute value of the net inspiratory flow is less than an absolute value of the net expiratory flow.

[0309] Aspect 46. The method of Aspect 43, wherein the first portion of each of the plurality of respiratory cycles is a hold, and wherein an absolute value of the net inspiratory flow is equal to an absolute value of the net expiratory flow.

[0310] Aspect 47. The method of any of Aspects 26 to 46, further comprising: measuring an intratracheal pressure in a trachea of the patient using an intratracheal sensor; and provide airflow pressure using one or more pressurizers based on the intratracheal pressure, wherein the airflow pressure includes at least one of a first inspiratory pressure to provide the first inspiratory gaseous volume to the first portion of the airway via the first inspiratory lumen, a second inspiratory pressure to provide the second inspiratory gaseous volume to the second portion of the airway via the second inspiratory lumen, and an expiratory pressure to evacuate the expiratory gaseous volume from at least one of the first portion of the airway and the second portion of the airway via the one or more expiratory lumens.

[0311] Aspect 48. The method of any of Aspects 26 to 47, wherein one or more markers are included along at least one of the first inspiratory lumen, the second inspiratory lumen, and the one or more expiratory lumens, wherein the one or more markers are at least one of radiopaque, radioactive, emissive of a magnetic field, and emissive of one or more electromagnetic signals.

[0312] Aspect 49. The method of any of Aspects 26 to 48, further comprising: receiving a third inspiratory gaseous volume into a third inspiratory lumen; providing the third inspiratory gaseous volume to a third portion of an airway using the third inspiratory lumen while the third inspiratory lumen is at least partially inserted into the airway.

[0313] Aspect 50. The method of any of Aspects 26 to 49, further comprising: filtering airflow at least in part by passing airflow through one or more one-way airflow valves of a microfilter adapter and through a microfilter medium of the microfilter adapter, wherein the airflow includes at least one of the first inspiratory gaseous volume, the second inspiratory gaseous volume, and the expiratory gaseous volume.

[0314] Aspect 51: A non-transitory computer-readable medium having stored thereon instructions that, when executed by one or more processors, cause the one or more processors to: receive a first inspiratory gaseous volume into a first inspiratory lumen; provide the first inspiratory gaseous volume to a first portion of an airway of a patient using the first inspiratory lumen while the first inspiratory lumen is at least partially inserted into the airway; receive a second inspiratory gaseous volume into a second inspiratory lumen; provide the second inspiratory gaseous volume to a second portion of the airway using the second inspiratory lumen while the second inspiratory lumen is at least partially inserted into the airway; and evacuate an expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens while the one or more expiratory lumens are at least partially inserted into the airway.

[0315] Aspect 52: The non-transitory computer-readable medium of Aspect 51, further comprising any of Aspects 26 to 50.

[0316] Aspect 53: An apparatus for airflow control, the apparatus comprising: means for receiving a first inspiratory gaseous volume into a first inspiratory lumen; means for providing the first inspiratory gaseous volume to a first portion of an airway using the first inspiratory lumen while the first inspiratory lumen is at least partially inserted into the airway of a patient; means for receiving a second inspiratory gaseous volume into a second inspiratory lumen; means for providing the second inspiratory gaseous volume to a second portion of the airway using the second inspiratory lumen while the second inspiratory lumen is at least partially inserted into the airway; and means for evacuating an expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens while the one or more expiratory lumens are at least partially inserted into the airway.

[0317] Aspect 54: The apparatus of Aspect 54, further comprising means for performing any of the operations of any of Aspects 26 to 50.

Claims

1. An apparatus for airflow control, the apparatus comprising: a first inspiratory lumen that is configured to receive a first inspiratory gaseous volume and to provide the first inspiratory gaseous volume to a first portion of an airway of a patient while the first inspiratory lumen is at least partially inserted into the airway; a second inspiratory lumen that is configured to receive a second inspiratory gaseous volume and to provide the second inspiratory gaseous volume to a second portion of the airway while the second inspiratory lumen is at least partially inserted into the airway; and one or more expiratory lumens that are configured to evacuate an expiratory gaseous volume from at least one of the first portion of the airway and the second portion of the airway while the one or more expiratory lumens are at least partially inserted into the airway.

2. The apparatus of claim 1, wherein the first portion of the airway includes a first lung, wherein the second portion of the airway includes a second lung distinct from the first lung.

3. The apparatus of claim 2, wherein the first inspiratory lumen is configured to provide the first inspiratory gaseous volume to a first lobe of the first lung, wherein the one or more expiratory lumens are configured

to evacuate the expiratory gaseous volume from a second lobe of the first lung, wherein the first lobe is different than the second lobe.

4. The apparatus of claim 1, wherein the first portion of the airway includes a first bronchus, wherein the second portion of the airway includes a second bronchus distinct from the first bronchus.

5. The apparatus of claim 1, wherein the first inspiratory lumen receives the first inspiratory gaseous volume from a first gas source, and wherein second inspiratory lumen receives the second inspiratory gaseous volume from the first gas source.

6. The apparatus of claim 1, wherein the first inspiratory lumen receives the first inspiratory gaseous volume from a first gas source, and wherein second inspiratory lumen receives the second inspiratory gaseous volume from a second gas source.

7. The apparatus of claim 1, wherein the first inspiratory gaseous volume and the second inspiratory gaseous volume both include an inspiratory mixture of a plurality of gases that are mixed according to one or more predetermined ratios.

8. The apparatus of claim 7, wherein the inspiratory mixture includes carbon dioxide (CO.sub.2).

9. The apparatus of claim 1, further comprising an endotracheal tube, wherein the endotracheal tube includes at least the first inspiratory lumen, the second inspiratory lumen, and the one or more expiratory lumens.

10. The apparatus of claim 9, wherein the first inspiratory lumen passes through the endotracheal tube and extends beyond a tip of the endotracheal tube toward the first portion of the airway, wherein the second inspiratory lumen passes through the endotracheal tube and extends beyond the tip of the endotracheal tube toward the second portion of the airway.

11. The apparatus of claim 10, wherein the tip of the endotracheal tube includes the tip of the one or more expiratory lumens.

12. The apparatus of claim 1, wherein the one or more expiratory lumens include a first expiratory lumen configured to evacuate a first expiratory gaseous volume from the first portion of the airway and a second expiratory lumen configured to evacuate a second expiratory gaseous volume from the second portion of the airway.

13. The apparatus of claim 12, wherein the first expiratory lumen passes through an endotracheal tube and extends beyond a tip of the endotracheal tube toward the first portion of the airway, wherein the second expiratory lumen passes through the endotracheal tube and extends beyond the tip of the endotracheal tube toward the second portion of the airway.

14. The apparatus of claim 12, further comprising: a first expiratory mixture pressurizer that provides suction to evacuate the first expiratory gaseous volume from the first portion of the airway through the first expiratory lumen and a second expiratory mixture pressurizer that provides suction to evacuate the second expiratory gaseous volume from the second portion of the airway through the second expiratory lumen.

15. The apparatus of claim 12, wherein the one or more expiratory lumens also include a third expiratory lumen configured to evacuate a third expiratory gaseous volume from a third portion of the airway.

16. The apparatus of claim 1, further comprising: one or more inspiratory flow control mechanisms that control flow of the first inspiratory gaseous volume to the first portion of the airway through the first inspiratory lumen and that control flow of second inspiratory gaseous volume to the second portion of the airway through the second inspiratory lumen.

17. The apparatus of claim 1, further comprising: one or more expiratory flow control mechanisms that provide pressurized suction to control flow of the expiratory gaseous volume from at least one of the first portion of the airway and the second portion of the airway to an expiratory air output through the one or more expiratory lumens.

18. The apparatus of claim 17, further comprising: one or more inspiratory flow control mechanisms that provide the first inspiratory gaseous volume to the first inspiratory lumen and that provide the second inspiratory gaseous volume to the second inspiratory lumen; a memory storing instructions; and a processor that executes the instructions, wherein execution of the instructions by the processor causes the processor to: maintain net inspiratory flow at a first level during a first portion of each of a plurality of respiratory cycles, wherein the net inspiratory flow corresponds to provision of both the first inspiratory gaseous volume and the second inspiratory gaseous volume, and maintain net expiratory flow at a second level during the first portion of each of the plurality of respiratory cycles, wherein the net expiratory flow corresponds to provision of the pressurized suction to control the flow of the expiratory gaseous volume.

19. The apparatus of claim 18, wherein the first portion of each of the plurality of respiratory cycles is an inspiration, and wherein an absolute value of the net inspiratory flow is greater than an absolute value of the net expiratory flow.

20. The apparatus of claim 18, wherein the first portion of each of the plurality of respiratory cycles is an expiration, and wherein an absolute value of the net inspiratory flow is less than an absolute value of the net expiratory flow.

21. The apparatus of claim 18, wherein the first portion of each of the plurality of respiratory cycles is a hold, and wherein an absolute value of the net inspiratory flow is equal to an absolute value of the net expiratory flow.

22. The apparatus of claim 1, further comprising: an intratracheal sensor that measures an intratracheal pressure in a trachea of the patient; and one or more pressurizers, wherein the one or more pressurizers are configured to provide airflow pressure based on the intratracheal pressure, wherein the airflow pressure includes at least one of a first inspiratory pressure to provide the first inspiratory gaseous volume to the first portion of the airway via the first inspiratory lumen, a second inspiratory pressure to provide the second inspiratory gaseous volume to the second portion of the airway via the second inspiratory lumen, and an expiratory pressure to evacuate the expiratory gaseous volume from at least one of the first portion of the airway and the second portion of the airway via the one or more expiratory lumens.

23. The apparatus of claim 1, further comprising: one or more markers along at least one of the first inspiratory lumen, the second inspiratory lumen, and the one or more expiratory lumens, wherein the one or more markers are at least one of radiopaque, radioactive, emissive of a magnetic field, and emissive of one or more electromagnetic signals.

24. The apparatus of claim 1, further comprising: a third inspiratory lumen that is configured to receive a third inspiratory gaseous volume and to provide the third inspiratory gaseous volume to a third portion of the airway while the third inspiratory lumen is at least partially inserted into the airway.

25. The apparatus of claim 1, further comprising: a microfilter adapter that includes a microfilter medium and one or more one-way airflow valves, wherein the microfilter adapter passes airflow through the one or more one-way airflow valves and filters the airflow through the microfilter medium, wherein the airflow includes at least one of the first inspiratory gaseous volume, the second inspiratory gaseous volume, and the expiratory gaseous volume.

26. A method for airflow control, the method comprising: receiving a first inspiratory gaseous volume into a first inspiratory lumen; providing the first inspiratory gaseous volume to a first portion of an airway of a patient using the first inspiratory lumen while the first inspiratory lumen is at least partially inserted into the

airway; receiving a second inspiratory gaseous volume into a second inspiratory lumen; providing the second inspiratory gaseous volume to a second portion of the airway using the second inspiratory lumen while the second inspiratory lumen is at least partially inserted into the airway; and evacuating an expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens while the one or more expiratory lumens are at least partially inserted into the airway.

27. The method of claim 26, wherein the first portion of the airway includes a first lung, wherein the second portion of the airway includes a second lung distinct from the first lung.

28. The method of claim 26, wherein an endotracheal tube includes at least the first inspiratory lumen, the second inspiratory lumen, and the one or more expiratory lumens.

29. The method of claim 28, wherein the first inspiratory lumen passes through the endotracheal tube and extends beyond a tip of the endotracheal tube toward the first portion of the airway, wherein the second inspiratory lumen passes through the endotracheal tube and extends beyond the tip of the endotracheal tube toward the second portion of the airway.

30. The method of claim 26, wherein the one or more expiratory lumens include a first expiratory lumen and a second expiratory lumen, wherein evacuating the expiratory gaseous volume from the first portion of the airway and from the second portion of the airway using one or more expiratory lumens includes evacuating a first portion of the expiratory gaseous volume from the first portion of the airway using the first expiratory lumen and evacuating a second portion of the expiratory gaseous volume from the second portion of the airway using the second expiratory lumen.